



EAGLE

PAN TILT SYSTEMS



EAGLE™ PT-TSC2 CONTROLLER

Eagle™ system compatible

Windows® XP based software

Convenient desktop form factor

Proportional digital joystick for control of pan tilt direction and focus functions; rocker for zoom control

Backlit 15" color LCD touch screen, with user adjustable angle and contrast

Integrates both pan-tilt direction, zoom / focus, and camera control into a single controller

Recall of 20 presets per head from control panel
Recall of 64 presets per head from touch screen

Universal camera control screens allow bi-directional control of various Hitachi cameras

Use of Windows® XP operating system allows easy future software upgrades from Eagle website

Can control up to 32 pan tilt heads on one RS-485 control chain

DB-9 type connector on rear allows for simple connection of RS-485 control line

All needed connectors are included

Includes transformer power supply


The EAGLE™ PT-TSC2 integrated pan-tilt and camera controller is a multi-faceted control unit. It allows the user to control up to 32 different EAGLE™ pan tilt heads, from one controller, with no added equipment or accessories. A backlit 15" color LCD touch screen in conjunction with the desktop control panel provides complete control of all pan-tilt, lens, and camera functions. A video preview window allows the user complete control of preset creation and selection, as well as setting up shots in live mode. Remote camera setup is also accomplished using the video preview.

The PT-TSC's desktop case allows it to easily be integrated into new or existing control room applications. Brightness and contrast are user adjustable from a menu on the control panel. The controller uses the Windows® XP operating system, with extensive user prompts and feedback.

Multiple operating language support is built in for English, French, German, and Spanish. There is also a user customizable version to enter your own translated language control phrases.

Presets can be named for convenient recall. Serial control of video switchers can be provided via a serial control port. The integrated camera control is configured to provide a customized style of control of the Hitachi HV-D30, HV-D15AS, HV-D5W, DK-H31, and Z-3000 or 4000 series cameras*. Full bi-directional communication with many Hitachi cameras provide functionality such that when a pan-tilt head is selected, the current camera setting info is automatically updated on the PT-TSC2 screen

* Control of other camera makes and models also possible. Check with your dealer or Hitachi rep for details.



SPECIFICATIONS

Weight : about 16 pounds

15" backlit color LCD touch screen for control input and video preview

Proportional digital joystick for control of focus, and direction of pan tilt systems, rocker for zoom control

Uses RS-485 communications protocol for interference free operation

Built in Ethernet port to allow downloading of software updates from Eagle™ website

DIMENSIONS

Approx. 16.5"H x 15.0"W x 15.0"D

OPTIONAL ACCESSORIES

PT-AAM Auto answer modem, includes one PT-RSA

PT-MP-1 control multiplexer; allows up to 5 controllers on single RS-485 backbone

PT-MFA multi function adapter; provides 8 relay closures, serial device control

PT-SB shot box; provides recording and replay of pre-set moves and paths

PT-CSI; contact closure input interface box



EAGLE
PAN TILT SYSTEMS

Helping to bring your world
into focus

Distributed by Hitachi Kokusai Electric America Ltd.
150 Crossways Park Dr. Woodbury NY 11797
Call (516) 921-7200 for a dealer near you or visit
www.hitachikokusai.com or www.eaglepan tilt.com
Eagle products are designed and manufactured in the
USA by Display Devices Inc., Arvada CO 80003

Specifications and design subject to change without notice

Windows XP ® is a registered trademark of Microsoft Corporation

Preliminary specifications: subject to change without notice
03/2006