



Program Directory for NTuneMON

Version 2 Release 6

Program Number 5648-141

for Use with
VM/ESA

Document Date: September 1999

GI10-6601-00

Note!

Before using this information and the product it supports, be sure to read the general information under "Notices" on page vii.

This program directory, dated September 1999, applies to NTuneMON Version 2 Release 6 for VM (NTuneMON V2R6 VM), program number 5648-141 for the following:

COMP IDs	REL	Feature Numbers	System Name
564814101	620	5821, 5822, 6202	VM/ESA

and to all subsequent releases and modifications until otherwise indicated in new editions.

A form for reader's comments appears at the back of this publication. When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© **Copyright International Business Machines Corporation 1994, 1999. All rights reserved.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Notices	vii
Notice to Users of Online Versions of This Book	viii
Trademarks	viii
1.0 Introduction	1
2.0 Program Materials	3
2.1 Basic Machine-Readable Material	3
2.2 Optional Machine-Readable Material	4
2.3 Program Publications	4
2.3.1 Basic Program Publications	4
2.3.2 Optional Program Publications	5
2.3.3 Softcopy Publications	5
2.3.4 Publications Associated with NTuneMON V2R6 VM	5
2.4 Program Source Materials	6
2.5 Publications Useful During Installation	6
3.0 Program Support	9
3.1 Preventive Service Planning	9
3.2 Statement of Support Procedures	9
4.0 Program and Service Level Information	11
4.1 Program Level Information	11
4.2 Service Level Information	11
4.3 Cumulative Service Tape	11
5.0 Installation Requirements and Considerations	13
5.1 Hardware Requirements	13
5.2 Program Considerations	13
5.2.1 Operating System Requirements	13
5.2.2 Other Program Product Requirements	13
5.2.2.1 Programming Requirements	13
5.2.3 Machine Requirements	13
5.2.3.1 Minimum Requisites	14
5.2.3.2 Functional Requisites	14
5.2.3.3 Compatibility Requisites	14
5.2.3.3.1 NCP and SSP	14
5.2.3.3.2 VTAM	15
5.3 Program Installation/Service Considerations	16
5.4 DASD Storage and User ID Requirements	16
5.5 System Considerations	17
5.6 Special Considerations	18

6.0 Installation Instructions	19
6.1 VMSES/E Installation Process Overview	19
6.2 Plan Your Installation For NTuneMON V2R6 VM	20
6.3 Allocate Resources for Installing NTuneMON V2R6 VM	22
6.3.1 Installing NTuneMON V2R6 VM on Minidisk	23
6.3.2 Installing NTuneMON V2R6 VM in SFS Directories	23
6.4 Install NTuneMON V2R6 VM	25
6.4.1 Update Build Status Table for NTuneMON V2R6 VM	28
6.5 Place NTuneMON V2R6 VM into Production	28
6.5.1 Copy NTuneMON V2R6 VM Files Into Production	28
7.0 Service Instructions	31
7.1 VMSES/E Service Process Overview	31
7.2 Servicing NTuneMON V2R6 VM	32
7.2.1 Prepare to Receive Service	32
7.2.2 Receive the Service	34
7.2.3 Apply the Service	34
7.2.4 Update the Build Status Table	36
7.2.5 Build Serviced Objects	38
7.3 Place the New NTuneMON V2R6 VM Service Into Production	38
7.3.1 Copy the New NTuneMON V2R6 VM Serviced Files Into Production	38
Appendix A. APARs Incorporated into This Program	41
Reader's Comments	43

Figures

1. Basic Material: Program Tape	3
2. Program Tape: File Content	4
3. Basic Material: Program Publications	4
4. Optional Material: Licensed Publications	5
5. Softcopy Publications	5
6. Publications Associated with NTuneMON V2R6 VM	6
7. Publications Useful During Installation / Service on VM/ESA V2R2	6
8. Publications Useful During Installation / Service on VM/ESA V2R3 or V2R4	6
9. PSP Upgrade and Subset ID	9
10. Component IDs	9
11. APARs Required to Monitor 3746 Model 900 CSS Token-Ring Lines	14
12. APAR Required to Display Information for the Last Beaconing MAC Address.	15
13. APARs Required to Display Information for Transmission Head Buffers	15
14. VTAM APARs Required to Operate NTuneMON with NTuneNCP	15

15.	VTAM APAR Required for SDLC Lines to Modify VTAM USE Parameter	15
16.	DASD Storage Requirements for Target Minidisks for NTuneMON V2R6 VM	17

Notices

References in this publication to IBM products, programs, or services do not imply that IBM intends to make them available in all countries in which IBM operates. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any of IBM's intellectual property rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, are the user's responsibility.

APAR numbers are provided in this document to assist in locating PTFs that may be required. Ongoing problem reporting may result in additional APARs being created. Therefore, the APAR lists in this document may not be complete. To obtain current service recommendations and to identify current product service requirements, always contact the IBM Customer Support Center.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

Site Counsel
IBM Corporation
P.O. Box 12195
3039 Cornwallis
Research Triangle Park, NC 27709-2195
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement.

This document is not intended for production use and is furnished as is without any warranty of any kind, and all warranties are hereby disclaimed including the warranties of merchantability and fitness for a particular purpose.

Notice to Users of Online Versions of This Book

For online versions of this book, you are authorized to:

- Copy, modify, and print the documentation contained on the media, for use within your enterprise, provided you reproduce the copyright notice, all warning statements, and other required statements on each copy or partial copy.
- Transfer the original unaltered copy of the documentation when you transfer the related IBM product (which may be either machines you own, or programs, if the program's license terms permit a transfer). You must, at the same time, destroy all other copies of the documentation.

You are responsible for payment of any taxes, including personal property taxes, resulting from this authorization.

THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Some jurisdictions do not allow the exclusion of implied warranties, so the above exclusion may not apply to you.

Your failure to comply with the terms above terminates this authorization. Upon termination, you must destroy your machine-readable documentation.

Trademarks

The following terms are trademarks of the IBM Corporation in the United States or other countries or both:

BookManager	NTuneMON
CBIPO	NTuneNCP
CBPDO	OS/2
FunctionPac	OS/390
IBM	RETAIN
IBMLink	SystemPac
NetView	VM/ESA
NTune	VTAM

Other company, product, and service names may be trademarks or service marks of others.

1.0 Introduction

This program directory is intended for the system programmer responsible for program installation and maintenance. It contains information concerning the material and procedures associated with the installation of NTuneMON V2R6 VM. You should read all of this program directory before installing the program and then keep it for future reference.

The program directory contains the following sections:

- 2.0, "Program Materials" on page 3 identifies the basic program materials and documentation for NTuneMON V2R6 VM.
- 3.0, "Program Support" on page 9 describes the IBM support available for NTuneMON V2R6 VM.
- 4.0, "Program and Service Level Information" on page 11 lists the program and service level information incorporated into NTuneMON V2R6 VM.
- 5.0, "Installation Requirements and Considerations" on page 13 identifies the resources and considerations for installing and using NTuneMON V2R6 VM.
- 6.0, "Installation Instructions" on page 19 provides detailed installation instructions for NTuneMON V2R6 VM.
- 7.0, "Service Instructions" on page 31 provides detailed servicing instructions for NTuneMON V2R6 VM.
- Appendix A, "APARs Incorporated into This Program" on page 41 lists the APARs incorporated into NTuneMON V2R6 VM.

NTuneNCP is an optional feature offered with NTuneMON V2R6 VM. The NTuneNCP Tuning Feature can be used in conjunction with NTuneMON V2R6 VM to provide enhanced online interactive tuning capabilities.

Before installing NTuneMON V2R6 VM, read 3.1, "Preventive Service Planning" on page 9. This section tells you how to find any updates to the information and procedures in this program directory. Also, read Section 5.6, "Special Considerations" on page 18 for information on using the ATUNELST CLIST.

Prior to NTuneMON V2R4, the NTuneNCP feature was packaged on separate media. The NTuneNCP feature of NTuneMON is now fully integrated into NTuneMON. There is no separate media to order and there is no separate installation process.

The NTuneNCP feature still remains a priced feature of NTuneMON. This feature must be licensed for every NCP image (1 for each 37xx) which will be tuned.

At the end of this program directory you will find a Reader's Comment Form. Please take time to complete this form and return it to the address shown on the form. Your comments and suggestions help improve this program directory and make installation easier.

2.0 Program Materials

An IBM program is identified by a program number and a feature number. The program number for NTuneMON V2R6 VM is 5648-141.

The program announcement material describes the features supported by NTuneMON V2R6 VM. Ask your IBM representative for this information if you have not already received a copy.

The following sections identify:

- Basic and optional program materials available with this program
- Basic, optional, and associated publications available for this program
- Publications useful during installation

2.1 Basic Machine-Readable Material

This section describes the basic machine-readable material for NTuneMON V2R6 VM.

The distribution medium for this program is a 9-track magnetic tape (written at 6250 bpi), a 3480 tape cartridge, or a 4 mm cartridge. The tape or cartridge contains all programs and data needed for installation. NTuneMON V2R6 VM is installed using VMSES/E. See section 6.0, "Installation Instructions" on page 19 for more information about how to install the program.

Figure 1 describes the program tape or cartridge for the NTuneMON V2R6 VM program. Figure 2 on page 4 describes the file content of the program tape or cartridge for the NTuneMON V2R6 VM program.

Medium	Feature Number	Physical Volume	Tape Content	External Tape Label
6250 tape	5821	1	NTuneMON V2R6 VM	NTuneMON V2R6 VM
3480 cart.	5822	1	NTuneMON V2R6 VM	NTuneMON V2R6 VM
4 mm cart.	6202	1	NTuneMON V2R6 VM	NTuneMON V2R6 VM

Figure 2. Program Tape: File Content

Tape File	Content
1	Tape Header
2	Tape Header
3	Product Header
4	Product Memo
5	Service Apply Lists
6	PTFPARTs
7	NTuneMON V2R6 VM Service
8	NTuneMON V2R6 VM Service
9	NTuneMON V2R6 VM Base Code
10	NTuneMON V2R6 VM Executable Code

2.2 Optional Machine-Readable Material

NTuneNCP has been incorporated in the base code of NTuneMON V2R6 VM. No optional machine-readable materials are provided for NTuneMON V2R6 VM. Please see section 1.0, "Introduction" on page 1 for more information.

2.3 Program Publications

The following sections identify the basic, optional, and associated publications for NTuneMON V2R6 VM.

2.3.1 Basic Program Publications

Figure 3 identifies the basic program publications for NTuneMON V2R6 VM. One copy of this publication is included when you order the basic feature materials. For additional copies, contact your IBM representative.

Figure 3. Basic Material: Program Publications

Publication Title	Form Number
NTuneMON Licensed Program Specifications	GC31-6267
NTuneMON User's Guide	SC31-6266

2.3.2 Optional Program Publications

There are no *unlicensed* program publications for NTuneMON V2R6 VM.

Figure 4 identifies the optional *licensed* publications for NTuneMON V2R6 VM. The first copy is available at no charge to licensees of the basic materials by ordering the 7xxx feature number. Order additional copies using the 8xxx feature number. A fee is charged for additional copies.

An asterisk (*) beside the Form Number indicates that it contains “Restricted Materials of IBM.”

<i>Figure 4. Optional Material: Licensed Publications</i>		
Title	Form Number	Feature Number
NTuneNCP Feature Reference	LY43-0039*	7001-8008

2.3.3 Softcopy Publications

All NTuneMON V2R6 VM manuals, licensed and unlicensed, except for *NTuneMON Licensed Program Specifications*, are offered in displayable softcopy form on the media listed in Figure 5. The first copy is available at no charge to licensees of the basic materials by ordering the 7xxx feature number. Order additional copies using the 8xxx feature number. A fee is charged for additional copies.

An asterisk (*) beside the Form Number indicates that it contains “Restricted Materials of IBM”.

<i>Figure 5. Softcopy Publications</i>		
Title	Form Number	Feature Number
ACF/NCP, ACF/SSP, EP, NPSI, and NTuneMON Softcopy Collection Kit CD-ROM	LK2T-0414*	7110-8110
Note: Order this collection kit under the NCP product. (It is not orderable under NTuneMON.)		

2.3.4 Publications Associated with NTuneMON V2R6 VM

Figure 6 on page 5 identifies publications that may be helpful when you use NTuneMON V2R6 VM. To order copies, contact your IBM representative. A fee is charged for each copy of these publications.

Figure 6. Publications Associated with NTuneMON V2R6 VM

Publication Title	Order/Form Number
Network Control Program Version 7 Release 8 Migration Guide	SC30-4024
Network Control Program, System Support Programs, and Emulation Program Resource Definition Guide	SC31-6223
Network Control Program, System Support Programs, and Emulation Program Resource Definition Reference	SC31-6224
Planning for NetView, NCP, and VTAM	SC31-8063
Planning for Integrated Networks	SC31-8062

2.4 Program Source Materials

No program source materials or viewable program listings are provided for NTuneMON V2R6 VM.

2.5 Publications Useful During Installation

The publications listed in Figure 7 or Figure 8, depending on your VM/ESA release, may be useful during the installation of NTuneMON V2R6 VM. To order copies, contact your IBM representative.

Figure 7. Publications Useful During Installation / Service on VM/ESA V2R2

Publication Title	Form Number
<i>VM/ESA: VMSES/E Introduction and Reference</i>	SC24-5747
<i>VM/ESA: Service Guide</i>	SC24-5749
<i>VM/ESA: Planning and Administration</i>	SC24-5750
<i>VM/ESA: CMS Command Reference</i>	SC24-5776
<i>VM/ESA: CMS File Pool Planning, Administration, and Operation</i>	SC24-5751
<i>VM/ESA: System Messages and Codes</i>	SC24-5784

Figure 8 (Page 1 of 2). Publications Useful During Installation / Service on VM/ESA V2R3 or V2R4

Publication Title	Form Number
<i>VM/ESA: VMSES/E Introduction and Reference</i>	GC24-5837
<i>VM/ESA: Service Guide</i>	GC24-5838
<i>VM/ESA: Planning and Administration</i>	SC24-5750
<i>VM/ESA: CMS Command Reference</i>	SC24-5776

Figure 8 (Page 2 of 2). Publications Useful During Installation / Service on VM/ESA V2R3 or V2R4

Publication Title	Form Number
<i>VM/ESA: CMS File Pool Planning, Administration, and Operation</i>	SC24-5751
<i>VM/ESA: System Messages and Codes</i>	GC24-5841

3.0 Program Support

This section describes the IBM support available for NTuneMON V2R6 VM.

3.1 Preventive Service Planning

Before installing NTuneMON V2R6 VM, check with your IBM Support Center or use IBMLink (Service Link) to determine if there is additional Preventive Service Planning (PSP) information. To obtain this information, specify the following UPGRADE and SUBSET values:

Figure 9. PSP Upgrade and Subset ID

Retain			
COMPID	Release	Upgrade	Subset
564814101	620	NTM260	620

3.2 Statement of Support Procedures

Report any difficulties you have using this program to your IBM Support Center. If an APAR is required, the Support Center will provide the address to which any needed documentation can be sent.

Figure 10 identifies the component ID (COMPID), RETAIN Release, and Field Engineering Service Number (FESN) for NTuneMON V2R6 VM.

Figure 10. Component IDs

Retain			
COMPID	Release	Component Name	FESN
564814101	620	NTuneMON V2R6 VM	0402392

4.0 Program and Service Level Information

This section identifies the program and any relevant service levels of NTuneMON V2R6 VM. The program level refers to the APAR fixes incorporated into the program. The service level refers to the PTFs shipped with this program. Information about the cumulative service tape is also provided.

4.1 Program Level Information

The program level refers to the APAR fixes incorporated into NTuneMON V2R6 VM. See Appendix A, "APARs Incorporated into This Program" on page 41 for a complete listing of the APARs incorporated into this program.

4.2 Service Level Information

The service level refers to the PTFs shipped with NTuneMON V2R6 VM.

Check the NTM260 PSP bucket for any additional PTFs that should be installed or any additional install information.

4.3 Cumulative Service Tape

Cumulative service for NTuneMON V2R6 VM is available through a monthly corrective service tape, Expanded Service Option (ESO).

5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing NTuneMON V2R6 VM.

5.1 Hardware Requirements

There are no special hardware requirements for NTuneMON V2R6 VM.

5.2 Program Considerations

The following sections list the programming considerations for installing NTuneMON V2R6 VM.

5.2.1 Operating System Requirements

NTuneMON V2R6 VM supports the following VM operating systems for as long as program services are available for the particular version and release.

- VM/ESA V2R2 or later
- VMSES/E on VM/ESA V2R2 or later. Prior to installing NTuneMON V2R6 VM, **RSU9403 service level** or later must be applied.

5.2.2 Other Program Product Requirements

5.2.2.1 Programming Requirements:

A platform-dependent BookManager product is required to display softcopy publications on CD-ROM. Limited function DOS, Windows, and OS/2 versions of these products are available on your CD-ROM. For more information or to order full-function releases of these products, or VM or MVS versions, refer to the IBM BookManager home page at <http://booksrv2.raleigh.ibm.com>.

5.2.3 Machine Requirements

The target system can run in any hardware environment that supports the required software.

5.2.3.1 Minimum Requisites:

A minimum requisite is defined as one of the following:

- *Installation Requisite:* A product that is required at installation time. i.e. this product **will not install** successfully unless this requisite is met.
- *Run Time Requisite:* A product that is **not** required for the successful installation of this product, but **is** needed at run time in order for this product to work.

This program is supported in conjunction with the following licensed VM programs at the function level of the version and release for as long as program services are available for the particular version and release:

- NetView V2R3 or later, with REXX support
- NCP V7R1 or later
- NCP V6R2
- NCP V5R4
- NCP V4R3.1

5.2.3.2 Functional Requisites:

VTAM V4R2 or later is required to use the NTuneNCP.

Adding a peripheral SDLC line requires the following with their associated prerequisites:

- NCP V7R3 or later
- NTuneNCP

5.2.3.3 Compatibility Requisites:

The following sections describe cross product service considerations for NCP, SSP, and VTAM.

5.2.3.3.1 NCP and SSP:

The APARs listed in Figure 11 are required in order for NTuneMON to monitor 3746 Model 900 Connectivity Subsystem (CSS) token-ring lines.

Product Name	APAR
NCP V6R2	IR99864
SSP V3R8	IR22686

The APAR listed in Figure 12 is required in order for NTuneMON to display the time and date stamp for the last beaconing MAC address.

<i>Figure 12. APAR Required to Display Information for the Last Beaconing MAC Address.</i>	
Product Name	APAR
NCP V7R6	IR36907

The APARs listed in Figure 13 are required in order for NTuneMON to display and tune the number of transmission head buffers allocated for 3745 frame-relay physical lines.

<i>Figure 13. APARs Required to Display Information for Transmission Head Buffers</i>	
Product Name	APAR
NCP V7R6	IR36886
SSP V4R6 OS/390	IR36896
SSP V4R6 VM	IR36902
SSP V4R6 VSE	IR36903

5.2.3.3.2 VTAM:

The VTAM APARs listed in Figure 14 are required to operate NTuneMON in conjunction with NTuneNCP.

<i>Figure 14. VTAM APARs Required to Operate NTuneMON with NTuneNCP</i>	
Product Name	APAR
VTAM V3R4.2 for MVS/ESA	OW01987
VTAM V3R4.1 for MVS/ESA	OW06097
VTAM V3R4.2 for MVS/ESA	OW06755

The VTAM APAR listed in Figure 15 is required if you use spare or redefinable SDLC peripheral lines and want to modify the VTAM USE parameter.

<i>Figure 15. VTAM APAR Required for SDLC Lines to Modify VTAM USE Parameter</i>	
Product Name	APAR
VTAM V4R2 for MVS/ESA	OW06708

5.3 Program Installation/Service Considerations

This section describes items that should be considered before you install or service NTuneMON V2R6 VM.

- VMSES/E is required to install and service this product.
- If multiple users install and maintain licensed products on your system, there might be a problem getting the necessary access to MAINT's 51D disk. If you find there is contention for write access to the 51D disk, you can eliminate it by converting the Software Inventory from minidisk to Shared File System (SFS). Refer to *VMSES/E Introduction and Reference*, "Changing the Software Inventory to an SFS Directory" section, for information about how to make this change.
- Customers will no longer install and service NTuneMON V2R6 VM strictly using the MAINT user ID, but will use a new user ID, P648141J. This is the IBM suggested user ID name. You are free to change this to any user ID name you wish; however, a PPF override must be created.

Note: It might be easier to make the changes during the installation procedure 6.2, "Plan Your Installation For NTuneMON V2R6 VM," step 6 on page 21, than after you have installed this product.

5.4 DASD Storage and User ID Requirements

Figure 16 on page 17 lists the user IDs and minidisks that are used to install and service NTuneMON V2R6 VM.

Important Installation Notes:

- For NTuneMON, user IDs and minidisks or SFS directories will be defined in section 6.2, "Plan Your Installation For NTuneMON V2R6 VM" on page 20 and are listed here so that you can get an idea of the resources that you will need prior to allocating them.
- For NTuneMON, P648141J is a default user ID and can be changed. If you choose to change the name of the installation user ID, you need to create a Product Parameter Override (PPF) to change the name. This is explained in section 6.2, "Plan Your Installation For NTuneMON V2R6 VM," step 6 on page 21 .

Note: If you choose to install NTuneMON V2R6 VM on a common user ID, the default minidisk addresses for NTuneMON V2R6 VM might already be defined. If any of the default minidisks required by NTuneMON V2R6 VM are already in use, you have to create an override to change the default minidisks for NTuneMON V2R6 VM so they are unique.

Figure 16. DASD Storage Requirements for Target Minidisks for NTuneMON V2R6 VM

Minidisk owner (user ID)	Default Address	Storage in Cylinders		FB-512 Blocks	SFS 4-K Blocks	Usage
		DASD	CYLS			Default SFS Directory Name
P648141J	2B2	3390 3380 9345	16 20 20	24000	3000	Contains all the base code shipped with NTuneMON V2R6 VM VMSYS:P648141J.ATF.OBJECT
P648141J	2C2	3390 3380 9345	4 5 5	6000	750	Contains customization files. This disk may also be used for local modifications. VMSYS:P648141J.ATF.LOCAL
P648141J	2D2	3390 3380 9345	32 40 40	48000	6000	Contains serviced files VMSYS:P648141J.ATF.DELTA
P648141J	2A6	3390 3380 9345	8 10 10	12000	1500	Contains AUX files and software inventory tables that represent the test service level of NTuneMON V2R6 VM VMSYS:P648141J.ATF.APPLYALT
P648141J	2A2	3390 3380 9345	8 10 10	12000	1500	Contains AUX files and software inventory tables that represent the service level of NTuneMON V2R6 VM that is currently in production. VMSYS:P648141J.ATF.APPLYPRD
P648141J	400	3390 3380 9345	25 30 30	36000	4500	Test BUILD disk. This code will be copied to a production disk. VMSYS:P648141J.ATF.TRUN
P648141J	401	3390 3380 9345	25 30 30	36000	4500	Production BUILD disk. Files from the test BUILD disk are copied here for application use. VMSYS:P648141J.ATF.RUN
P648141J	191	3390 3380 9345	25 30 30	36000	4500	P648141J user ID's 191 minidisk VMSYS:P648141J.

Note: Cylinder values defined in this table are based on a 4-K block size. FB-512 block and SFS values are derived from the 3380 cylinder values in this table. The FBA blocks are listed as 1/2-K but should be CMS formatted at 1-K size. 26250 4-K blocks are needed for SFS install.

5.5 System Considerations

There are no system considerations for NTuneMON V2R6 VM.

5.6 Special Considerations

Following are special considerations for NTuneMON V2R6 VM:

- The **ATUNELST NCCFLST** file provided with NTuneMON must be installed. It contains the default values for various NTuneMON parameters and threshold values.

You should make a working copy of the ATUNELST file and save the original as backup. Make all your changes to the working copy. If a problem arises, you still have the original ATUNELST file. It is also recommended that you test your changes before making them permanent.

There is a section in ATUNELST that indicates that no changes should be made below a certain point. If you change anything below this point, you might affect the operation of NTuneMON.

ATUNELST allows you to preset the NTuneMON threshold values. For additional information, refer to the *NTuneMON User's Guide*.

- Because NTuneMON uses colors to highlight certain panel fields, you should use a color terminal to take full advantage of the information NTuneMON provides.

In addition, NetView V2R2 users should maximize the amount of virtual memory available to NetView. This may require movement of shared segments. Refer to the *NetView Tuning Guide* for additional guidance on conserving virtual storage for large applications.

6.0 Installation Instructions

This section describes the installation methods and the step-by-step procedures to install NTuneMON V2R6 VM.

The step-by-step procedures are in two column format. The steps to be performed are in bold large numbers. Commands for these steps are on the left hand side of the page in bold print. Additional information for a command may exist to the right of the command. For more information about the two column format refer to “Understanding Dialogs with the System” in *VM/ESA Installation Guide*.

Each step of the installation instructions must be followed. Do not skip any step unless directed otherwise.

Throughout these instructions, the use of IBM-supplied default minidisk addresses and user IDs is assumed. If you use different user IDs, minidisk addresses, or SFS directories to install NTuneMON V2R6 VM, adapt these instructions as needed for your environment.

Note!

The sample console output presented throughout these instructions was produced on a VM/ESA R2.2.0 system. If you are installing NTuneMON V2R6 VM on a different VM/ESA system, the results obtained for some commands may differ from those depicted here.

6.1 VMSES/E Installation Process Overview

The following is a brief description of the main steps in installing NTuneMON V2R6 VM using VMSES/E.

- Plan Your Installation

Use the VMFINS command to load several VMSES/E files from the product tape and to obtain NTuneMON V2R6 VM resource requirements.

- Allocate Resources

The information obtained from the previous step is used to allocate the appropriate minidisks (or SFS directories) and user IDs needed to install and use NTuneMON V2R6 VM.

- Install the NTuneMON V2R6 VM Product

Use the VMFINS command to load the NTuneMON V2R6 VM product files from tape to the test BUILD and BASE minidisks/directories. VMFINS is used to update the VM SYSBLDS file used by VMSES/E for software inventory management.

- Place NTuneMON V2R6 VM Files into Production

Once the product files have been installed and the operation of NTuneMON V2R6 VM is satisfactory, the product files are copied from the test BUILD disk to the production BUILD disk.

For a complete description of all VMSES/E installation options, refer to *VMSES/E Introduction and Reference*.

6.2 Plan Your Installation For NTuneMON V2R6 VM

The VMFINS command will be used to plan the installation. This section has 2 main steps that will:

- load the first tape file, containing installation files
- generate a “PLANINFO” file listing
 - all user ID and minidisk/SFS directory requirements
 - required products

To obtain planning information for your environment:

- 1** Log on as NTuneMON V2R6 VM installation planner.
This user ID can be any ID that has read access to MAINT’s 5E5 minidisk and write access to MAINT’s 51D minidisk.
- 2** Mount the NTuneMON V2R6 VM installation tape and attach it to user ID at virtual address 181. The VMFINS EXEC requires the tape drive to be at virtual address 181.
- 3** Establish read access to the VMSES/E code.

**link MAINT 5e5 5e5 rr
access 5e5 b**

The MAINT 5E5 disk contains the VMSES/E code.

- 4** Establish write access to the Software Inventory disk.

**link MAINT 51d 51d mr
access 51d d**

The MAINT 51D disk is where the VMSES/E system-level Software Inventory and other dependent files reside.

Note: If another user already has the MAINT 51D minidisk linked in write mode (R/W), you only obtain read access (R/O) to this minidisk. If this occurs, you need to have that user re-link the 51D in read-only mode (RR), and re-issue the above LINK and ACCESS commands. Do not continue with these procedures until a R/W link is established to the 51D minidisk.

- 5** Load the NTuneMON V2R6 VM product control files to the 51D minidisk.

vmfins install info (nomemo)

The NOMEMO option will load the memos from the tape but will not issue a prompt to send them to the system printer. Specify the MEMO option if you want to be prompted for printing the memo.

This command will perform the following:

- load Memo-to-Users
- load various product control files, including the Product Parameter File (PPF) and the PRODPART files
- create VMFINS PRODLIST on your A-disk. The VMFINS PRODLIST contains a list of products on the installation tape.

```
VMFINS2760I VMFINS processing started
VMFINS1909I VMFINS PRODLIST created on your A-disk
VMFINS2760I VMFINS processing completed successfully
Ready;
```

6 Obtain resource planning information for NTuneMON V2R6 VM.

Note: The product will **not** be loaded by the VMFINS command at this time.

vmfins install ppf 5648141J {NTUNEMON | NTUNEMONSFS} (plan nomemo)

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

The PLAN option indicates that VMFINS will perform requisite checking, plan system resources, and provide an opportunity to override the defaults in the product parameter file.

You can override any of the following:

- the name of the product parameter file
- the default user IDs
- minidisk/directory definitions

Notes:

- a. If you change the PPF name, a default user ID, or other parameters via a PPF override, you need to use your changed values instead of those indicated (when appropriate), throughout the rest of the installation instructions, as well as the instructions for servicing NTuneMON V2R6 VM. For example, you need to specify your PPF override file name instead of 5648141J for certain VMSES/E commands.
- b. If you are not familiar with creating PPF overrides using VMFINS, you should review the “Using the Make Override Panel” section in the *VMSES/E Introduction and Reference* before you continue.
- c. For more information about changing the VMSYS file pool name, refer to the *VMSES/E Introduction and Reference*.

```
VMFINS2760I VMFINS processing started
VMFREQ2805I Product 5648141J component NTuneMON passed requisite checking
Do you want to create an override for 5648141J NTuneMON (prodid 5648141J)?
Enter 0 (No), 1 (Yes) or 2 (Exit)
0
VMFRMT2760I VMFRMT processing started
VMFRMT2760I VMFRMT processing completed successfully
VMFPLA1909I 5648141J PLANINFO created on your A-disk
VMFINS2760I VMFINS processing completed successfully
```

- 7** Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview install

6.3 Allocate Resources for Installing NTuneMON V2R6 VM

Use the planning information in the 5648141J PLANINFO file, created in the **PLAN** step, to:

- Create the P648141J user directory for minidisk install
- OR**
- Create the P648141J user directory for SFS install

6.3.1 Installing NTuneMON V2R6 VM on Minidisk

- 1 Obtain the user directory from the 5648141J PLANINFO file.

Note: The user directory entry is located at the bottom of the PLANINFO file of the resource section; these entries will contain all the links and privilege classes necessary for the P648141J user ID. Use the directory entry found in PLANINFO as a model for input to your system directory.

- 2 Add the MDISK statements to the directory entry for P648141J. Use Figure 16 on page 17 to obtain the minidisk requirements.

- 3 If you are installing NTuneMON V2R6 VM on a VM/ESA 370 system, the following directory entry change must be made:

- For the P648141J directory entry:
 - Change the user ID storage from 24M to 16M.
 - Comment out or remove the MACHINE XA statement from the directory entry.

- 4 Add the P648141J directory to the system directory. Change the password for P648141J from xxxxx to a valid password, in accordance with your security guidelines.

- 5 Place the new directories on-line using VM/Directory Maintenance (DIRMAINT) or an equivalent CP directory maintenance method.

Note

All minidisks for the P648141J user ID must be formatted before installing NTuneMON V2R6 VM.

6.3.2 Installing NTuneMON V2R6 VM in SFS Directories

- 1 Obtain the user directory from the 5648141J PLANINFO file.

Note: The user directory entry is located at the bottom of the PLANINFO file of the resource section; these entries contain all of the links and privilege classes necessary for the P648141J user ID. Use the directory entry found in PLANINFO as a model for input to your system directory.

- 2 If you are installing NTuneMON V2R6 VM on a VM/ESA 370 Feature system, the following directory entry change must be made:

- For the P648141J directory entry:
 - Change the user ID storage from 24M to 16M.

- Comment out or remove the MACHINE XA statement from the directory entry.
- 3** Add the P648141J directory to the system directory. Change the password for P648141J from xxxxx to a valid password, in accordance with your security guidelines.
- 4** Place the new directories on-line using VM/Directory Maintenance (DIRMAINT) or an equivalent CP directory maintenance method.
- 5** An SFS install also requires the following steps:
 - a** Determine the number of 4K blocks that are required for SFS directories by adding up the 4K blocks required for each SFS directory you plan to use.

If you intend to use all the default NTuneMON V2R6 VM SFS directories, the 4K block requirements for each NTuneMON V2R6 VM are summarized in Figure 16 on page 17.

This information is used when enrolling the P648141J to the VMSYS filepool.
 - b** Enroll user P648141J in the VMSYS filepool using the ENROLL USER command:

```
ENROLL USER P648141J VMSYS: (BLOCKS blocks
```

where *blocks* is the number of 4K blocks that you calculated in the previous step.

Note: This must be done from a user ID that is an administrator for VMSYS: filepool.
 - c** Determine if there are enough blocks available in the filepool to install NTuneMON V2R6 VM. This information can be obtained from the QUERY FILEPOOL STATUS command. Near the end of the output from this command is a list of minidisks in the filepool and the number of blocks free. If the number of blocks free is smaller than the total 4K blocks needed to install NTuneMON V2R6 VM, you need to add space to the filepool. Refer to *VM/ESA SFS/CRR Planning, Administration, and Operation* for information about adding space to a filepool.
 - d** Create the necessary subdirectories listed in the 5648141J PLANINFO file using the CREATE DIRECTORY command.

set filepool vmsys:
create directory *dirid*

dirid is the name of the SFS directory you're creating, such as:

```
create directory vmsys:P648141J.NTUNEMON  
create directory vmsys:P648141J.NTUNEMON.object
```

If necessary, refer to *VM/ESA CMS Command Reference* for more information about the CREATE DIRECTORY command.

A complete list of default NTuneMON SFS directories is provided in Figure 16 on page 17.

- e** If you intend to use an SFS directory as the work space for the P648141J user ID, include the following IPL control statement in the P648141J directory entry:

```
IPL CMS PARM FILEPOOL VMSYS
```

This will cause CMS to automatically access the P648141J's top directory as file mode A.

6.4 Install NTuneMON V2R6 VM

The *ppfname* used throughout these installation instructions is **5648141J**, which assumes you are using the PPF supplied by IBM for NTuneMON V2R6 VM. If you have your own PPF override file for NTuneMON V2R6 VM, you should use your file's *ppfname* instead of **5648141J**. The *ppfname* you use should be used **throughout** the rest of this procedure.

- 1** Log on to the installation user ID **P648141J**.
- 2** Create a PROFILE EXEC that will contain the ACCESS commands for MAINT 5E5 and 51D minidisks.

```
xedit profile exec a  
====> input /**/  
====> input 'access 5e5 b'  
====> input 'access 51d d'  
====> file
```

If either 5E5 or 51D is in a shared file system (SFS) then substitute your SFS directory name in the access command.

- 3** Execute the profile to access MAINT's minidisks.

profile

- 4 Establish write access to the Software Inventory disk, if it is not already linked R/W.

Note: If the MAINT 51D minidisk was accessed R/O, you need to have the user who has it linked R/W link it as R/O. You can then issue the following commands to obtain R/W access to it.

**link MAINT 51d 51d mr
access 51d d**

- 5 Mount the NTuneMON V2R6 VM installation tape and attach it to P648141J at virtual address 181. The VMFINS EXEC requires the tape drive to be at virtual address 181.

- 6 Install NTuneMON V2R6 VM.

Note:

If you have already created a PPF override file, you should specify your override file name after the **PPF** keyword for the following VMFINS command.

You may be prompted for additional information during VMFINS INSTALL processing depending on your installation environment. If you are unsure how to respond to a prompt, refer to “Installing Products with VMFINS” and “Install Scenarios” chapters in *VMSES/E Introduction and Reference* to decide how to proceed.

vmfins install ppf 5648141J {NTUNEMON | NTUNEMONSFS} (nomemo nolink

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

The NOLINK option indicates that you do not want VMFINS to link to the appropriate minidisks, only access them if not accessed.

```

VMFINS2760I VMFINS processing started
VMFREQ2805I Product 5648141J component NTuneMON passed requisite checking
Do you want to create an override for 5648141J NTuneMON (prodid 5648141J)?
Enter 0 (No), 1 (Yes) or 2 (Exit)
0
VMFINT2760I VMFINST processing started
VMFSET2760I VMFSETUP processing started
VMFUTL2205I Minidisk|Directory Assignments:
          String      Mode  Stat  Vdev  Label/Directory
VMFUTL2205I LOCALSAM  E    R/W  2C2   SES2C2
VMFUTL2205I APPLY     F    R/W  2A6   SES2A6
VMFUTL2205I           G    R/W  2A2   SES2A2
VMFUTL2205I DELTA     H    R/W  2D2   SES2D2
VMFUTL2205I BUILD0    I    R/W  400   SES400
VMFUTL2205I BASE1     J    R/W  2B2   SES2B2
VMFUTL2205I -----  A    R/W  191   SES191
VMFUTL2205I -----  B    R/O  5E5   MNT5E5
VMFUTL2205I -----  D    R/W  51D   SES51D
VMFUTL2205I -----  S    R/O  190   MNT190
VMFUTL2205I -----  Y/S  R/O  19E   MNT19E
VMFSET2760I VMFSETUP processing completed successfully
VMFREC2760I VMFREC processing started
VMFREC1852I Volume 1 of 1 of INS TAPE 9800
VMFREC1851I (1 of 6) VMFRCAXL processing AXLIST
VMFRCX2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (2 of 6) VMFRCPTF processing PARTLST
VMFRCP2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (3 of 6) VMFRCCOM processing DELTA
VMFRCC2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (4 of 6) VMFRCALL processing APPLY
VMFRCA2159I Loading part(s) to APPLY 2A6 (F)
VMFRCA2159I Loaded 1 part(s) to APPLY 2A6 (F)
VMFREC1851I (5 of 6) VMFRCALL processing BASE
VMFRCA2159I Loading part(s) to BASE1 2B2 (J)
VMFRCA2159I Loaded 1529 part(s) to BASE1 2B2 (J)
VMFREC1851I (6 of 6) VMFRCALL processing BUILD
VMFRCA2159I Loading part(s) to BUILD0 400 (I)
VMFRCA2159I Loaded 1527 part(s) to BUILD0 400 (I)
VMFREC2760I VMFREC processing completed successfully
VMFINT2603I Product installed
VMFINS2760I VMFINS processing completed successfully

```

- 7** Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA System Messages and Codes*, or use on-line HELP.

vmfview install

6.4.1 Update Build Status Table for NTuneMON V2R6 VM

- 1 Update the VM SYSBLDS software inventory file for NTuneMON V2R6 VM.

vmfins build ppf 5648141J {NTUNEMON | NTUNEMONSFS} (serviced nolink

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

The SERVICED option will build any parts that were not built on the installation tape (if any) and update the Software Inventory build status table showing that the product 5648141J has been built.

- 2 Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, refer to *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview install

6.5 Place NTuneMON V2R6 VM into Production

This section describes the procedure to place NTuneMON V2R6 VM into production.

6.5.1 Copy NTuneMON V2R6 VM Files Into Production

- 1 Log on to the P648141J user ID. This user ID owns the disk that will contain the “production” level of the NTuneMON V2R6 VM code.

a If installing using minidisks

access 400 e

access 401 f

vmfcopy * * e = = f2 (prodid 5648141J%NTUNEMON olddate replace

The VMFCOPY command will update the VMSES PARTCAT file on the 401 disk.

b If installing using Shared File System

access P648141J.ATF.trun e

access P648141J.ATF.run f

vmfcopy * * e = = f2 (prodid 5648141J%NTUNEMON olddate replace

The VMFCOPY command will update the VMSES
PARTCAT file on the 401 disk.

NTuneMON V2R6 VM is now installed and built on your system.

7.0 Service Instructions

This section contains the procedure to install CORrective service to NTuneMON V2R6 VM.

VMSES/E is used to install the service. To become more familiar with service using VMSES/E, you should read the introductory chapters in *VMSES/E Introduction and Reference*. This manual also contains the command syntax for the VMSES/E commands listed in the procedure.

Note: Each step of the servicing instructions must be followed. Do not skip any step unless otherwise directed. All instructions showing accessing of disks assume the use of default minidisk addresses. If different minidisk addresses are used, or if using a shared file system, change the instructions appropriately.

7.1 VMSES/E Service Process Overview

The following is a brief description of the main steps in servicing NTuneMON V2R6 VM using VMSES/E.

- Setup Environment

Access the software inventory disk. Use VMFSETUP command to establish the correct minidisk access order.

- Merge Service

Use the VMFMRDSK command to clear the alternate apply disk before receiving new service. This allows you to easily remove the new service if a serious problem is found.

- Receive Service

The VMFREC command receives service from the delivery media and places it on the Delta disk.

- Apply Service

The VMFAPPLY command updates the version vector table (VVT), which identifies the service level of all the serviced parts. In addition, AUX files are generated from the VVT for parts that require them.

- Reapply Local Service (if applicable)

All local service (mods) must be entered into the software inventory to allow VMSES/E to track the changes and build them into the system. Refer to Chapter 7 in the *VM/ESA Service Guide* for this procedure.

- Build New Levels

The build task generates the serviced level of an object and places the new object on a test BUILD disk.

- Place the New Service into Production

Once the service is satisfactorily tested, it should be put into production by copying the new service to the production disk, re-saving the NSS (Named Saved System).

7.2 Servicing NTuneMON V2R6 VM

This section describes the procedure to service NTuneMON V2R6 VM.

7.2.1 Prepare to Receive Service

The *ppfname* used throughout these servicing instructions is **5648141J**, which assumes you are using the PPF supplied by IBM for NTuneMON V2R6 VM. If you have your own PPF override file for NTuneMON V2R6 VM, you should use your file's *ppfname* instead of **5648141J**. The *ppfname* you use should be used **throughout** the rest of this procedure, unless otherwise stated differently.

1 Log on to NTuneMON V2R6 VM service user ID **P648141J**

2 Establish access to the software inventory disk.

Note: If the MAINT 51D minidisk was accessed R/O, you need to have the user that has it accessed R/W link it R/O. You can then issue the following commands to obtain R/W access to it.

**link MAINT 51d 51d mr
access 51d d**

The 51D minidisk is where the VMSES/E Software Inventory files and other product dependent files reside.

3 Have the NTuneMON V2R6 VM CORrective service tape mounted and attached to **P648141J**.

4 Establish the correct minidisk access order.

vmfsetup 5648141J {NTUNEMON | NTUNEMONSFS}5648141J is the PPF that was shipped with the product. If you have your own PPF override, you should substitute your PPF name for 5648141J.

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

5 Receive the documentation. VMFREC, with the INFO option, loads the documentation and displays a list of all the products on the tape.

Electronic Service

If you are receiving service from Service Link (electronic service), refer to Appendix A, "Receiving Service for VMSES Envelopes", section "Receive Service Documentation", in the *VM/ESA Service Guide*. Remember to substitute the *ppfname* and *compname* used for servicing NTuneMON V2R6 VM in the instructions shown in that Appendix. Then return back to this program directory and continue with step 7 on page 33 below.

vmfrec info

This command will load the service memo to the 191 disk.

- 6 Check the receive message log (\$VMFREC \$MSGLOG) for warning and error messages.

vmfview receive

Also make note of which products and components have service on the tape. To do this, use the PF5 key to show all status messages which identify the products on the tape.

- 7 Clear the alternate APPLY disk to ensure that you have a clean disk for new service.

vmfmrdsk 5648141J {NTUNEMON | NTUNEMONSFS} apply

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

This command clears the alternate APPLY disk.

- 8 Review the merge message log (\$VMFMRD \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA System Messages and Codes*, or use on-line HELP.

vmfview mrd

7.2.2 Receive the Service

Note: If you are installing multiple service tapes, you can receive all of the service for this prodid before applying and building it.

Electronic Service

If you are receiving service from Service Link (electronic service), refer to the Appendix A, "Receiving Service for VMSES Envelopes", section "Receive the Service", in the *VM/ESA Service Guide*. Remember to substitute the *ppfname* and *compname* used for servicing NTuneMON V2R6 VM in the instructions shown in that Appendix. Then return back to this program directory and continue with section 7.2.3, "Apply the Service."

For **each** service tape you want to receive, do the following:

- 1 Receive the service.

vmfrec ppf 5648141J {NTUNEMON | NTUNEMONSFS}

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

This command receives service from your service tape. All new service is loaded to the DELTA disk.

- 2 Review the receive message log (\$VMFREC \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA System Messages and Codes*, or use on-line HELP.

vmfview receive

7.2.3 Apply the Service

- 1 Apply the new service.

vmfapply ppf 5648141J {NTUNEMON | NTUNEMONSFS}

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

This command applies the service that you just received. The version vector table (VVT) is updated with all serviced parts, and all necessary AUX files are generated on the alternate apply disk.

You must review the VMFAPPLY message log if you receive a return code (RC) of a 4, as this may indicate that you have local modifications that need to be reworked.

- 2** Review the apply message log (\$VMFAPP \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA System Messages and Codes*, or use on-line HELP.

vmfview apply

Note

If you get message VMFAPP2120W, re-apply any local modifications before building the new NTuneMON V2R6 VM. Refer to *VM/ESA Service Guide*. Follow the steps that are applicable to your local modification.

The following substitutions need to be made:

- **esalcl** should be **5648141J**
- **esa** should be **5648141J**
- *compname* should be **NTUNEMON** or **NTUNEMONSFS** (minidisk or SFS)
- *appid* should be **5648141J**
- *fm-local* should be the fm of 2C2
- *fm-applyalt* should be the fm of 2A6

If you have changed any of the installation parameters through a PPF override, you need to substitute your changed values where applicable.

Keep in mind that when you get to the “Rebuilding Objects” step in *VM/ESA Service Guide*, you should return to this program directory at 7.2.4, “Update the Build Status Table.”

7.2.4 Update the Build Status Table

- 1 Update the Build Status Table with serviced parts.

vmfbld ppf 5648141J {NTUNEMON | NTUNEMONSFS} (status

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

This command updates the Build Status Table.

Note

If the \$PPF files have been serviced, you get the following prompt:

VMFBLD2185R The following source product parameter files
have been serviced:

VMFBLD2185R 5648141J \$PPF

VMFBLD2185R When source product parameter files are serviced,
all product parameter files built from them must
be recompiled using VMFPPF before VMFBLD can be run.

VMFBLD2185R Enter zero (0) to have the serviced source
product parameter files built to your A-disk
and exit VMFBLD so you can recompile your
product parameter files with VMFPPF.

VMFBLD2185R Enter one (1) to continue only if you have
already recompiled your product parameter files with VMFPPF.

0

Enter a 0 and complete the following steps
before you continue.

VMFBLD2188I Building 5648141J \$PPF
on 191 (A) from level \$PFnnnnn

vmfppf 5648141J {NTUNEMON | NTUNEMONSFS}

Note: If you created your own PPF override,
use your PPF name instead of 5648141J.

Use **NTUNEMON** for installing on minidisks or
NTUNEMONSFS for installing in Shared File
System directories.

**copyfile 5648141J \$PPF a = = d (olddate replace
erase 5648141J \$PPF a**

Note: **Do not** use your own PPF name in
place of 5648141J for the COPYFILE and
ERASE commands.

vmfbld ppf 5648141J {NTUNEMON | NTUNEMONSFS} (status

1

Re-issue VMFBLD to complete updating the
build status table.

Use **NTUNEMON** for installing on minidisks or
NTUNEMONSFS for installing in Shared File
System directories. When you receive the
prompt that was previously displayed, enter a
1 to continue.

- 2 Use VMFVIEW to review the build status messages, and see what objects need to be built.

vmfview build

7.2.5 Build Serviced Objects

- 1 Rebuild NTuneMON V2R6 VM serviced parts.

vmfbld ppf 5648141J {NTUNEMON | NTUNEMONSFS} (serviced

Use **NTUNEMON** for installing on minidisks or **NTUNEMONSFS** for installing in Shared File System directories.

Note: If your software inventory disk (51D) is not owned by the MAINT user ID then make sure the VMSESE PROFILE reflects the correct owning user ID.

- 2 Review the build message log (\$VMFBLD \$MSGLOG). If necessary, correct any problems before proceeding. For information about handling specific error messages, refer to *VM/ESA System Messages and Codes*, or use on-line HELP.

vmfview build

7.3 Place the New NTuneMON V2R6 VM Service Into Production

This section describes the procedure to place the new NTuneMON V2R6 VM service into production.

7.3.1 Copy the New NTuneMON V2R6 VM Serviced Files Into Production

- 1 Log on to the P648141J user ID. This user ID owns the disk that will contain the “production” level of the NTuneMON V2R6 VM code.

a If installing using minidisks

access 400 e
access 401 f
vmfcopy * * e = = f2 (prodid 5648141J%NTUNEMON olddate replace

The VMFCOPY command updates the VMSES
PARTCAT file on the 401 disk.

b If installing using Shared File System

access P648141J.ATF.trun e
access P648141J.ATF.run f
vmfcopy * * e = = f2 (prodid 5648141J%NTUNEMON olddate replace

The VMFCOPY command updates the VMSES
PARTCAT file on the 401 disk.

You have finished servicing NTuneMON V2R6 VM.

Appendix A. APARs Incorporated into This Program

The following NTuneMON V2R5 APARs are incorporated into this program.

IR38773
IR39003
IR39305
IR39326
IR39332
IR39383
IR39459
IR39523
IR39895
IR39918
IR40456
IR40888
IR40890

Reader's Comments

Program Directory for NTuneMON Version 2 Release 6 for VM

You may use this form to comment about this document, its organization, or subject matter with the understanding that IBM may use or distribute whatever information you supply in any way it believes appropriate without incurring any obligation to you.

For each of the topics below please indicate your satisfaction level by circling your choice from the rating scale. If a statement does not apply, please circle N.

RATING SCALE						
very satisfied	<----->				very dissatisfied	not applicable
1	2	3	4	5	N	

	Satisfaction					
Ease of product installation	1	2	3	4	5	N
Contents of program directory	1	2	3	4	5	N
Installation Verification Programs	1	2	3	4	5	N
Time to install the product	1	2	3	4	5	N
Readability and organization of program directory tasks	1	2	3	4	5	N
Necessity of all installation tasks	1	2	3	4	5	N
Accuracy of the definition of the installation tasks	1	2	3	4	5	N
Technical level of the installation tasks	1	2	3	4	5	N
Ease of getting the system into production after installation	1	2	3	4	5	N

Did you order this product as an independent product or as part of a package?

- Independent
- Package

If this product was ordered as part of a package, what type of package was ordered?

- CustomPac
- FunctionPac
- SystemPac
- System Delivery Offering (SDO)
- Other - Please specify type:

Is this the first time your organization has installed this product?

- Yes
- No

Were the people who did the installation experienced with the installation of these products?

- Yes
- No

If yes, how many years? ___

If you have any comments to make about your ratings above, or any other aspect of the product installation, please list them below:

Please provide the following contact information:

Name and Job Title

Organization

Address

Telephone

Thank you for your participation.

Please send the completed form to (or give it to your IBM representative who will forward it to the NTuneMON Development group):

Design & Information Development
Dept. CGF/Bldg. 656
International Business Machines Corporation
PO Box 12195
RESEARCH TRIANGLE PARK NC 27709-9990

FAX Number: 1-800-253-3520

E-Mail: <http://www.networking.ibm.com/feedback/pubsurv.html>



Program Number: 5648-141 5821
5822
6202

Printed in U.S.A.

G110-6601-00

