



## VARIABLE AUTOTRANSFORMERS

### THREE PHASE, 208 VOLT, 60 Hz INPUT

RATED CURRENT AMPERES	MAX CURRENT AMPERES	KVA	OUTPUT VOLTAGE RANGE	TYPE NO.	MTG	CONNECTION	CHOKES REQ'D FOR PARALLEL OP*	NET WEIGHT (lbs)	SHIP WEIGHT (lbs)	DIMENSIONS		
										W	H	D
7.1	9.2	3.31	0-208	W5LG3M	ENCL	WYE	-	22	32	5.125	6.750	12.250
8.5	11.0	3.96	0-208	W5LG3	OPEN	WYE	-	20	23	4.50	4.937	12.125
10.0	13.0	4.68	0-208	W8LG3	OPEN	WYE	-	25	27	4.50	4.937	13.312

### THREE PHASE, 208-240 VOLT, 50-60 Hz INPUT

2.0	2.6	1.08	0-280	W5HG2	OPEN	OPEN DELTA		13	15	4.50	4.937	8.0
2.0	2.6	1.08	0-280	W5HG2M	ENCL	OPEN DELTA		15	23	5.125	6.750	8.125
2.0	2.6	1.08	0-240	W2G3M	ENCL	WYE		12	21	4.375	5.750	12.125
2.4	3.1	1.29	0-240	W2G3	OPEN	WYE		11	13	3.250	3.687	12.0
4.0	5.2	2.16	0-280	W10HG2	OPEN	OPEN DELTA		24	27	5.750	6.312	9.312
4.0	5.2	2.16	0-280	W10HG2M	ENCL	OPEN DELTY		29	33	7.125	9.687	9.50
5.0	6.5	2.70	0-240	W5G3M	ENCL	WYE		22	32	5.125	6.750	12.250
6.0	7.8	3.24	0-240	W5G3	OPEN	WYE		20	22	4.50	4.937	12.125
8.0	10.4	4.32	0-280	W20HG2	OPEN	OPEN DELTA		41	46	7.50	8.062	9.187
8.0	10.4	4.32	0-280	W20HG2M	ENCL	OPEN DELTA		45	54	9.0	12.062	9.375
8.5	11.0	4.57	0-240	W8G3	OPEN	WYE		25	27	4.50	4.937	13.937
10.0	13.0	5.40	0-240	W10G3	OPEN	WYE		37	40	5.750	6.312	14.0
10.0	13.0	5.40	0-240	W10G3M	ENCL	WYE		43	47	7.125	9.687	14.187
12.0	15.6	6.48	0-280	W30HG2	OPEN	OPEN DELTA		59	76	10.0	10.0	9.875
12.0	15.6	6.48	0-280	W30HG2M	ENCL	OPEN DELTA		64	87	11.375	11.375	10.062
20.0	26.0	10.8	0-240	W20G3	OPEN	WYE		65	71	7.50	7.50	13.750
20.0	26.0	10.8	0-240	W20G3M	ENCL	WYE		71	82	9.0	9.0	13.937
20.0	31.0	12.9	0-280	W50HG2M	ENCL	OPEN DELTA		126	165	13.812	17.062	14.687
25.0	32.5	13.5	0-280	W50HG2	OPEN	OPEN DELTA		116	153	12.50	13.750	14.50
28.0	32.0	13.3	0-240	W30G3M	ENCL	WYE		99	125	11.375	14.937	14.687
30.0	36.0	15.0	0-240	W30G3	OPEN	WYE		93	113	12.50	13.75	20.875
40.0	45.0	18.7	0-240	W50G3M	ENCL	WYE		179	221	13.812	17.062	21.062
50.0	50.0	20.8	0-240	W50G3	OPEN	WYE		163	206	12.50	13.750	20.875
40.0	62.0	25.8	0-280	W50HG4BBM	ENCL	OPEN DELTA	2	255	328	13.812	17.062	27.875
50.0	65.0	27.0	0-280	W50HG4BB	OPEN	OPEN DELTA	2	230	300	12.50	13.75	27.250
80.0	90.0	37.4	0-240	W50G6BBM	ENCL	WYE	3	355	430	13.812	17.062	40.187
100.0	100.0	41.6	0-240	W50G6BB	OPEN	WYE	3	325	400	12.50	13.750	40.0
150.0	150.0	62.4	0-240	W50G9BB*	OPEN	WYE (CHOKES INCL)		600	720	39	35.0	17.0
200.0	200.0	83.2	0-240	W50G12BB*	OPEN	WYE (CHOKES INCL)		760	880	39	41.0	17.0

\* AVAILABLE IN MOTOR DRIVE ONLY

### THREE PHASE, 480 VOLT, 50-60 Hz INPUT

Three phase, 480 volt input Variacs are available on special order from the factory in a variety of ratings. Our Sales Department can assist you in determining the needed rating for your specific application. You will need to know the line frequency, line voltage, and load current requirements. Variac auto-transformers can be connected in either a wye or open delta configuration.