



VARIABLE AUTOTRANSFORMERS
SINGLE PHASE MODELS, 120V, 50-60Hz INPUT

RATED CURRENT AMPERES	MAX CURRENT AMPERES	KVA	OUTPUT VOLTAGE RANGE	TYPE NO.	MTG	NOTES	CHOKES REQ'D FOR PARALLEL OP*	NET WEIGHT (lbs)	SHIP WEIGHT (lbs)	DIMENSIONS		
										W	H	D
2.0	3.0	0.36	0-140	U2	OPEN	60 to 440 Hz		2.5	3	3.250	3.687	2.937
2.0	2.6	0.31	0-140	W2M †	ENCL			4	9	4.125	5.562	4.375
2.4	3.1	0.37	0-140	W2 †	OPEN			3	4	3.250	3.687	3.937
5.0	6.5	0.78	0-140	W5M †*	ENCL			7	13	4.875	6.562	4.375
6.0	7.8	0.94	0-140	W5 † ‡	OPEN			6	8	4.500	4.937	3.937
7.1	9.2	1.1	0-120	W5LM	ENCL	60 Hz ONLY		7	13	4.875	6.562	4.375
8.5	11.0	1.32	0-120	W5L † ‡	OPEN	60 Hz ONLY		7	8	4.500	4.937	4.687
8.5	11.0	1.32	0-140	W8	OPEN			8	9	4.500	4.937	4.437
10.0	13.0	1.56	0-120	W8L ‡	OPEN	60 Hz ONLY		8	12	4.500	4.937	4.437
10.0	13.0	1.56	0-140	W10 †	OPEN			12	13	5.750	6.312	3.937
10.0	13.0	1.56	0-140	W10M †*	ENCL			15	17	6.750	9.500	5.250
14.2	18.4	2.2	0-120	W5LG2M	ENCL	60 Hz ONLY	1	15	23	5.125	6.750	8.125
17.0	22.0	2.6	0-120	W5LG2	OPEN	60 Hz ONLY	1	14	16	4.500	4.937	8.000
17.0	22.0	2.6	0-140	W8G2	OPEN		1	16	19	4.500	4.937	9.312
20.0	26.0	3.12	0-140	W20 † ‡	OPEN			21	24	7.500	8.062	4.625
20.0	26.0	3.12	0-140	W20M †	ENCL			24	29	8.625	11.937	5.375
20.0	26.0	3.1	0-120	W8LG2	OPEN	60 Hz ONLY	1	17	19	4.500	4.937	9.312
21.3	27.6	3.3	0-120	W5LG3M	ENCL	60 Hz ONLY	3	22	32	5.125	6.750	12.250
25.5	33.0	4.0	0-120	W5LG3	OPEN	60 Hz ONLY	3	20	22	4.500	4.937	12.125
25.5	33.0	4.0	0-140	W8G3	OPEN		3	25	27	4.500	4.937	13.937
28.0	32.0	3.84	0-140	W30M	ENCL			37	47	11.000	14.750	5.750
30.0	36.0	4.32	0-140	W30	OPEN			30	38	10.000	11.812	4.125
30.0	39.0	4.7	0-120	W8LG3	OPEN	60 Hz ONLY	3	25	27	4.500	4.937	13.937
40.0	52.0	6.2	0-140	W20G2M	ENCL		1	48	56	9.000	12.062	9.375
40.0	52.0	6.2	0-140	W20G2	OPEN		1	43	48	7.500	8.062	9.187
40.0	45.0	5.40	0-140	W50M †*	ENCL			57	74	13.437	16.875	6.250
50.0	50.0	6.00	0-140	W50 † ‡	OPEN			50	57	12.500	13.750	6.250
56.0	64.0	7.7	0-140	W30G2M	ENCL		1	67	90	11.375	14.937	10.062
60.0	72.0	8.6	0-140	W30G2	OPEN		1	61	80	10.000	11.812	9.875
60.0	78.0	9.4	0-140	W20G3M	ENCL		3	71	82	9.000	12.062	13.937
60.0	78.0	9.4	0-140	W20G3	OPEN		3	65	71	7.500	8.062	13.750
80.0	90.0	10.8	0-140	W50G2M	ENCL		1	123	160	13.812	17.062	13.750
84.0	96.0	11.5	0-140	W30G3M	ENCL		3	99	125	11.375	14.937	11.687
90.0	108.0	13.0	0-140	W30G3	OPEN		3	93	113	10.000	11.812	20.875
100.0	100.0	12.0	0-140	W50G2	OPEN		1	112	147	12.500	13.750	14.500
120.0	135.0	16.2	0-140	W50G3M	ENCL		3	179	221	13.812	17.062	21.062
150.0	150.0	18.0	0-140	W50G3	OPEN		3	163	206	12.500	13.750	20.875
160.0	180.0	21.6	0-140	W50G4BBM	ENCL		4	240	313	13.812	17.062	27.437
200.0	200.0	24.0	0-140	W50G4BB	OPEN		4	215	288	12.500	13.750	27.250
240.0	270.0	32.4	0-140	W50G6BBM	ENCL		6	355	430	13.812	17.062	40.187
300.0	300.0	36.0	0-140	W50G6BB	OPEN		6	325	400	12.500	13.750	40.000

† UL Listed * UL Recognized ‡ CSA Approved