



SCHMATIC

SPEED (SECONDS)	MODEL NUMBER
30	30M5011E-9Y
60	60M5011E-9Y

WIRING	INPUT		OUTPUT		SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		INPUT	OUTPUT	
				MAX. AMPS				MAX. KVA
THREE PHASE WYE	240	60	0-280	150	72.5	CW	2-2-2 D-D-D	

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ± DECIMALS .XX .0000-12 .0000 .03 1° DRAFT 1-1/2° UNITS IN [mm]

MATERIAL: ALL DIMENSIONS APPLY AFTER PLATING

TITLE: SPECIFICATION CONTROL DRAWING
MOTORIZED VARIABLE TRANSFORMER
30 & 60M5011E-9Y

STACO ENERGY PRODUCTS CO.
A Components Corporation of American Company
302 South Boulevard Dayton, Ohio 45408 USA

DRAWN BY: TIM RAU DATE: 12/14/95 FIRST USED ON: DO NOT SCALE DWG.
CHECKER: DATE: WEIGHT APPROX. CAGE CODE: 83008
ENGINEER: DATE: SCALE: .125=1 SHEET 1 OF 1

DWG. NO. 031-7018

RECOMMENDED AREAS FOR CONDUIT ENTRY