



Micro488A™

Serial/IEEE 488 Controller



Features

- Enables control of up to 14 IEEE devices from any computer with an RS-232 or RS-422 port
- Programmed with HP-style commands—REMOTE, TRIGGER, ENTER, CLEAR, OUTPUT
- Built-in 32,000 character data buffer
- Supports baud rates up to 57,600 baud
- Packaged in a rugged all metal case
- OEM board-level version available

The Micro488A™ adds complete IEEE 488 programmable bus control to any computer having an RS-232 or RS-422 port. The serial link enables up to 14 IEEE 488 devices to be controlled hundreds of feet from the host computer. The Micro488A accepts simple high-level commands from the host, and converts them into IEEE protocol and handshaking. Data received from the IEEE bus is returned to the host on the same full duplex serial port. When used with Iotech's Data Acquisition Instruments, a complete remote system can be configured. A unique "MACRO" feature allows the Micro488A to store a sequence of commands from the host and execute those commands with a single user-specified instruction. This greatly reduces the commands transferred across the serial port. The "ONSRQ DOMACRO" feature allows the unit to automatically execute a macro when a service request occurs. Up to 100 macros can be defined in the Micro488A. The Micro488A can also operate in bidirectional transparent mode in the same manner as the Serial488A™ converter.



Micro488A converts any computer with a serial port into a full-featured IEEE controller

Specifications

Serial Interface

All parameters are switch selectable.

Electrical Characteristics: Selectable RS-232 or RS-422

Duplex: Full with echo/no-echo

Data Bits: 7 or 8

Stop Bits: 1 or 2

Parity: On transmit; odd, even, mark, space or disabled

Baud Rates: 110, 300, 600, 1200, 2400, 3600, 4800, 7200, 9600, 19200, 38400, and 57600

Terminator: On Transmit; CR, LF, CR-LF or LF-CR. On Receive; any CR or LF combination

Control: Supports Clear To Send (CTS), Request To Send (RTS) and XON/XOFF

Serial I/O Buffers: Dynamically allocatable, 32K max

Connector: Accepts 25-Pin Sub-D male: DCE configured

IEEE 488 Interface

Controller Subsets: C1, C2, C3, C4, and C10 of IEEE 488-1978

Terminator: Software selectable CR, LF, CR-LF, LF-CR and/or EOI

Connector: Standard IEEE 488 connector with metric studs

General

Indicators: LEDs for Talk, Listen, SRQ, Error, and Power

Power: 105 to 125V or 210 to 250V, 50/60 Hz; 10 VA max


Environment: 0° to 35°C; 0 to 95% RH, non-condensing

Controls: Power switch (rear panel); internal dip switches for RS-232C and IEEE parameters, jumper selectable RS-232 or RS-422 operation

Dimensions: 138 mm W x 190 mm D x 68 mm H (5.4" x 7.5" x 2.7")

Weight: 1.6 kg (2.3 lbs)

Micro488A System Example



Ordering Information

Description
Serial/IEEE controller
Shielded IEEE 488 cable, 6 ft.

Part No.
Micro488A
CA-7-3

For complete information on accessories and cables, visit
www.iotech.com/acc