



## UHF TRUNKED RADIOS

# IC-F620TR (25W)

# IC-F621TR (45W)

Phase II — Compliant with NTS Release 2.4

**LTR  
PassPort**



## Capture More of Your System's Range...and Profits

With more flexibility, more power, and more spectrum coverage the IC-F620/F621TR allows you to load more customers on to your existing system. Now as part of an integrated system, combine this Icom trunking mobile with Icom's IC-F4TR portable or IC-FR4000 repeater to maximize your existing system's potential.

### More Flexibility (3-in-1)

The IC-F620/F621TR offers basic LTR, PassPort, and conventional operations in one unit. Conventional operation and talk around during trunking operation are both available with the touch of a button.

#### ○ LTR Features and Select Call

Program up to 50 systems and up to 250 talk groups per system. All basic LTR features, including DTMF direct calling with the optional DTMF microphone, HM-152T, telephone interconnect and wide/narrow channel spacing are available.

#### ○ PassPort Features — NTS Release 2.4

- Individual Selective Call (MIN call) – Allows private call between individual members within a fleet.
- Display MIN Text – While in group conversation, you can see the name of the calling party in the display, instead of the MIN number.
- Primary Talk Group – “All Call” allows individual users to call all groups in the fleet.
- RSSI (Receive signal strength indicator) – Detects the strongest signal site, providing seamless roaming.
- Site Lock – Allows the user to lock the radio onto the current site to avoid roaming.

### More Power (45W of Trunking Power\*)

Maximize the footprint the FCC gave you. More power equals greater access/coverage. It also means more reliable handshakes at the edge of your footprint. (\* IC-F621TR only.)

### More Spectrum

Wide bandwidth of 440–490MHz with switchable 12.5/25kHz widths per channel allows for greater system configuration flexibility.

### 5 Prog. Buttons & Independent AF Volume Knob

P0–P4 buttons allow you to customize functions to meet specific needs. The independent volume knob provides quick operation.

### Invertible Chassis for Clearer Speaker Audio



Avoid installation and/or use of the radio in direct sunlight.

**Icom Inc.**

**ADDITIONAL FEATURES**

- CTCSS, DTCS encoder and decoder built-in
- Conventional, system and group scans
- Flash ROM CPU for firmware upgrade capability
- MIL-STD-810 rugged construction
- Advanced PC programming capability
- One touch abbreviated dialing with optional DTMF Microphone, HM-152T
- Dead beat stuns the radio for certain periods

**Now part of an integrated system**

Take advantage of Icom's integrated design that offers a value alternative for trunking systems. The IC-F43TR and IC-FR4000\* are designed companions to our mobile radio. (\* External trunking controller is required for LTR and PassPort trunking.)



IC-FR4000



IC-F43TR

All trademarks are the properties of their respective holders.

**SPECIFICATIONS**

- Frequency coverage : 400–430MHz, 440–490MHz
- Number of channels : Max. 250 channels (conventional)
- Power supply voltage : 13.6V DC
- Current drain (approx.):
  - Tx at 45W : 13A
  - at 25W : 7A
  - Rx max. audio : 1.2A
  - standby : 300mA
- Operating temperature range : –30°C to +60°C; –22°F to +140°F
- Antenna impedance : 50Ω (SO-239)
- Dimensions (W×H×D) : 140×40×170mm; 5½×19/16×611/16in
- Weight : 1.2kg; 2.6lb
- Rated output power : IC-F620TR : 25W  
IC-F621TR : 45W
- Microphone impedance : 600Ω (8-pin modular)
- Audio output power : 4W typical at 10% distortion with a 4Ω load
- External speaker connector : 2-conductor 3.5 (d) mm (1/8")/4Ω

Measurements made in accordance with EIA-152C/204D, TIA-603. All stated specifications are subject to change without notice or obligation.

**Applicable U.S. Military Specifications**

Icom makes rugged products that have been tested to and passed the following MIL-STD requirements and strict environmental standards.

Standard	MIL 810C		MIL 810D		MIL 810E		MIL 810F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4-3	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	–
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	–
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

**Supplied Accessories**

- Hand mic. (HM-152)
- DC power cable
- Mounting bracket kit
- Fuses
- Key assign stickers

**OPTIONS**

Some options may not be available in some countries. Please ask your dealer for details.

- **HM-152 HAND MICROPHONE**
- **HM-152T DTMF MICROPHONE**  
Hand microphone with a DTMF keypad.
- **OPC-617 ACC CABLE**  
Connection cable for ignition SW, dimmer control, etc.
- **SM-25 DESKTOP MICROPHONE**  
Convenient for dispatching. Equipped with monitor switch.
- **SP-10/SP-22 EXTERNAL SPEAKERS**  
Input impedance: 4Ω; Max. input power: 5W
- **UT-109 VOICE SCRAMBLER UNIT (Version 02)**  
Non-rolling type. Up to 32 codes are available.
- **UT-110 VOICE SCRAMBLER UNIT (Version 02)**  
Rolling type. Available in conventional mode only.



**Icom Inc.**

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

**Count on us!**

**Icom America Inc.**

2380 116th Avenue NE,  
Bellevue, WA 98004, U.S.A.  
Phone : +1 (425) 454-8155  
Fax : +1 (425) 454-1509  
E-mail : sales@icomamerica.com  
URL : <http://www.icomamerica.com>

**Icom Canada**

Glenwood Centre #150-6165 Highway 17,  
Delta, B.C., V4K 5B8, Canada  
Phone : +1 (604) 952-4266  
Fax : +1 (604) 952-0090  
E-mail : info@icomcanada.com  
URL : <http://www.icomcanada.com>

**Icom (Australia) Pty. Ltd.**

A.B.N. 88 006 092 575  
Unit 1 / 103 Garden Road,  
Clayton VIC 3168 Australia  
Phone : +61 (03) 9549 7500  
Fax : +61 (03) 9549 7505  
E-mail : sales@icom.net.au  
URL : <http://www.icom.net.au>

**Icom New Zealand**

146A Harris Road, East Tamaki,  
Auckland, New Zealand  
Phone : +64 (09) 274 4062  
Fax : +64 (09) 274 4708  
E-mail : inquiries@icom.co.nz  
URL : <http://www.icom.co.nz>

**Icom (Europe) Gmbh**

Communication Equipment  
Himmelgeister Str. 100,  
D-40225 Düsseldorf, Germany  
Phone : +49 (0211) 346047  
Fax : +49 (0211) 333639  
E-mail : info@icom-europe.com  
URL : <http://www.icomeurope.com>

**Icom Spain S.L.**

Ctra. Rubi, No. 88 "Edificio Can Castanyer"  
08190, Sant Cugat del Valles, Barcelona, Spain  
Phone : +34 (93) 590 26 70  
Fax : +34 (93) 589 04 46  
E-mail : icom@icomspain.com  
URL : <http://www.icomspain.com>

**Icom (UK) Ltd.**

Unit 9, Sea St., Herne Bay,  
Kent, CT6 8LD, U.K.  
Phone : +44 (01227) 741741  
Fax : +44 (01227) 741742  
E-mail : info@icomuk.co.uk  
URL : <http://www.icomuk.co.uk>

**Icom France S.a**

Zac de la Plaine, 1,  
Rue Brindejone des Moulins BP 5804,  
31505 Toulouse Cedex, France  
Phone : +33 (5) 61 36 03 03  
Fax : +33 (5) 61 36 03 00  
E-mail : icom@icom-france.com  
URL : <http://www.icom-france.com>

**Icom Polska**


Sopot, 3 maja 54, Poland  
Phone : +48 (58) 550 7135  
Fax : +48 (58) 551 0484  
E-mail : icompolska@icompolska.com.pl  
URL : <http://www.icompolska.com.pl>

**Asia Icom Inc.**

6F No. 68, Sec. 1 Cheng-Teh Road,  
Taipei, Taiwan, R.O.C.  
Phone : +886 (02) 2559 1899  
Fax : +886 (02) 2559 1874  
E-mail : sales@asia-icom.com  
URL : <http://www.asia-icom.com>

**Beijing Icom Ltd.**

10C07, Long Silver Mansion, No.88, Yong Ding  
Road, Haidian District, Beijing, 100039, China  
Phone : +86 (010) 5889 5391/5392/5393  
Fax : +86 (010) 5889 5395  
E-mail : bjicom@bjicom.com  
URL : <http://www.bjicom.com>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.

Your local distributor/dealer: