



VHF AND UHF TRANSCEIVERS

IC-F31GT
(VHF transceiver with keypad)

IC-F41GT
(UHF transceiver with keypad)

IC-F31GS
(VHF transceiver without keypad)

IC-F41GS
(UHF transceiver without keypad)



Icom Inc.

The answer to 21st Century business communication is here!

If you want a durable, versatile, reliable and easy-to-operate portable communications tool, the IC-F31G & IC-F41G series is efficient for you. This series is designed for commercial communication or professional use with a host of built-in features, such as multiple tone-signalings, Flash ROM, high speed PLL, Componder function and more. Not only for conventional operation, but also compatible with Trunking systems*, this series is useful for small systems to large wide networks. Icom's technologies guarantee to satisfy your needs.

* Optional unit is required.

VHF AND UHF TRANSCEIVERS

VHF transceiver with keypad
IC-F31GT

VHF transceiver without keypad
IC-F31GS

UHF transceiver with keypad
IC-F41GT


UHF transceiver without keypad
IC-F41GS

Full built-in tone-signalings

All tone-signalings are builtin such as CTCSS, DTCS, 2-tone/5-tone and DTMF encode/decode, so you don't need to install an optional tone-signaling board. And a wide variety of selective calling systems are available to call specific station(s) or control a repeater. In addition, ANI (Automatic Number Indication) function is available with 2-tone/5-tone and DTMF.

Largest LCD in its class

With the large LCD, a simple sentence of up to 24 full-dot matrix characters provides more smooth communication than previous one word indication. Operational icons, such as antenna (S-meter) or battery life, show various operating status at a glance. What is more, original characters can be made and indicated on the LCD.



8x20 dot character can be made on a PC and plural characters can be combined on LCD.

Durable construction

The body is compact, yet the polycarbonate panel and one-piece aluminum chassis provides durable construction to meet MIL STD grade C, D and E for shock and vibration. You can count on the unit to operate in challenging environments.

Flash ROM for system upgrades

Flash ROM is adapted as the main CPU, which allows system customize and future compatibility with other protocol. A newly designed ultra high speed PLL, with a Fractional-N system, offers faster acquisition times for efficient trunking use.

Up to 8 dealer-programmable key assignments

The following functions can be programmed.

- Channel up/down • Bank up • Call • Beep
- Scan A/B start/stop • Scan Tag add/delete
- Priority A/B • Key lock • Monitor • Scrambler
- C. Tone CH enter • MR-CH 1/2/3/4 • High/Low
- Talk around • ID-MR select • Null (Light)
- Tx code enter • Re-dial • Wide/Narrow
- Tx code CH select • Emergency single/repeat
- DTMF autodial • Special function 1/2
- OPT 1/2/3 momentary • Compand

Advanced PC programming for Microsoft® Windows® 95/98

256 memory channels

Up to 256 memory channels with 12 character channel names can be stored with up to 16 banks. The rotary selector allows you to select each bank or memory channel.

Simultaneously work 2 optional internal units

2 optional units can be installed and will work simultaneously. You can select optional units to suit your needs and to provide versatile usage.

Combination of available internal units

Option slot 2 \ Option slot 1	UT-109 Voice Scrambler Unit	UT-110 Voice Scrambler Unit	UT-113 Man Down Unit
UT-109 Voice Scrambler Unit			✓
UT-110 Voice Scrambler Unit			✓
UT-113 Man Down Unit	✓	✓	
UT-105 (2) SmarTrunk II™ Logic Board	✓	✓	①
UT-111 (2) LTR® Trunking Board	✓	✓	①

✓ Available simultaneously

① UT-113 is available in conventional mode.

② UT-105 and the UT-111 have to be installed in slot 1.

* Same optional types, such as UT-109 and UT-110, can not be installed simultaneously.

Prolonged Ni-MH battery

The Ni-MH battery is designed for 10 hours operation. A battery case is optionally available for using a set of alkaline batteries (six AA (R6) cells) during charging.

Built-in compander function

Built-in compander function provides clear audio quality under noisy environments.

* Receiving party must have same function.

Smart design with easy operation

The rounded, compact* design fits comfortably in your palm, and is easy to carry around. The large keypad makes one-hand operation easy.

* Size: 54(W)×139(H)×38(D) mm

Multi connector for accessories

The 9-pin multi connector, which use the spring action for close contact, allows you reliable operation with accessories, such as speaker-microphone or earphone.



Other features

- The red key on the top panel can be an emergency trigger
- Normal and priority scan functions
- Time-out timer capability
- Narrow/wide multi-band width and 2-step power save are supported
- Talk around function changes duplex channels to simplex channel
- VOX capability and more...

OPTIONS

BATTERY PACKS AND CASE

BP-208	BP-209	BP-210
AA (R6) batteries × 6	Ni-Cd 7.2 V/1100 mAh	Ni-MH 7.2 V/1650 mAh

BATTERY CHARGER
BC-137 (#02)+BC-122

BC-121+AD-94 (#02)×(6 pcs.) +BC-124

BC-119 +AD-94 (#02)

MB-74 BELT CLIP

SPEAKER-MICROPHONES

EM-80

EM-89

AD-52 EARPHONE JACK ADAPTOR

INTERNAL UNITS

UT-105 SmarTrunk II™ Logic Board

UT-109 VOICE SCRAMBLER UNIT

UT-110 VOICE SCRAMBLER UNIT

UT-111 TRUNKING UNIT

UT-113 MAN DOWN UNIT

ANTENNA
FA-SC25V
VHF ANTENNA FOR 136-155 MHz
FA-SC55V
VHF ANTENNA FOR 146-174 MHz
FA-SC25U
UHF ANTENNA FOR 400-430 MHz
FA-SC57U
UHF ANTENNA FOR 440-470 MHz
FA-SC72U
UHF ANTENNA FOR 470-520 MHz

Approx. output power and battery life (Tx (Hi): Rx: standby=5:5:90)

BATTERY PACK	OUTPUT POWER		BATTERY LIFE (approx.)
	IC-F31GT/GS	IC-F41GT/GS	
BP-208	1 W typ.	1 W typ.	—
BP-209	5 W typ.	4 W typ.	6.5 hours
BP-210	5 W typ.	4 W typ.	10 hours

BC-137 (#02) BATTERY CHARGER + BC-122 AC ADAPTOR
Regularly charges a battery pack, BP-209 or BP-210, with/without transceiver. The AC adaptor, BC-122, is additionally required.

BC-119 DESKTOP CHARGER + AD-94 (#02) CHARGER ADAPTOR
For rapid charging of battery pack, BP-209 or BP-210. An AC adaptor is supplied with the charger. Charging time: 1.5 to 2 hours
BC-121 MULTI-CHARGER + AD-94 (#02) CHARGER ADAPTOR + BC-124 AC ADAPTOR
For rapid charging of up to 6 battery packs (six AD-94s are required.), BP-209 or BP-210. The BC-124 outputs 12 V DC and has 7 A capacity for the BC-121. Charging time: 1.5 to 2 hours.

MB-74 BELT CLIP
Alligator type. Clips onto almost anything in a variety of convenient places.
MB-68 BELT CLIP
Same as that supplied is also available.

EM-80 : Durable, full-sized microphone with internal speaker.
EM-89 : Slim dimensions. Equipped with an earphone jack and a transmit indicator.

AD-52 EARPHONE JACK ADAPTOR
Transforms 9-pin multi connector to φ 3.5 mm earphone connector.

UT-105 : Provides SmarTrunk II™ capabilities.
UT-109 : Provides operating security. Up to 32 scrambling codes are available. The scrambling system is not compatible with the UT-110.
UT-110 : Provides higher operating security. Up to 1020 (255 codes × 4 groups) scrambling codes are available. The scrambling system is not compatible with the UT-109.
UT-111 : Provides LTR® trunking capabilities.
UT-113 : Automatically sends an emergency signal when the transceiver is left in horizontal position.

SPECIFICATIONS

GENERAL

- Frequency range :
 - IC-F31GT/GS 136–174 MHz
 - IC-F41GT/GS 400–430 MHz
 - 440–480 MHz
- Number of Channels : Max. 256 Ch/ 16 banks
- Type of emission : 16K0F3E (25/30 kHz)
- 8K50F3E (12.5/15 kHz)
- 14K0F3E (20 kHz)
- Channel spacing : 30/15 kHz (25/12.5 kHz)
- 20/12.5 kHz
- Antenna impedance : 50 Ω
- Frequency error : ±1.5 kHz
- PLL channel step : 5 kHz, 6.25 kHz, 7.5 kHz
- Power supply requirement : 7.5 V DC (Icom battery pack)
- Current drain (at 7.5 V DC; approx):
 - Transmit at 5 W 1.7 A typ. (IC-F31GT/GS)
 - at 4 W 1.7 A typ. (IC-F41GT/GS)
 - Receive at AF max. 300 mA
 - at stand-by 95 mA
- Operating temp. range : –25°C to +55°C
- Dimensions : 54(W)×139(H)×38(D) mm
(projections not included)
- Weight (with BP-210) : 420 g

TRANSMITTER

- Modulation system : Variable reactance frequency modulation
- Output power : 5.0 W (IC-F31GT/GS)
- (nominal) 4.0 W (IC-F41GT/GS)
- Max. freq. deviation : ± 2.5 kHz, ± 5 kHz, ± 4 kHz
- Modulation limiting : 60–100%
- Audio harmonic distortion: 3% typ. (1 kHz/40% dev.)
- Spurious emissions : Less than 0.25 μW
- Adjacent Ch. power : 60 dB (12.5 kHz)
- 70 dB (25/20 kHz)
- Residual modulation : 43 dB typ. (12.5 kHz)
- 45 dB typ. (25/20 kHz)
- External MIC connector : 9-pin multi connector/ 2.2 kΩ

RECEIVER

- Intermediate freq. : 1st 31.65 MHz (IC-F31GT/GS)
- 47.25 MHz (IC-F41GT/GS)
- 2nd 450 kHz
- Sensitivity : 0.63 μV typ. (at 20 dB SINAD) e.m.f.
- Squelch sensitivity : 0.25 μV (at threshold)
- Adjacent Ch. selectivity : 63 dB typ. (12.5 kHz)
- 73 dB typ. (25 kHz)
- Spurious response : 70 dB
- Intermodulation : 70 dB typ.
- Hum and noise ratio : 43 dB typ. (12.5 kHz)
- 45 dB typ. (25/20 kHz)
- Audio output power : 0.5 W typ. (at 5% distortion with an 8 Ω load)
- External SP connector : 9-pin multi connector/ 8 Ω

Applicable U.S. Military Specifications

Icom makes rugged products that meet MIL-STD requirements and strict environmental standards as follows.

Standard	MIL 810C		MIL 810D		MIL 810E	
	Method	Procedure	Method	Procedure	Method	Procedure
Vibration	514.2	X	514.3	I	514.4	I
Shock	516.2	I	516.3	I	516.4	I

Measurements made in accordance with ETS 300-086.

All stated specifications are subject to change without notice or obligation.


Microsoft and Windows are registered trademarks of Microsoft Corporation in the U.S.A. and other countries.

SmarTrunk II is a trademark of the SmarTrunk System Corporation.

LTR is a registered trademark of the EFJohnson Radio Systems.

Supplied accessories:

- Antenna (may differ according to version)



• Belt clip, MB-68

• Battery pack, BP-210

Icom Inc.

6-9-16, Kamihigashi, Hirano-ku, Osaka 547-0002, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone: (425) 454-7619

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: (604) 952-4266 Fax: (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022
URL : <http://www.icom.net.au>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
Phone: (02) 2559 1899 Fax: (02) 2559 1874

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, SPAIN
Phone: (93) 590 26 70 Fax: (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
URL : <http://www.icomuk.co.uk>

Icom France S.a

Zac de la Plaine, Rue Brindejonc des Moulinais
BP 5804, 31505 Toulouse Cedex, France
Phone: 561 36 03 03 Fax: 561 36 03 00
URL : <http://www.icom-france.com>



Certificate Number Q14190

Icom Inc. (Japan), is an
ISO9001 certification
acquired company.

Your local distributor/dealer: