

ICOM

SSB RADIO TELEPHONE

IC-M700PRO



Long distance communication made simple.

Simplified operation

The IC-M700PRO is easy to use whether you are new to SSB or an expert. Channel selection is quick and easy to access with large, independent GROUP and CHANNEL knobs. Each panel button has only 1 function. The large, easy to read display shows channel (or frequency) and operating status at a glance. A new green LCD is easy to see in sunlight, but not too bright for night operations.

Powerful output extends your communications reach

The powerful 150 W* (PEP) transmitter provides long distance communication you can rely on. To make sure that power is always available to you—even during demanding RTTY (radio teletype) or E-mail operation—a large cooling fan combined with the IC-M700PRO's aluminum chassis keep the radio cool.

*60 W (PEP) above the 24 MHz bands.

Scanning functions

Locate desired signals quickly with a powerful memory scan feature.

And more...

- Automatic antenna tuner, the AT-130, is available to match the transceiver to your antenna
- Numerous operating modes* available: USB, AM, CW, FSK and AFSK
- *Ask your dealer for details.
- Wide band, general coverage receive—0.5 to 29.9999 MHz
- Channel/frequency knob allows the user to tune specific frequencies around the memory channel
- NMEA plus 2 DIN connectors are available for external equipment connection, such as a linear amplifier, FSK terminal, E-mail modem, etc.
- Optional 2-tone alarm function (UT-95 2-TONE ALARM UNIT required) provides simple transmission of emergency signals
- NMEA0813 interface included

Icom Inc.

SPECIFICATIONS

GENERAL

- Frequency coverage

Receive	0.5 kHz–29.999 MHz		
Transmit	1.6– 2.9999 MHz	4.0– 4.9999 MHz	
	6.0– 6.9999 MHz	8.0– 8.9999 MHz	
	12.0–13.9999 MHz	16.0– 17.9999 MHz	
	18.0–19.9999 MHz	22.0– 22.9999 MHz	
	25.0–27.50000 MHz		
- Mode : USB, AM, CW, FSK and AFSK
- Number of channels : 150 (max.; 3 groups of 50 channels each)
- Antenna connector : SO-239 (50 Ω)
- Power supply requirement : 13.6 V DC ±15%
- Current drain (at 13.6 V DC) : Tx max. power 30 A
Rx max. audio 2.5 A
- Usable temperature range : –30°C to +60°C; –22°F to +140°F
(Guaranteed range –20°C to +60°C; –4°F to +140°F)
- Frequency stability : ±10 Hz (0.5–14.9999 MHz)
±20 Hz (15–29.9999 MHz)
- Dimensions (projections not included) : 291.4(W)×116.4(H)×315(D) mm
11^{3/16}(W)×4^{13/32}(H)×12^{1/2}(D) in
- Weight : 7.9 kg; 17 lb 7 oz
- Remote connector : NMEA D-sub 9-pin (female)
- ACC 1 connector : DIN 8-pin (female)
- ACC 2 connector : DIN 7-pin (female)

All stated specifications are subject to change without notice or obligation.

TRANSMITTER

- Output power : 150 W PEP (below 24 MHz)
60 W PEP (above 24 MHz)
- Spurious emissions : –75 dB typical
- Unwanted sideband suppression : 70 dB typical
- Carrier suppression : 65 dB typical
- Microphone connector : 8-pin connector (800 Ω)

RECEIVER

- Sensitivity

USB, CW, FSK, AFSK (for 12 dB SINAD)	6.3 μV (0.5–1.5999 MHz) 1 μV (1.6–1.7999 MHz) 0.35 μV typical (1.8–29.9999 MHz)
AM (for 10 dB SIN)	32 μV (0.5–1.5999 MHz) 6.3 μV (1.6–1.7999 MHz) 2.2 μV typical (1.8–29.9999 MHz)
- Spurious response rejection ratio : 80 dB typical (1.6–29.9999 MHz)
- Audio output power (at 13.6 V DC) : 5.0 W typical at 10% distortion with a 4 Ω load
- Clarity variable range : ±150 Hz
- External speaker jack : 2-conductor 6.5 (d) mm (1/4"×4–8 Ω)

Supplied accessories:

- Hand microphone
- DC power cable
- ACC plugs
- Mounting bracket kit
- Microphone hanger
- Speaker plug
- Spare fuses

OPTIONS

AT-130 HF AUTOMATIC ANTENNA TUNER



Matches the transceiver to a long wire antenna with little insertion loss.

MN-100 ANTENNA MATCHER




Matches the transceiver to a dipole antenna. Covers all HF bands from 1.5 to 30 MHz. 8 m × 2 antenna wires come attached.

MN-100L ANTENNA MATCHER



Match the transceiver to a long wire antenna. Covers all HF bands from 1.5 to 30 MHz. 15 m × 1 antenna wire comes attached.

AH-710 FOLDED DIPOLE ANTENNA



Covers from 1.5 to 30 MHz band. Has an SO-239 connector. Easy to assemble (non-link construction).

PS-60 DC POWER SUPPLY



Provides 13.6 V DC (30 A) output from an AC outlet.

PS-66 DC-DC CONVERTER



Provides 13.6 V DC (30 A) output from 18–32 V DC.

HS-50 HANDSET



Provides clear audio reception and comes in handy for listening privacy.

FL-100 CW/FSK NARROW FILTER (500 Hz/–6 dB)

Have good shape factor to provide better CW/RTTY reception.

UT-95 2-TONE ALARM UNIT

Provides the alarm function. Already built in to the Marine version.

Icom Inc. 1-1-82, Kametani 1-chome, Osaka 547-0228, Japan Phone: 06-6758-5900 Fax: 06-6751-0210 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

©Copyright 1999 Icom Inc.
2882 116th Ave. S.E., Bellevue, WA 98004, U.S.A.
Phone: 206-454-6155 Fax: 206-456-7599
URL: <http://www.icomusa.com>
©Copyright Reserved Phone: 1-800-454-6155

Icom Canada

General Centre 30-6122 P. Drive 17,
Delta, B.C. V9K 2J6, Canada
Phone: 604-651-4907 Fax: 604-650-0299
URL: <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 33 220 232 221
220/224 A'Court Street, Brookvale, Sydney, 2100 Australia
Phone: 02 9527 0252 Fax: 02 9527 0022
URL: <http://www.icomau.com>

Icom New Zealand

1475, 4th Street, East Tamaki, Auckland, New Zealand
Phone: 06 274 0400 Fax: 09 274 4706
URL: <http://www.icomnz.com>

Icom (Europe) GmbH

Communications-EU GmbH
Friedenstraße 50, 100 00 Berlin, Deutschland, D-10117
Phone: 030 21346042 Fax: 030 2132589
URL: <http://www.icomeurope.com>

Icom Spain S.L.

Calle de Greda 4, Marbella 29 14 32
06100 San Pedro de Alcantara, España, S.A.
Phone: 365 962 26 20 Fax: 365 593 24 42
URL: <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 6, Sea St., Hereford, Here, HR12 3JG, U.K.
Phone: 01432 76174 Fax: 01432 74 262
URL: <http://www.icomuk.com>

Icom France S.a

221 20 80, Route, Rue de la République, 93100
St-Denis, 93100, France, C.C.I.C., France
Phone: 01 48 46 33 Fax: 01 48 33 11 02
URL: <http://www.icomfrance.com>

Asia Icom Inc.

2/F, No. 66, Sec. 1, Sheng-Hai Road,
Taipei, Taiwan, R.O.C.
Phone: 02-2599-1869 Fax: 02-2553-1874

Your local distributor/dealer:



ISO 9001
UKAS
Quality Management System
Certificate Number: 014122
Icom Inc. (Japan) is an ISO9001
certification acquired company.