

  
ICOM

# *Marine Products*

SIMPLY THE BEST



Icom Inc.



# Compact marine, commercial or recreational

## Tough and waterproof

The IC-M88 is built tough to withstand hazardous environments. Even if it is dropped into water, waterproof construction\* will protect it from harm.

\* Equivalent to JIS Grade 7. (1m depth/30min.)

## Simple operation

6 clearly labelled buttons on the front panel and the volume/power knob maximize simplicity of operation. A large, clear LCD with backlighting and backlit buttons make night time operation easy.

## Li-Ion battery for long battery life

With the standard battery pack, you can get up to 15 hours of operating time.\* Also, no worries about 'memory effect' of the battery with Li-Ion technology.

\* Tx:Rx:Stand-by= 5:5:90 with BP-227.

## Optional speaker-microphone

An optional waterproof\* speaker-microphone, the HM-138, provides reliable operation.

\* Equivalent to JIS Grade 7. (1m depth/30min.)

## 22 free channels for land use

The IC-M88 has 22 free channels reserved for land use (146-174MHz). Wide/narrow channel spacing is programmable for each channel, and CTCSS and DTCSS signaling is built-in.

\* Appropriate license will be required.

## Additional features

- Instant access to Ch.16 and Ch.9
- Simple add/delete TAG scanning
- Monitor button opens squelch
- 2-step power saver • Key lock function
- 4-step battery indicator
- Auto WX alert function (U.S.A. version only)



# Marine radio that set the standard that others look up to

## Ergonomic design, waterproof

The IC-M1V is waterproof\*, and its ergonomic size, 52.5x129x30 mm (2 1/16x5 3/32x1 3/16 in), layout and lightweight, only 280g (9.9oz), make it extremely convenient to use.

\* Equivalent to JIS Grade 7 (1m depth/30 min.)

## Powerful, long hours of operation

5W of powerful output power and long 15 to 16 hours\* of operating time are possible with the standard Lithium Ion battery pack.

\* Tx:Rx:Stand-by=5:5:90 with BP-215L.

## Optional speaker-microphone

A waterproof\* speaker-microphone plugs right in to the waterproof jack on top of the IC-M1V. Go where its wet without fear!

\* Equivalent to JIS Grade 7 (1m depth/30 min.)

## Alphanumeric indication

A large, easy-to-read backlit LCD shows channel number and names. Up to 10-characters can be assigned.

## Additional features

- Supplied battery charger stands by itself or can be mounted to a wall
- Fast, "TAG" scanning
- Self check function
- Remaining battery power indicator
- Dual/Tri-watch functions
- Auto WX alert function (U.S.A. version only)
- Instant Ch.16 and Ch.9 access
- Optional voice scrambling capability (not available in some countries)
- Auto backlit for LCD and front panel keys







# Big screen, tough body and it's waterproof too!

## Extra-large LCD display

The extra large LCD (35x24 mm; 1 3/8 x 1 5/16 in. dimensions) is incorporated into the design allowing easy viewing of channel display and status. Bright LCD backlighting is great for night time operation.

## Waterproof construction\*

The IC-M2A is built waterproof to repel all forms of moisture.

\* Equivalent to JIS Grade 7. (1m depth/30 min.)

## Desktop charger supplied

The BC-150 desktop charger is a simple drop-in charger. It has screw holes to fix to various places and also a catch to fix the battery with the BC-150 with/without the transceiver. So you can leave it alone to charge even in choppy seas.

## Simple operation

Well spaced, clearly labelled buttons provide easy, one-handed access to frequently used functions. The IC-M2A does not require complicated operation to use it efficiently and to its maximum potential.

## Additional features

- Swivel belt clip, MB-87 standard
- 4-step battery life indicator
- Dual/Tri-watch function
- Normal, priority and tag scanning
- One-touch access to Ch.16 and Ch.9
- 2-step power saver
- Key lock function
- S-meter shows the signal strength of the received signal
- Auto WX alert function (U.S.A. version only)



# A cost performance winner

## Simple operation

Icom's easy to use ergonomic layout with clearly labelled buttons extends throughout our handheld range. The simple push of one button controls each function. Channel selection is a snap with the up/down keys.

## Large LCD with backlighting

The extra large LCD and superior contrast and backlighting make viewing easy on your eyes. And with key backlighting, operation at night is not a problem.

## Water-resistant construction\*

Water-resistant, non-corrosive construction, including water-tight gaskets for the control knob and antenna connector.

\* Equivalent to JIS Grade 4.

## 'Tag' scan system

Icom's 'tag' scan system makes scanning easy—add or delete channels at the push of a button.

## Alkaline battery\* ready

Alkaline batteries can be used as a convenient backup to rechargeable Ni-Cds. Keep an extra set of alkaline batteries on board for temporary operation or emergencies.

\* Water-resistance is maintained using alkaline cells.

## Additional features

- One-touch selection of Ch. 16 and Ch. 9
- Powerful 5 W output power
- Dual watch and tri-watch
- Receive WX channels with a WX alert function (U.S.A. version only)
- Compact size





## *GMDSS portable for survival craft*

### **Conforms to IMO A 809 (19) and A 694 (17)**

The IC-GM1500 complies with the demanding requirements of IMO resolution A 809 (19) and A 694 (17) for survival craft radios.

### **Long-life battery**

For IMO survival craft use, the CM-176 (non-rechargeable) 3600mAh lithium battery pack provides more than 24 hours\* of operation at 25°C. For the U.S.A. version, the CM-165, rechargeable 1200mAh Ni-Cd battery pack, is available for 8 hours\* of operation.

\* Tx:Rx:Stand-by=10:10:80.

### **Waterproof**

For the IC-GM1500, waterproof means resistance to water intrusion even while completely submerged—prevents water entry for at least 5 minutes at a depth of 1m.

### **Compact and rugged body**

The IC-GM1500 is compact at 68.5×45.3×215 mm (2<sup>1</sup>/<sub>16</sub>×1<sup>25</sup>/<sub>32</sub>×8<sup>1</sup>/<sub>2</sub> in)\*. Drop resistant construction protects it from damage when dropped from a height of 1m onto any surface.

\* With CM-176; not including antenna.

### **Simple operation**

A minimum number of buttons and controls with tactile feedback provide user-friendly operation.

### **Additional features**

- Instant access to Ch.16
- All simplex, VHF marine channels are included
- Auto LCD backlighting
- Lock function
- Low battery indicator

SURVIVAL CRAFT 2-WAY RADIO  
**IC-GM1500**

## *A “waterproof” portable that really is waterproof!*

### **Waterproof protection\***

Imagine wading through shallow water to secure a safety line and suddenly realizing your transceiver is attached to your belt! No problem for the IC-M15—even total submersion in salt or fresh water is OK.

\* Equivalent to JIS Grade 7 (1m depth/30 min.)

### **Large, easy-to-use buttons and controls**

Each button is large and clearly labelled so that operation, even while wearing gloves, is a breeze.

### **Rugged construction**

One-piece, cylindrical housing over a die-cast aluminum frame provides the durability and dependability needed in the demanding marine environment.

### **Additional features**

- One-touch access to Ch.16 and the programmable call channel\*
- Power saver function
- Easy-to-read LCD with backlighting
- Lock function
- Optional voice scrambler unit for private communications
- Scan functions\*
- 5 W output power
- Dual/tri-watch functions\*
- All necessary VHF marine channels\* plus 24 memories and 1 call channel

\* Availability varies according to version.

Not available in the U.S.A.

VHF MARINE TRANSCEIVER  
**IC-M15**



# The ultimate VHF!



Accepts up to two COMMANDMIC®s.



Both black and white versions available.

## VHF MARINE TRANSCEIVER IC-M602

### 4×6", flush-mount design

With its slim dimensions (depth), it will easily fit into your cabin console or dashboard. With full dot matrix characters, settings can be easily read under any lighting conditions.

### DSC meets RTCM SC101

The "DISTRESS" button can transmit a formatted distress alert with your position and time. Up to 40 distress IDs are available. 40 received messages can be stored.

### Waterproof protection

With a waterproof rating equivalent to JIS Grade 7, IC-M502 withstands the wettest conditions (1 m/30 min.; except cables).

### Optional COMMANDMIC®

The COMMANDMIC® allows you to remotely control all functions of the IC-M502 (except DSC operation) from up to 21m (70ft) away.

### Other features

- Supplied audible 'Smart-speaker-mic.'
- Simple 'TAG' scanning function
- Instant access to Ch.16 and Ch.9
- 8 backlit levels for LCD and keypad
- Optional voice scrambler unit for privacy
- Auto WX alert function (U.S.A. version only)

### Built-in ITU Class-D DSC

An independent receiver continuously watches Ch. 70, while using another channel. A single antenna connector allows VHF and Ch. 70 operation.

### Simultaneous connection of two COMMANDMIC®s

Allows 2nd and/or 3rd station or intercom function.

### NMEA Input/Output

NMEA output allows you to plot own/other ship's position data on a PC or navigation equipment.

### 22 Watt 2-way Hailer capability

When connected to a hailer horn, communication with other boats, Deck or marina staff is easy.

### Other features

- Waterproof construction equivalent to JIS Grade 7 (1m /30min.; except cables)
- Superior receiver performance
- Auto fog horn function
- Large LCD with dot-matrix characters
- Detachable 'Smart-speaker-microphone'
- Instant access to Ch.16 and Ch.9
- Auto WX alert function (U.S.A. version only)
- Optional Voice Scrambler, UT-112

# Easy to operate, easy to install!



Best VHF Radio Telephone – Fixed



COMMANDMIC® capable.



Both black and white versions available.

## VHF MARINE TRANSCEIVER IC-M502



# Easy to see! Easy to hear!



COMMANDMIC®  
capable.  
IC-M402 only.



Both black and white versions available.  
Photo shows the IC-M402.

## VHF MARINE TRANSCEIVERS IC-M402 IC-M402S

### Flush-mount design

Flush mounting into an instrument control panel or similar flat surface is a snap with the uniquely designed mounting 'lip'.

### Simple operation

Controls and buttons are clearly labelled, providing intuitive operation and a large, easy-to-read display measuring 20x60 mm (1 1/16x1 5/8 in) indicates all necessary information at a glance.

### Remote function microphone

The microphone allows you to conveniently change channels or select output power without using the front panel buttons.

### Other features

- Auto WX alert function (U.S.A. version only)
- Icom's 'Tag' scan system
- Dual/tri-watch functions
- Instant access to Ch.16 and Ch.9
- Up/down keys for channel selection
- Low battery indicator
- Backlit for LCD

### Large channel indication

The large, easy to see display has 27x43 mm (1 1/16x1 5/8 in) dimensions. 10-character channel names and all settings are displayed at the same time.

### Built-in DSC meets RTCM SC101

The DSC watch function monitors Ch 70, while receiving another channel. The position request function indicates a caller's position. Up to 30 DSC IDs are memorized.

### Rugged waterproof construction\*

The IC-M402/S is designed to work for many years in all conditions the marine environment can throw at it!

\* Equivalent to JIS Grade 7 (1m/30 min; except cables)

### Optional COMMANDMIC®

The COMMANDMIC® makes it convenient for using the IC-M402 from a separate cabin or tower from up to 21m (70ft) away.

\* Available with IC-M402 only.

### Other features

- Dual and tri-watch functions
- Position indication with GPS receiver (GPS receiver is not included)
- LCD backlighting and key illumination
- Auto WX alert function (U.S.A. version only)

# Easy, reliable operation



Both black and white versions available.

## VHF MARINE TRANSCEIVER IC-M45

# Advanced DSP marine radio with compact remote head



**PRODUCT AWARD RECIPIENT**  
Best of Show & Best SSB Radio Telephone



Photo shows the IC-M802 U.S.A. version.

## HF MARINE TRANSCEIVER IC-M802

### Digital Signal Processor

The digital IF filter provides flexible filter settings for narrow bandwidth signals without having to install an optional filter.

### Built-in ITU Class E DSC\*

The IC-M802 conforms to Class E DSC requirements, vital for your safety at sea.  
\* U.S.A. and Canadian versions only.

### Alphanumeric readout

Seven characters can be programmed into each memory channel to conveniently display station names or ship names for simplified operation.

### 150W output power

A large cooling fan system, in combination with the aluminum chassis, allows conditions for transmission at a full 150W\* (PEP) RF output power—even during demanding RTTY (radio teletype) operation.  
\* 60W (PEP) above 24 MHz bands.

### Other features

- General coverage receiver
- Terminals for frequency/mode control via NMEA interfacing
- Automatic tuning function
- Large, front-mounted speaker
- Weather fax ready
- Backlight control
- CW full break-in and semi break-in
- 2-tone alarm built-in (Optional depending on version)
- 1136 channels available

### One touch e-mail button\*

The e-mail button allows you to make a quick link to your coast station/server.  
\* U.S.A. and Canadian versions only.

### Automatic antenna tuner, AT-140

The optional AT-140 easily connects to the radio without opening the casing. The tuner through function can be used with the AT-140.

### Other features

- 4×8-inch remote controller and 4×4-inch external speaker
- Large LCD with dot matrix characters
- Channel and Group dials offer easy channel selection and operation
- Powerful 150W (PEP) output
- 0.5 to 29.9999MHz wideband receiver
- DIN and RS-232C connectors for external equipment
- NMEA 0183 interface included
- Built-in 2-tone alarm function\*  
\* General version only.

## Worldwide communications at an affordable price



## HF MARINE TRANSCEIVER IC-M710



# A favorite among SSB marine radio operators



HF TRANSCEIVER  
**IC-M700PRO**

## Simple operation with keypad

A minimum of buttons and knobs provide superior feature selectability. The 10-key-pad allows you to enter an operating frequency or a memory channel number directly. VFO mode operation is available for continuous frequency operation.

## General coverage receive

The IC-718 and IC-78 covers 0.03–29.99999MHz\* in SSB, CW, RTTY and AM modes. The 1st receiver mixer provides superior receiver sensitivity, rejecting nearby interfering signals.

\* Guaranteed range: 0.5–29.99999MHz

## Front mounted loud speaker

With the speaker facing the operator, audio sounds can be clearly heard without impediment during operation.

## Other features

- 101 memory channels
- VOX (Voice operated transmission)
- Digital S/Rf meter
- Band stacking register
- IF shift interference rejection
- Optional AF DSP capabilities (IC-718 only)
- Squelch/RF gain control
- Optional automatic antenna tuner, AT-140 available (IC-78 only)

## Simplified operation

Channel selection is quick and easy to access with large, independent Group and Channel knobs. Each panel button has only 1 function. The large easy to read display shows channel (or frequency) and operating status at a glance.

## Data operation capability

The powerful 150W\* (PEP) transmitter provides long distance communication, and ensures that power is always available to you—even during demanding RTTY (radio teletype) or E-mail operation.

\*60W (PEP) above 24MHz bands.

## Other features

- Optional automatic antenna tuner, AT-140/AT-130, matches the radio to your antenna
- 0.5 to 29.9999MHz wide band general coverage receive
- Channel knob allows the user to tune specific frequencies around a memory channel
- 2 DIN connectors for external equipment connection—linear amplifier, FSK terminal, E-mail modem, etc.
- 2-tone alarm built-in (Optional depending on version)
- NMEA 0183 interface included

# Reliable long distance communications



Photo shows the IC-78.

The IC-78 and IC-718 are not certified for marine use in the U.S.A. by the FCC.

HF TRANSCEIVERS  
**IC-78 IC-718**





## Easy operation under all conditions

- Powerful 4kW output power
- High contrast 5.7 inch LCD display
- 60cm radome scanner observes up to 36nm
- Multiple language indication  
English, Spanish, Portuguese, Chinese and Korean
- External GPS and Compass data input with NMEA0183, N+1, AUX format



● Radome Scanner for MR-570R

### LCD MARINE RADAR MR-570R

## High Resolution over long ranges

- Bright 8-level picture on 10-inch monochrome green CRT
  - Powerful 4kW output power
  - Two types of scanner units  
MR-1000T : 120cm open array scanner observes up to 48nm  
MR-1000R : 60cm radome scanner observes up to 36nm
  - Multiple language indication  
English, Spanish, Portuguese and Korean
  - External GPS and Compass data input with NMEA 0183, N+1, AUX format
- Not available in the U.S.A.



● Open Array Scanner for MR-1000T




● Radome Scanner for MR-1000R



### CRT MARINE RADAR MR-1000R MR-1000T

## Fully integrated GPS, Plotter, Sounder




















- 5.6 inch TFT color LCD
- Splash resistant body equivalent to JIS Grade 4
- 500W powerful dual frequency video sounder  
Up to 640m (2000ft) water depth range available.
- Built-in 12-channel GPS, differential GPS ready  
\* Optional RD-200 required
- Cartography supplied by 









NAVIONICS is a registered trademark of NAVIONICS S.p.A.  
Not available in the U.S.A.

### MARINE PLOTTER/SOUNDER FP-561

# OPTIONS FOR VHF HANDHELD TRANSCEIVERS








MODEL NAME	BATTERY CASES			BATTERY PACKS					
	BP-204 AA(R6)×6 cells	BP-223 AA(R6)×6 cells	BP-226 AA(R6)×5 cells	BP-215L 7.4V/1800mAh (Li-Ion)	BP-224 7.2V/750mAh (Ni-Cd)	BP-227 7.2V/1700mAh (Li-Ion)	CM-138 7.2V/900mAh (Ni-Cd)	CM-139 7.2V/1200mAh (Ni-Cd)	CM-165 7.2V/1200mAh (Ni-Cd)
IC-M88									
IC-M88			✓			✓			
IC-M1V				✓					
IC-M2A		✓			✓				
IC-M3A	✓								
IC-GM1500									✓
IC-M15							✓	✓	

MODEL NAME	BATTERY PACKS	DESKTOP CHARGERS			MULTI-CHARGER	BATTERY CHARGERS		
	CM-176 12V/3600mAh (Lithium: non-rechargeable)	BC-119N Rapid charger	BC-150 Regular charger	BC-152 Regular charger	BC-121N Rapid charger	AD-43	AD-49	AD-95
								
IC-M88		✓		✓	✓			
IC-M1V		✓			✓			✓
IC-M2A		✓	✓		✓			
IC-M3A								
IC-GM1500	✓	✓			✓		✓	
IC-M15		✓			✓	✓		




MODEL NAME	CHARGER ADAPTERS				AC ADAPTERS				
	AD-68	AD-100	AD-102	AD-103	BC-122 12V/200mA	BC-124 12V/7A	BC-145 16V/1A	BC-147 12V/300mA	BM-95 12V/300mA
									
IC-M88		(Use with BC-119N/BC-121N)				(Use with BC-121N)	(Use with BC-119N)	(Use with BC-152)	
IC-M1V			(Use with BC-119N/BC-121N)		(Use with AD-95)	(Use with BC-121N)	(Use with BC-119N)		
IC-M2A				(Use with BC-119N/BC-121N)		(Use with BC-121N)	(Use with BC-119N)	(Use with BC-150)	
IC-M3A									
IC-GM1500	(Use with BC-119N/BC-121N)					(Use with BC-121N)	(Use with BC-119N)		(Use with AD-49)
IC-M15	(Use with BC-119N/BC-121N)					(Use with BC-121N)	(Use with BC-119N)		(Use with AD-43)



# OPTIONS FOR VHF HANDHELD TRANSCEIVERS

MODEL NAME	WALL CHARGERS		CIGARETTE LIGHTER CABLES			DC POWER CABLES			
	BC-110D/V 12V/200mA	BC-131A 12V/100mA	CP-1	CP-12L w/noise filter	CP-17L	OPC-254L	OPC-515L	OPC-656	
									
IC-M88					(Use with BC-119N/BC-152)		(Use with BC-119N/BC-152)	(Use with BC-121N)	
IC-M1V					(Use with AD-95/BC-119N)		(Use with AD-95/BC-119N)	(Use with BC-121N)	
IC-M2A					(Use with BC-119N/BC-150)		(Use with BC-119N/BC-150)	(Use with BC-121N)	
IC-M3A	(IC-M3A GEN version)	(IC-M3A U.S.A. version)		✓		✓			
IC-GM1500			(Use with AD-49)		(Use with BC-119N)		(Use with BC-119N)	(Use with BC-121N)	
IC-M15			(Use with AD-43)		(Use with BC-119N)		(Use with BC-119N)	(Use with BC-121N)	





MODEL NAME	MOUNTING BRACKET	BELT CLIPS						SPEAKER MICROPHONES	
	MB-25 Wall type	MB-68	MB-74	MB-79	MB-86	MB-87	MB-88	HM-125 Waterproof	HM-138 Waterproof
									
IC-M88				✓	✓				✓
IC-M1V							✓	✓	
IC-M2A		✓	✓			✓			
IC-M3A		✓	✓			✓			
IC-GM1500	✓								
IC-M15	✓								





MODEL NAME	VOICE SCRAMBLERS								
	UT-79 128 analog voice scramble codes available	UT-98 128 analog voice scramble codes available	UT-112 Total of 32 voice scramble codes available						
									
IC-M88									
IC-M1V		(Version 02)	✓						
IC-M2A									
IC-M3A									
IC-GM1500									
IC-M15	✓								

✓ : Applicable









□ : Not applicable

# OPTIONS FOR VHF FIXED MOUNT TRANSCEIVERS

MODEL NAME	HAND MICROPHONES				COMMANDMIC®	EXTENSION CABLE	FLUSH MOUNT KITS		
	HM-124B/W	HM-126B/W	HM-129B/W	HM-136B/W	HM-127B/W Waterproof	OPC-999 6 m; 20 ft	MB-69	MB-75	
									
IC-M602				✓	✓	✓ (Use with HM-127B/W)		✓	
IC-M502		✓			✓	✓ (Use with HM-127B/W)		✓	
IC-M402			✓		✓	✓ (Use with HM-127B/W)	✓		
IC-M402S			✓				✓		
IC-M45A	✓						✓		








MODEL NAME	EXTERNAL SPEAKERS		VOICE SCRAMBLERS						
	SP-5	SP-10	UT-98 128 analog voice scramble codes available	UT-112 Total of 32 voice scramble codes available					
									
IC-M602			✓	✓					
IC-M502	✓	✓	✓	✓					
IC-M402	✓	✓							
IC-M402S	✓	✓							
IC-M45A	✓	✓							









# OPTIONS FOR HF MARINE TRANSCEIVERS


MODEL NAME	DC POWER SUPPLIES		ANTENNA ELEMENT	FOLDED DIPOLE ANTENNA	ANTENNA MATCHERS		ANTENNA TUNERS		
	PS-60 13.6V/30A	PS-125 13.8V/25A	AH-2b	AH-710	MN-100	MN-100L	AH-4 (Matches amateur bands only)	AT-130	AT-140
									
IC-M802	✓			✓	✓	✓		✓	✓
IC-M710	✓			✓	✓	✓		✓	✓
IC-M700PRO	✓			✓	✓	✓		✓	✓
IC-78		✓	✓	✓	✓	✓	✓	✓	✓
IC-718		✓	✓	✓			✓		



# OPTIONS FOR HF MARINE TRANSCEIVERS

MODEL NAME	ANTENNA TUNER	SHIELDED CONTROL CABLES		HANDSET	HAND MICROPHONES			DESKTOP MICROPHONES	
	AT-180 (Matches amateur bands only)	OPC-566	OPC-1147	HS-50	EM-101	HM-135	HM-36	SM-6	SM-20
									
IC-M802		✓ (Use with AT-130)	✓ (Use with AT-140)			✓			
IC-M710		✓ (Use with AT-130)	✓ (Use with AT-140)	✓	✓				
IC-M700PRO		✓ (Use with AT-130)	✓ (Use with AT-140)	✓	✓				
IC-78		✓ (Use with AT-130)	✓ (Use with AT-140)				✓	✓	✓
IC-718	✓						✓	✓	✓

MODEL NAME	EXTERNAL SPEAKERS				MOBILE BRACKET	CARRYING HANDLE	REMOTE CONTROLLER	SEPARATION CABLE	LINEAR AMPLIFIER
	SP-7	SP-20	SP-21	SP-24	IC-MB5	MB-23	RC-25	OPC-1106	IC-PW1 (Not certified for marine use in the U.S.A. by the FCC)
									
IC-M802				✓			✓	✓	
IC-M710									
IC-M700PRO									
IC-78	✓	✓	✓		✓	✓			
IC-718	✓	✓	✓		✓	✓			✓

MODEL NAME	ACC CABLE ADAPTER	CI-V CONVERTER							
	OPC-599	CT-17							
									
IC-M802									
IC-M710									
IC-M700PRO									
IC-78		✓							
IC-718	✓	✓							

MODEL NAME	FL-100 CW/RTTY (FSK) NARROW FILTER 500Hz/-6dB	455KHZ FILTERS FL-52A: 500Hz/-6dB FL-53A: 250Hz/-6dB FL-222: 1.8kHz/-6dB FL-257: 3.3kHz/-6dB	UT-95 2-TONE ALARM UNIT Provides an alarm function.	UT-102 VOICE SYNTHESIZER Announces an accessed band's frequency, operating mode and S-meter level in English (or Japanese).	UT-106 DSP UNIT Provides AF DSP capability, such as noise reduction and auto notch function.	CR-338 HIGH STABILITY CRYSTAL UNIT Provides improved frequency stability. Frequency stability: ±0.5ppm
	IC-M802					
IC-M710	✓		(Already built-in to some versions)			
IC-M700PRO	✓		(Already built-in to some versions)			
IC-78		✓		✓	✓	✓
IC-718		✓		✓	✓	✓

: Applicable
  : Not applicable

# SPECIFICATIONS

## VHF HANDHELD TRANSCEIVERS

	IC-M88	IC-M1V	IC-M2A	IC-M3A	IC-GM1500	IC-M15
<b>Frequency range (Unit:MHz)</b>	Tx: 156.025–157.425 Rx: 156.050–163.275 146–174 (LMR; Tx/Rx)	Tx: 156.025–157.425 Rx: 156.025–163.275	Tx: 156.025–157.425 Rx: 156.050–163.275	Tx: 156.025–157.425 Rx: 156.025–163.275	156.300–156.875 (Tx/Rx)	Tx: 156.025–157.425 Rx: 156.025–163.275
<b>Dimensions (projections not included; W×H×D)</b>	62×97×39 mm 2 <sup>7</sup> / <sub>16</sub> ×3 <sup>13</sup> / <sub>16</sub> ×1 <sup>17</sup> / <sub>32</sub> in	52.5×129×30 mm 2 <sup>1</sup> / <sub>16</sub> ×5 <sup>3</sup> / <sub>32</sub> ×1 <sup>3</sup> / <sub>16</sub> in	61×135×41 mm 2 <sup>13</sup> / <sub>32</sub> ×5 <sup>5</sup> / <sub>16</sub> ×1 <sup>5</sup> / <sub>8</sub> in	58×140.5×43.5 mm 2 <sup>9</sup> / <sub>32</sub> ×5 <sup>17</sup> / <sub>32</sub> ×1 <sup>23</sup> / <sub>32</sub> in	68.5×165.5×45.3 mm 2 <sup>11</sup> / <sub>16</sub> ×6 <sup>1</sup> / <sub>2</sub> ×1 <sup>25</sup> / <sub>32</sub> in	62×150×44 mm 2 <sup>13</sup> / <sub>32</sub> ×5 <sup>29</sup> / <sub>32</sub> ×1 <sup>11</sup> / <sub>16</sub> in
<b>Weight</b>	280g; 9.9oz (With BP-227)	280g; 9.9oz (With BP-215L)	360g; 12.7oz (With BP-224)	410g; 14.4oz	515g; 1.1lb (with CM-165)	460g; 1.0lb (with CM-138)
<b>Current drain</b>	<b>Transmit (High)</b>	1.6A typ.	1.5A typ.	1.5A typ.	1.6A typ.	1.5A
	<b>Max. audio</b>	200mA typ.	200mA typ.	200mA typ.	230mA typ.	500mA
	<b>Stand-by</b>	20mA typ.	20mA typ.	20mA typ.	60mA typ.	15mA typ.
<b>Sensitivity (at 12dB SINAD)</b>	0.25μV typ.	0.25μV typ.	0.25μV typ.	0.25μV typ.	0.35μV (at 20dB SINAD)	0.35μV typ.
<b>Intermodulation rejection</b>	70dB typ.	70dB typ.	70dB typ.	70dB	68dB	60dB
<b>Audio output power (With an 8Ω load)</b>	350mW typ.	350mW typ.	350mW typ.	500mW	500mW	500mW
<b>RF output power</b>	5/3/1W	5/1/0.5W	5/3/1W	5/1W	2/0.8W	5/0.7W

Measurements made in accordance with EIA-152C and EIA-204D(E).

## VHF FIXED MOUNT TRANSCEIVERS

	IC-M602	IC-M502	IC-M402 IC-M402S	IC-M45
<b>Frequency range (Unit:MHz)</b>	Tx: 156.025–157.425 Rx: 156.050–163.275	Tx: 156.025–157.425 Rx: 156.050–163.275	Tx: 156.025–157.425 Rx: 156.050–163.275	Tx: 156.025–157.425 Rx: 156.025–163.275
<b>Power supply requirement</b>	13.8V DC ±15%	13.8V DC ±15%	13.8V DC ±15%	13.8V DC ±15%
<b>Dimensions (projections not included; W×H×D)</b>	220×110×109.4 mm 8 <sup>21</sup> / <sub>32</sub> ×4 <sup>11</sup> / <sub>32</sub> ×4 <sup>9</sup> / <sub>16</sub> in	165×110×84.4 mm 6 <sup>1</sup> / <sub>2</sub> ×4 <sup>11</sup> / <sub>32</sub> ×3 <sup>9</sup> / <sub>32</sub> in	153×67×141.6 mm 6 <sup>1</sup> / <sub>32</sub> ×2 <sup>9</sup> / <sub>8</sub> ×5 <sup>9</sup> / <sub>16</sub> in	152×67×140 mm 6×2 <sup>9</sup> / <sub>8</sub> ×5 <sup>1</sup> / <sub>2</sub> in
<b>Weight</b>	1.35kg; 3.0lb	1.13kg; 2.5lb	900g; 2lb	900g; 2lb
<b>Current drain</b>	<b>Transmit (High)</b>	5.2A typ.	6.0A	6.0A
	<b>Max. audio output</b>	1.2A typ.	1.2A	1.2A
<b>Sensitivity (at 12dB SINAD)</b>	0.32μV	0.25μV	0.25μV	0.22μV
<b>Intermodulation rejection</b>	80dB	80dB	70dB	70dB
<b>Audio output power (With a 4Ω load)</b>	5W typ.	3.5W typ.	4.5W typ.	4.0W typ.
<b>RF output power</b>	25/1W	25/1W	25/1W	25/1W

Measurements made in accordance with TIA/EIA 603.

## HF MARINE TRANSCEIVERS

	IC-M802	IC-M710	IC-M700PRO	IC-78 IC-718
<b>Frequency range (Unit:MHz)</b>	Tx: 1.6–2.9999, 4.0–4.9999, 6.0–6.9999, 8.0–8.9999, 12.0–13.9999, 16.0–17.9999, 18.0–18.9999, 22.0–22.9999, 25.0–27.5000 Rx: 0.5–29.9999			Tx: 1.6–29.9999* Rx: 0.03–29.9999 (Guaranteed : 0.5–29.9999)
<b>Power supply requirement</b>	13.6V DC ±15% (negative ground)	13.6V DC ±15% (negative ground)	13.6V DC ±15% (negative ground)	13.8V DC ±15% (negative ground)
<b>Dimensions (projections not included; W×H×D)</b>	Main unit: 240×94×238.4 mm; 9 <sup>7</sup> / <sub>16</sub> ×3 <sup>11</sup> / <sub>16</sub> ×9 <sup>9</sup> / <sub>16</sub> in Controller unit: 220×110×84.4 mm; 8 <sup>21</sup> / <sub>32</sub> ×4 <sup>11</sup> / <sub>32</sub> ×3 <sup>9</sup> / <sub>16</sub> in	291.4×116.4×315 mm 11 <sup>15</sup> / <sub>32</sub> ×4 <sup>19</sup> / <sub>32</sub> ×12 <sup>13</sup> / <sub>32</sub> in	291.4×116.4×315 mm 11 <sup>15</sup> / <sub>32</sub> ×4 <sup>19</sup> / <sub>32</sub> ×12 <sup>13</sup> / <sub>32</sub> in	240×95×239 mm 9 <sup>7</sup> / <sub>16</sub> ×3 <sup>3</sup> / <sub>4</sub> ×9 <sup>13</sup> / <sub>32</sub> in
<b>Weight</b>	Main unit: 4.7kg; 10.4lb, Controller unit: 570g; 1.3lb	7.9kg; 17.4lb	7.9kg; 17.4lb	3.8kg; 8.4lb
<b>Current drain</b>	<b>Transmit (High)</b>	30A typ. at max. power	30A at max. power	30A at max. power
	<b>Max. audio output</b>	3.0A	2.5A	2.5A
<b>Sensitivity (at 10dB S/N; except 0.5–1.7999MHz)</b>	J3E, A1A, J2B, F1B : 0.5μV H3E : 3.2μV	J3E, J2B, F1B, R3E, A1A (12dB SINAD) : 0.5μV H3E : 3.2μV	J3E, J2B, F1B, R3E, A1A : 0.5μV H3E : 3.2μV	SSB, CW, RTTY : 0.16μV AM : 2.0μV typ.
<b>Selectivity</b>	J3E, R3E, J2B, A1A : 2.4kHz/–6dB 3.6kHz/–60dB	J3E, R3E, J2B, A1A : 2.3kHz/–6dB 4.2kHz/–60dB	J3E, R3E, J2B, A1A : 2.3kHz/–6dB 4.2kHz/–60dB	SSB, CW, RTTY : 2.1kHz/–6dB 4.5kHz/–60dB AM : 6.0kHz/–6dB 20kHz/–60dB
<b>Audio output power (With a 4Ω load)</b>	4.0W	4.5W	4.5W	2.0W (with a 8Ω load)
<b>RF output power (PEP) (output power differs depending on version)</b>	150/60/20W	150/60/20W (below 24MHz) 60/20W (above 24MHz)	150/60/20W (below 24MHz) 60/20W (above 24MHz)	SSB, CW, RTTY : 2–100W AM : 2–40W

\*IC-78 : Not guaranteed for some frequency bands.  
IC-718 : Restriction may be applied depending on version.



# SPECIFICATIONS

## MARINE RADAR

		MR-1000R	MR-1000T	MR-570R	
General	Minimum range	25m (when measurement range is 1/8 NM)	25m (when measurement range is 1/8 NM)	25m (when measurement range is 1/8 NM)	
	Maximum range	36NM	48NM	36NM	
	Power supply requirement	10.2-42V DC	10.2-42V DC	10.2-42V DC	
	Power consumption	50W	60W	47W	
Display	Display (pixels)	10" monochrome CRT (640×480)	10" monochrome CRT (640×480)	5.7" monochrome LCD (320×240)	
	Usable temperature range	-15°C to +55°C; +5°F to +131°F	-15°C to +55°C; +5°F to +131°F	-15°C to +55°C; +5°F to +131°F	
	Dimensions (W×H×D) (projections not included)	269×264×258 mm 10 <sup>19</sup> / <sub>32</sub> ×10 <sup>13</sup> / <sub>32</sub> ×10 <sup>5</sup> / <sub>32</sub> in	269×264×258 mm 10 <sup>19</sup> / <sub>32</sub> ×10 <sup>13</sup> / <sub>32</sub> ×10 <sup>5</sup> / <sub>32</sub> in	186×203×103 mm 7 <sup>5</sup> / <sub>16</sub> ×8×4 <sup>1</sup> / <sub>16</sub> in	
	Weight	6.5kg; 14.3lb	6.5kg; 14.3lb	2kg; 4.4lb	
Scanner	Type	60cm (2ft) slotted wave-guided array in radome	1.2m (3.9ft) slotted wave-guided array	60cm (2ft) slotted wave-guided array in radome	
	Peak output power	4kW (PEP)	4kW (PEP)	4kW (PEP)	
	Rotation speed	24-48rpm typ.	24-48rpm typ.	24-48rpm typ.	
	Beamwidth	Horizontal	4° typ.	2° typ.	4° typ.
		Vertical	22° typ.	25° typ.	22° typ.
	Intermediate frequency	60MHz	60MHz	60MHz	
	Transmission frequency	9410MHz ±30MHz	9410MHz ±30MHz	9410MHz ±30MHz	
	Usable temperature range	-25°C to +70°C; -13°F to +158°F	-25°C to +70°C; -13°F to +158°F	-25°C to +70°C; -13°F to +158°F	
	Dimensions (projections not included)	607(d)×243(H) mm 23 <sup>29</sup> / <sub>32</sub> (d)×9 <sup>9</sup> / <sub>16</sub> (H) in	1205(d)×381(H) mm 47 <sup>7</sup> / <sub>16</sub> (d)×15(H) in	607(d)×243(H) mm 23 <sup>29</sup> / <sub>32</sub> (d)×9 <sup>9</sup> / <sub>16</sub> (H) in	
	Weight	9kg; 19.8lb	17kg; 37.5lb	9kg; 19.8lb	
Cables	Connection cable length between display and scanner	15m; 49.2ft (OPC-989, standard) 20m; 65.6ft (OPC-1077, option) 30m; 98.4ft (OPC-1078, option)	20m; 65.6ft (OPC-1189, standard) 30m; 98.4ft (OPC-1078, option)	10m; 32.8ft (OPC-1075, standard) 20m; 65.6ft (OPC-1077, option) 30m; 98.4ft (OPC-1078, option)	

## MARINE PLOTTER/SOUNDER

		FP-561
General	Display (pixels)	5.6" TFT color LCD (320×234)
	Power supply	11-30V DC
	Power consumption	22W
	Usable temperature range	±0°C to +50°C; +32°F to 122°F
	Dimensions (W×H×D) (projections not included)	186×203×102 mm
	Weight	2.2kg
	Unit of	Water depth
Water temperature		°C, °F
Speed		KT (knots), km/h, MI/h (miles/h)
Distance		NM (nautical miles), km, MI (miles)
GPS	Receive system	12 parallel-channel, all-in view
	Data renewed interval	1 sec.
Plotter	Scale setting	16 steps
	Plotting interval	5 sec. to 60 min., 0.01-9.99NM*
	No. of track memories	5000
	No. of route memories	20 (50 points/route)
	Color presentation	7 colors
Video sounder	Ultrasonic frequencies	50kHz, 200kHz
	Output power	500W rms
	Depth ranges	5-640m* in 8 colors indication
	Measurable water temperature range	±0°C to +40°C; +32°F to 104°F
	Measurable vessel speed range	0.0-99.9KT*
	Bottom expansion ranges	5, 10, 20 or 40m*
	Phase shift ranges	1-640m*

\* Selectable in each unit



### Applicable U.S. Military Specifications

Icom makes rugged products that meet MIL-STD requirements and strict environmental standards as follows.

Standard	Low pressure		High temperature		Low temperature		Temperature shock	Solar radiation	Rain																				
Method/Procedure	500.1/I	500.2/II, II	500.3/II	500.4/II, II	501.1/I	501.2/II	501.3/II	501.4/II, II	502.1/I	502.2/II	502.3/II	502.4-3/II, II	503.1/I	503.2/II	503.3/II	503.4/II	505.1/I	505.2/II	505.3/II	505.4/II	506.1/II, II	506.2/II, II	506.3/II, II	506.4/II, III					
Applicable MIL-810 series	C	D	F	T	C	D	F	T	C	D	F	T	C	D	F	T	C	D	F	T	C	D	F	T	C	D	F	T	
IC-M88	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IC-M1V	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IC-M2A	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IC-M3A	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IC-M602	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IC-M45	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Standard	Humidity	Salt fog	Vibration	Shock
Method/Procedure	507.1/I, II	507.2/II, III	507.3/III	507.4
Applicable MIL-810 series	C	D	F	T
IC-M88	✓	✓	✓	✓
IC-M1V	✓	✓	✓	✓
IC-M2A	✓	✓	✓	✓
IC-M3A	✓	✓	✓	✓
IC-M602	✓	✓	✓	✓
IC-M45	✓	✓	✓	✓



**Icom Inc.** 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

**Count on us!**

**Icom America Inc.**

<Corporate Headquarters>  
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.  
Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509  
URL : <http://www.icomamerica.com>  
<Customer Service> Phone: +1 (425) 454-7619

**Icom Canada**

Glenwood Centre #150-6165 Highway 17,  
Delta, B.C., V4K 5B8, Canada  
Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090  
URL : <http://www.icomcanada.com>

**Icom (Australia) Pty. Ltd.**

A.B.N. 88 006 092 575  
290-294 Albert Street, Brunswick, Victoria, 3056, Australia  
Phone: +61 (03) 9387 0666 Fax: +61 (03) 9387 0022  
URL : <http://www.icom.net.au>

**Icom New Zealand**

146A Harris Road, East Tamaki, Auckland, New Zealand  
Phone: +64 (09) 274 4062 Fax: +64 (09) 274 4708  
URL : <http://www.icom.co.nz>

**Icom (Europe) GmbH**

Communication Equipment  
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany  
Phone: +49 (0211) 346047 Fax: +49 (0211) 333639  
URL : <http://www.icomeurope.com>

**Icom Spain S.L.**

Crta. de Gracia a Manresa Km. 14,750  
08190 Sant Cugat del Valles Barcelona, SPAIN  
Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46  
URL : <http://www.icomspain.com>

**Icom (UK) Ltd.**

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.  
Phone: +44 (01227) 741741 Fax: +44 (01227) 741742  
URL : <http://www.icomuk.co.uk>

**Icom France S.a**

Zac de la Plaine, 1, Rue Brindejonc des Moulinais  
BP 5804, 31505 Toulouse Cedex, France  
Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00  
URL : <http://www.icom-france.com>

**Asia Icom Inc.**

6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.  
Phone: +886 (02) 2559 1899 Fax: +886 (02) 2559 1874  
URL : <http://www.asia-icom.com>

**Beijing Icom Ltd.**

1305, Wanshang Plaza, Shijingshan Road, Beijing, China  
Phone: +86 (010) 6866 6337 Fax: +86 (010) 6866 3553  
URL : <http://www.bjicom.com>



Certificate Number Q14190  
Icom Inc. (Japan), is an ISO9001 certification\* acquired company.  
\*All products in this catalog, except for Marine Radar and Marine Plotter/sounder, conform to ISO9001 certification.

Your local distributor/dealer: