

Page 57

To change the transmittable signals for operating another manufacturer's TV _____

Error	Correction
<p>4. Enter manufacturer's code (three digits) using buttons 1 – 9, and 0. See the list on pages 59 and 60 to find the code. Examples: For a JVC product, press 0, 5, then 3. For a Hitachi product, press 0, 5, then 6.</p>	<p>4. Enter manufacturer's code (two digits) using buttons 1 ~ 9, and 0. See the list on below to find the code. Examples: For a JVC product, press 0 then 1. For a Hitachi product, press 1 then 0.</p>

Page 58

To change the transmittable signals for operating a CATV converter or DBS tuner _____

Error	Correction
<p>4. Enter manufacturer's code (three digits) using buttons 1–9, and 0. See the list on page 60 to find the code. Examples: For a JVC product, press 7, 7, then 5. For a Pioneer product, press 1, 4, then 4.</p>	<p>4. Enter manufacturer's code (two digits) using buttons 1 ~ 9, and 0. See the list on below to find the code. Examples: For a Echostar product, press 2 then 1. For a Pioneer product, press 1 then 3.</p>

Page 58

To change the transmittable signals for operating another manufacturer's VCR _____

Error	Correction
<p>4. Enter manufacturer's code (three digits) using buttons 1–9, and 0. See the list on pages 61 and 62 to find the code. Examples: For a JVC product, press 0, 0, then 8. For a Funai product, press 0, 0, then 0.</p>	<p>4. Enter manufacturer's code (two digits) using buttons 1 ~ 9, and 0. See the list on below to find the code. Examples: For a JVC product, press 0 then 1. For a Funai product, press 1 then 0.</p>