

Specifications

AIM5 ANALOG INPUT MODULE 5

Input channels: 4 low level, isolated from each other and ground

Input characteristics.

Gain: x100, user configurable for other gains with optional resistor

Input range: $\pm 50\text{mV}$ max

Accuracy:

Gain: $\pm 0.2\%$, adjustable to 1 lsb

Gain linearity: $\pm 0.02\%$ max

Input offset: $\pm 20\mu\text{V}$ max, adjustable to zero

Output offset: $\pm 12\text{mV}$ max, adjustable to zero

Temperature coefficient:

Gain: $\pm 0.005\%/^{\circ}\text{C}$

Input offset: $\pm 2.5\mu\text{V}/^{\circ}\text{C}$

Output offset: $\pm 50\mu\text{V}/^{\circ}\text{C}$

Input noise voltage: $1\mu\text{V}$ p-p, 0.01Hz to 100Hz, $R_S < 1\text{kohm}$

Input bias current: $+ 8\text{nA}$ max

Input resistance: 100Mohms

Protection: 130V RMS max, normal mode

Isolation: 500V peak, channel to channel or channel to ground

Common mode rejection: 130db, $R_S < 100$ ohms, $f \leq 60\text{Hz}$

Normal mode rejection: 55db, $f \geq 50\text{Hz}$

Settling time after channel selection: 2.5 ms to 0.01% assuming settled input

Temperature reference junction sensor:

Output: $100\text{mV}/^{\circ}\text{C}$

Accuracy: $\pm 0.25^{\circ}\text{C}$

Temperature coefficient: $0.1^{\circ}\text{C}/^{\circ}\text{C}$

LTR	REVISIONS	APP.	DATE	DRN.	DATE	KEITHLEY Keithley Instruments Inc. Cleveland, Ohio 44139		
A	RELEASED 9/87		1/1-82	CKD.	DATE		SPECIFICATIONS	PART NUMBER
				APP.	DATE			SPEC-AIM5