

PART NUMBER
SPEC-AOMI

Specifications

AOMI ANALOG OUTPUT MODULE 1

Output channels: 5

Output ranges: $\pm 2.5V$, $\pm 5V$, $\pm 10V$, 0 to +5V, 0 to + 10V, switch selectable for each channel

Resolution: 12 bits, 1 part in 4096

Nonlinearity: $\pm 0.012\%$ of F.S. ($\pm 1/2$ lsb) max

Output impedance: 0.1 ohms

Load characteristics: 5k ohm min, 1000pf max
short circuit protected

Slew rate. 15 V/us


Settling time: 5us to 0.01% of full scale transition

Temperature Coefficient.

Gain: 0.0016%/°C of F.S., unipolar ranges
0.0023%/°C of F.S.*, bipolar ranges

Offset: 0.0006%/°C of F.S., unipolar ranges
0.0010%/°C of F.S.*, bipolar ranges

* Full scale for bipolar ranges is defined as $-V_{F.S.}$ to $+ V_{F.S.}$

LTR	REVISIONS	APP.	DATE	DRN.	DATE	 Keithley Instruments Inc. Cleveland, Ohio 44139
A	RELEASED PART		11-83	CKD.	DATE	
				APP.	DATE	
				SPECIFICATIONS		PART NUMBER
						SPEC-AOMI