

S41/RF1X72 Multiplexer

RF PARAMETERS:

Frequency	DC-8GHz	8-18GHz
Insertion Loss	1.0 dB max	2.5 dB max
VSWR	1.5:1	2.0:1
Isolation	70 dB min	60 dB min

SWITCH CONFIGURATION: One 1x72 or two 1x36 or fourteen 1x6 coaxial multiplexers when RF cables are removed.

IMPEDANCE: 50Ω.

ACTUATION TIME: 15ms

RF CONTACTS: Break-before-make, normally open

OPERATING LIFE: 1,000,000 operations, cold switched.

SUPPLIED ACCESSORIES

LIGHT PEN Provides interactive programming of channels, cross points, scan lists, and memory.

OPTIONAL ACCESSORIES

8503 **DIN to BNC Trigger Cable:** Provides BNC connector interface to hardware trigger lines.

S41-RMK-1 **Fixed Rack Mount Kit:** Enables rack mounting without chassis support for one System 41 Mainframe.

ORDERING INFORMATION

S41/RF1X72 1x72 RF coaxial multiplexer switch system

S41/RF1X72-T Test data on the RF module – must be purchased at the same time the switch system is purchased

GENERAL

DISPLAY: Dual line vacuum fluorescent.

1st Line: 20-character alphanumeric.

2nd Line: 32-character alphanumeric.

Channel status LED grid.

IEEE-488 BUS IMPLEMENTATION: Conforms to SCPI-1990, IEEE-488.2 and IEEE-488.1.

REAR PANEL CONNECTORS:

SMA

IEEE-488

8-pin micro DIN for Trigger Link

8-pin micro DIN for Trigger Link expansion

POWER: 100-240V AC universal input, 50-60Hz, 270VA maximum.

STANDARDS:

Safety: Conforms with European Union Directive 73/23/EEC.

EMC: Conforms with European Union Directive 89/336/EEC

ENVIRONMENT:

Operating: 0°C to 50°C, <80% relative humidity (0°C to 35°C)

Storage: -25°C to +65°C


DIMENSIONS, WEIGHT: 178mm high x 482mm wide x 515mm deep (7 in x 19 in x 20 in). Net weight 10kg (21 lbs).

RACK MOUNTING: Standard 19" rack shelf or chassis support angles.

Specifications subject to change without notice.

SBG 3/21/00
Rev. A

BRUNING 40-21 62198-SBG

LTR	REVISIONS	APP.	DATE	DRN.	DATE	 Keithley Instruments, Inc. Cleveland, Ohio 44139
				CKD.	DATE	
				APP.	DATE	
				<h2 style="margin: 0;">SPECIFICATIONS</h2>		PART NUMBER