


KENWOOD



KFC-W308 Design Specifications for Ported & Iso-vent Enclosures

BOX SIZE cu. ft.	TUNING FREQ.	PORT DIA.	NUMBER OF PORTS	PORT LENGTH	NUMBER OF DRIVERS	3dB DOWN POINT	RIPPLE
0.8	46	4"	1	17"	1	46	0
0.8	48	4"	1	15.5	ISO-VENT	48	2
0.8	55	4"	1	17"	ISO-VENT	50	2
0.8	56	4"	1	10.56"	1	51	2
1	46	3"	2	15"	ISO-VENT	44	0
1	54	3"	3	16"	ISO-VENT	48	2
1	46	4"	1	13"	1	43	0
1	54	4"	1	8.75"	1	47	2
1	58	3"	2	8.25"	2	58	2
1.2	45	3"	1	5.68"	1	42	0
1.2	46	4"	1	10.5"	ISO-VENT	42	0
1.2	52	4"	2	16.8"	ISO-VENT	45	2
1.2	52	4"	1	7.56"	1	45	2
1.2	58	3"	2	6.356"	2	54	2
1.4	45	3"	1	4.556"	1	40	0
1.4	50	4"	1	6.82"	1	43	2
1.4	58	3"	2	5"	2	52	2
1.6	48	4"	1	6.322"	1	41	2
1.6	56	3"	2	4.5"	2	50	2
1.8	46	4"	1	6.025"	1	39	2

Dia.	fs	Qts	Qes	Qms	Vas	Z	re	Pt	Xmax	Sens.	Le	VC dia.
8"	45 Hz	.396	.433	4.667	.97 cu. ft.	.97 cu. ft.	3.38	300W	.646	89dB	.056 mH	