


KENWOOD




KFC-W3082

Design Specifications for Ported Enclosures

Vb (cu.ft.)	Fb (Hz)	Port Dia. (in.)	Port Length (in.)	f3 (Hz)	Ripple (dB)
1.5	35	3	8.17	37.4	3
1.5	32	3	10.21	37.6	3
1.5	35	2.5	5.37	37.4	3
1.5	32	2.5	6.78	37.6	3
1.5	35	2	3.14	37.4	3
1.5	32	2	4.05	37.6	3
1.75	34.8	3	6.79	35.1	3
1.75	33.5	3	7.51	35	3
1.75	34.8	2.5	4.41	35.1	3
1.75	33.5	2.5	4.91	35	3
1.75	34.8	2	2.53	35.1	3
1.75	33.5	2	2.85	35	3
2	35	3	5.58	33.2	3
2	32	3	7.11	33.1	3
2	35	2.5	3.57	33.2	3
2	32	2.5	4.63	33.1	3
2	35	2	1.99	33.2	3

KENWOOD



KFC-W3082

Design Specifications for Ported Enclosures

2	32	2	2.67	33.1	3
2.25	37	4	8.07	32.6	4
2.25	37	3	3.99	32.6	4
2.25	34	3	5.13	31.6	3
2.25	37	2.5	2.47	32.6	4
2.25	34	2.5	3.26	31.6	3
2.25	37	2	1.29	32.6	4

Thiele/Small Parameters

Dia.	Z	Fs	Vas	Qts	Qes	Qms	Xmax
12	8	34.8	2.13	.61	.65	9.5	.11