

COMMUNICATIONS SPEAKER

# SP-23

## INSTRUCTION MANUAL

# KENWOOD

KENWOOD CORPORATION

© PRINTED IN JAPAN B62-0154-00(MKT)  
92/6 5 4 3 2 1 91/12 11 10 9 8 7 6 5 4

The SP-23 is a midrange speaker designed for use with any receiver or transceiver. The SP-23 can be used in place of the transceiver's built-in speaker for greater clarity and improved tone. The speaker cabinet matches the transceiver front panel to provide a clean looking, integrated station.

### ■ SPECIFICATIONS

SPEAKER SIZE	:	3" (75 mm)
RATED INPUT	:	1.0 W
IMPEDANCE	:	8 $\Omega$
FREQUENCY RESPONSE	:	300 Hz to 5 kHz
DIMENSIONS (excluding feet)	:	W123 mm (4-13/18") $\times$ H96 mm (3-3/4") $\times$ D235 mm (9-1/4")
WEIGHT	:	1.3 kg (2.8 lbs.)

### ■ ACCESSORIES INCLUDED

SPEAKER CABLE ASSY.	:	E30-1629-15	...	1 ea.
INSTRUCTION MANUAL	:	B62-0154-XX	...	1 copy

### ■ OPERATION

The SP-23 is supplied with a 3 foot speaker cord. Simply connect the speaker cord to the EXTERNAL SPEAKER jack on the transceiver for operation. The transceiver's internal speaker will be disconnected.

The bail on the front bottom of the cabinet can be used to raise the front panel.

