

MODEL 984A
ATTENUATOR
OPERATION MANUAL

KIKUSUI ELECTRONICS CORP.



GENERAL

The Model 984A is Attenuator with four dials. The Specification is mentioned below.

SPECIFICATION

Dimensions	335(W) x 105(H) x 125(D) mm
Weight	Approx. 3.7 kg
Frequency response	0 ~ 150 kHz
Attenuation	0 ~ 121 dB 0.1 dB step
Impedance	600 Ω \pm 10 Ω unbalance
Attenuator accuracy	

Attenuation	0 ~ 50 kHz	0 ~ 150 kHz
0 ~ 5 dB	\pm 0.05 dB	\pm 0.1 dB
5.1 ~ 40 dB	\pm 0.1 dB	\pm 0.2 dB
40.1 ~ 91 dB	\pm 0.2 dB	\pm 0.5 dB
91.1 ~ 121 dB	\pm 0.5 dB	\pm 1 dB

OPERATING INSTRUCTION

1. Use of instrument in the frequency higher than specified may introduce the additional error.
2. Terminate properly the output terminals with a 600 Ω resistor to obtain current attenuator.
3. Input level should not be exceeded more than the rated value, + 30dBm which is approximately 24.5 volts.

984A形 可变抵抗減衰器接統圖

