Kurz·Kasch, Inc.

Electronics Division
Box 1246 • 2271 Arbor Blvd.
Dayton, Ohio 45439
Telephone (513) 299-0990

Operating Instructions

For Model ___406A___

SUPER PAC MAN

MIDWAY

```
            SL2                        START 2                    SR2                           5V
                  x                          x       x                          x
   LLP        SL1         SL3          LRP                RLP        SR1       SR3         RRP
                  SL5                              x                          SR5                ON      OFF
                                                START1
      x          x     x     x                  x      x      x           x     x      x
                  SL4                                                         SR4                   x
   SL6                   SL7                   COIN                 SR6             SR7         POWER
      x                   x                     x                   x               x     x

                                                                                              ON      OFF
```

1. Insert 406A card into slot "A" number side up.

2. Connect 11-pin connector to circuit board, note the key position.

3. Connect 9-pin connector to circuit board, note the key position.

4. Connect 20-pin connector to circuit board, note key position.

5. Connect 10-pin connector to circuit board, note key position.

6. Turn 5V and power to ON position.

7. Controls are:

```
   COIN--------COIN 1
   SR6---------COIN 2
   START 1-----PLAYER 1 START
   START 2-----PLAYER 2 START
   SR1---------MOVE LEFT
   SR2---------MOVE UP
   SR3---------MOVE RIGHT
   SR4---------MOVE DOWN
   SR5---------MOVE FAST WHEN SUPER PAC MAN
   SL1---------MOVE LEFT
   SL2---------MOVE UP
   SL3---------MOVE RIGHT                     }  2-player
   SL4---------MOVE DOWN                      }  cocktail mode
   SL5---------MOVE FAST WHEN SUPER PAC MAN   }
   SL6---------TILT SWITCH
   SL7---------SERVICE SWITCH
   TEST SWITCH IS ON CARD.
```

8. Connect speaker to short wires on 9-pin connector.