



## A

Acquisition, 4, 5, 6  
Amplitude  
  External Clock, 13  
  External Reference, 2  
  Trigger Comparator, 7

## C

Calibration, 16  
Calibration, 17, 18, 19

## D

Delay, 4, 6

## E

External Clock, 1, 13, 16, 17, 18  
  Amplitude, 13, 17  
  Calibration, 18, 19  
  clock source, 18  
  enabling it, 15  
  Gated Clock, 18  
  Input Impedance, 13  
  Max. Input Voltage, 13  
  Mean, 17  
  Minimum Slew Rate, 13  
  number of cycles, 18  
  RMS, 17  
  Sampling Uncertainty, 13  
  Swept Clock, 14  
External Reference, 1, 2, 4  
  Amplitude, 2  
  enabling it, 3  
  Frequency Range, 2  
  Maximum Input Voltage, 2  
  Offset, 2  
  Sampling Uncertainty, 2  
External vs Internal Reference, 6

## F

Frequency Range  
  External Reference, 2

## G

Gated Clock, 18

## H

Histograms, 4

## I

Input Impedance  
  External Clock, 13  
  External Reference, 2  
Internal vs External Reference, 5

## J

Jitter, 4, 5, 6

## M

Maximum Input Voltage  
  External Clock, 13  
  External Reference, 2  
Minimum Slew Rate  
  External Clock, 13

## O

Offset  
  External Reference, 2

## P

Phase-lock, using an external  
  reference, 1, 2  
Phase-synchronization, 1, 2  
Pulse Width, 7, 8

---

**R**

RECALIBRATE, 17  
Recalibration, 18  
Ref. Clock menu, 16  
REFERENCE\_CLOCK, RCLK,  
  Command/Query, 3, 20  
Remote Control, 20

**S**

Sample Rate  
  tuning it using external  
  clock, 1  
SAMPLE\_CLOCK, SCLK,  
  Command/Query, 21  
Sampling time, 4, 6  
Sampling Uncertainty  
  External Clock, 13  
  External Reference, 2

SPECIAL MODES, 3  
Swept Clock, 14  
Synchronization, 1, 2, 4, 6

**T**

TIMEBASE, 3, 18  
Trigger Comparator, 1, 7, 8  
  Amplitude, 7  
  Max. externally-applied  
  voltage, 7  
  Pulse Width, 7, 8  
  Trigger conditions, 8

**U**

UTILITIES, 3

---