



6910, 6920 & 6930 series RF Power Sensors

A range of 17 power sensors available for use with 6200B series MTS, CPM, 6960B and 6970 power meters



- Wide frequency coverage 30 kHz to 46 GHz
- Power levels from -70 dBm (100 pW) to +44 dBm (25 W)
- 50 Ω and 75 Ω sensors
- Low VSWR reduces measurement uncertainty
- Linearity correction data supplied
- Field replaceable RF assembly
- High overload capability

These stable and accurate power sensors operate at frequencies up to 46 GHz. They are for use with the 6960B and 6970 Power Meters as well as the CPM 20, 40 Counter Power Meter and the

6200B series Microwave Test Set.

High Measurement Accuracy

High measurement accuracy over a wide frequency range is ensured by low input VSWR - the result of innovative design.

Fully Interchangeable

The sensors are fitted with precision connectors. They have a multiway socket for cable connection to the Power Meter, and are interchangeable.

Small and Lightweight

The small size and light weight of these sensors makes them very adaptable for use anywhere without requiring additional mechanical support.

Rugged Construction

Rugged mechanical construction makes

them ideal for both bench and field use. Minimum down-time is ensured by using a pre-calibrated field replaceable RF sensing assembly. Unit lifetime is enhanced by high overload capabilities. Seventeen different sensors are currently available covering a range of frequencies from 30 kHz to 46 GHz. Type N, APC-7, MPC 3.5 and 2.92 mm connectors are available from -70 dBm (100 pW) to +44 dBm (25 W). A 75 Ω sensor is also available.

For the 40 GHz sensors (6914, 6924 and 6934) a waveguide 22 transformer is optionally available. By ordering version '002' the transformer (54417/002) is supplied as well as a calibration table to give both accurate waveguide and coaxial measurements. The calibration information is traceable to national standards.

6910 series: Medium Power Thermocouple Power Sensors

	6910	6911	6912
FREQUENCY RANGE	10 MHz - 20 GHz	10 MHz - 20 GHz	30 kHz - 4.2 GHz
POWER RANGE	-30 dBm to +20 dBm (1 μW to 100 mW)	-30 dBm to +20 dBm (1 μW to 100 mW)	-30 dBm to +20 dBm (1 μW to 100 mW)
MAX RF INPUT	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μs	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μs	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μs
SENSING ELEMENT	Semiconductor thermocouple	Semiconductor thermocouple	Semiconductor thermocouple
VSWR	1.25 10 MHz - 30 MHz 1.1 30 MHz - 2GHz 1.18 2 GHz - 16 GHz 1.28 16 GHz - 18 GHz 1.4 typical 18 GHz - 20 GHz †	1.25 10 MHz - 30 MHz 1.15 30 MHz - 2 GHz 1.18 2 GHz - 16 GHz 1.28 16 GHz - 18 GHz 1.4 typical 18 GHz - 20 GHz †	1.6 30 kHz - 100 kHz 1.2 100 kHz - 300 kHz 1.1 300 kHz - 4.2 GHz
LINEARITY FACTOR	Provided with sensor	Provided with sensor	Provided with sensor
Accuracy	±0.5% at 25°C between +10 and +20 dBm Improves by a factor of 10 for each lower range	±0.5% at 25°C between +10 and +20 dBm Improves by a factor of 10 for each lower range	±0.5% at 25°C between +10 and 20 dBm Improves by a factor of 10 for each lower range
CALIBRATION FACTOR	Provided with sensor	Provided with sensor	Provided with sensor
Accuracy	Uncertainty provided with sensor	Uncertainty provided with sensor	Uncertainty provided with sensor
Resolution	0.01%	0.01%	0.01%
RF CONNECTOR	Precision N-type, male 50 Ω	APC-7, 50 Ω	Precision N-type, male 50 Ω
SIZE & WEIGHT	87 mm long, 33.5 mm dia. 140g	87 mm long, 33.5 mm dia. 140 g	87 mm long, 33.5 mm dia. 140 g
ORDER CODES	56910/900	56911/900	56912/900

† specifications involving APC-7 and type N connectors above 18 GHz are not traceable to national standards as these do not exist at present

Power Sensors

6910 Series: Medium Power Thermocouple Power Sensors (continued)

	6913	6914	6914S	6919
FREQUENCY RANGE	10 MHz - 26.5 GHz	10 MHz - 40 GHz	10 MHz - 46 GHz	30 kHz - 3 GHz
POWER RANGE	-30 dBm to +20 dBm (1 μ W to 100 mW)	-30 dBm to +20 dBm (1 μ W to 100 mW)	-30 dBm to +20 dBm (1 μ W to 100 mW)	-30 dBm to +20 dBm (1 μ W to 100 mW)
MAX RF INPUT	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μ s	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μ s	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 μ s	+25 dBm (300 mW) CW +42 dBm (15 W) peak for 2 ms
SENSING ELEMENT	Semiconductor thermocouple	Semiconductor thermocouple	Semiconductor thermocouple	Semiconductor thermocouple
VSWR	1.4 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.1 100 MHz - 2 GHz 1.15 2 GHz - 12.4 GHz 1.2 12.4 GHz - 18 GHz 1.25 18 GHz - 26.5 GHz	1.58 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.1 100 MHz - 2 GHz 1.15 2 GHz - 12.4 GHz 1.21 2.4 GHz - 18 GHz 1.43 18 - 40 GHz (vers. /001) 1.55 26.5 - 40 GHz (vers. /002)	1.58 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.1 100 MHz - 2 GHz 1.15 2 GHz - 12.4 GHz 1.43 12.4 GHz - 33 GHz 3.6 40 GHz - 46 GHz†††	1.4 30 kHz - 100 kHz 1.15 100 kHz - 300 kHz 1.1 300 kHz - 2 GHz 1.2 typical 2 GHz - 3 GHz
LINEARITY FACTOR Accuracy	Provided with sensor \pm 0.5% at 25°C between +10 and +20 dBm. Improves by a factor of 10 for each lower range	Provided with sensor \pm 0.5% at 25°C at 100 mW, decreasing by 0.005% per mW	Provided with sensor \pm 0.5% at 25°C at 100 mW, decreasing by 0.005% per mW	Provided with sensor \pm 0.5% at 25°C between +10 and +20 dBm. Improves by a factor of 10 for each lower range
CALIBRATION FACTOR Accuracy	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%
Resolution	0.01%	0.01%	0.01%	0.01%
RF CONNECTOR	MPC 3.5 mm, male 50 Ω	MPC 2.92 mm, male 50 Ω †	MPC 2.92 mm, male 50 Ω †	Precision N-type, male, 75 Ω
SIZE & WEIGHT	80 mm long, 33.5 mm dia. 140g	88.5 mm long, 33.5 mm dia. 140g	88.5 mm long, 33.5 mm dia. 140g	89 mm long, 33.5 mm dia. 140g
ORDER CODES	56913/900	56914/001 56914/002 includes waveguide 22 coax transition and cal table	56914/003	56919/900
Supplied with	Adapter part no. 23443/822 for connection between 6913 and 0 dBm Power Reference.	Adapter part no. 23443/822 for connection between 6914 and 0 dBm Power Reference.	Adapter part no. 23443/822 for connection between 6914 and 0 dBm Power Reference.	Adapter part no. 23443/842 for connection between 6919 and 0 dBm Power Reference.

†2.92 mm connectors mate non-destructively with 3.5 mm and SMA connectors.

6920 Series: High Sensitivity Diode Sensors

	6920	6923	6924	6924S
FREQUENCY RANGE	10 MHz - 20 GHz	10 MHz - 26.5 GHz	30 kHz - 40 GHz	10 MHz - 46 GHz
POWER RANGE	-70 dBm to -20 dBm† (0.1 nW to 10 μ W)	-70 dBm to -20 dBm†* (0.1 nW to 10 μ W)	-70 dBm to -20 dBm†* (0.1 nW to 10 μ W)	-70 dBm to -20 dBm†* (0.1 nW to 10 μ W)
MAX RF INPUT	+26 dBm (300 mW) CW +30 dBm (1 W) peak for 2 μ s	+26 dBm (300 mW) CW +30 dBm (1 W) peak for 2 μ s	+26 dBm (400 mW) CW +30 dBm (1 W) peak for 2 μ s	+26 dBm (300 mW) CW +30 dBm (1 W) peak for 2 μ s
SENSING ELEMENT	Shottky barrier diode	Shottky barrier diode	Shottky barrier diode	Shottky barrier diode
VSWR	1.4-1.2 10 MHz - 40 MHz 1.2 40 MHz - 10 GHz 1.35 10 GHz - 18 GHz 1.4 typ 18 GHz - 20 GHz††	1.4 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.12 100 MHz - 2 GHz 1.17 2 GHz - 8 GHz 1.3 8 GHz - 18 GHz 1.5 18 GHz - 26.5 GHz	1.58 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.12 100 MHz - 2 GHz 1.33 2 GHz - 18 GHz 1.51 8 GHz - 33 GHz 1.95 26.5 - 40 GHz(vers./001) 1.97 26.5 - 40 GHz(vers./002)	1.4-1.2 10 MHz - 40 MHz 1.15 40 MHz - 100 MHz 1.12 100 MHz - 2 GHz 1.33 2 GHz - 18 GHz 1.5 18 GHz - 33 GHz 1.95 33 GHz - 40 GHz 3.6 40 GHz - 46 GHz†††
LINEARITY FACTOR Accuracy	Provided with sensor \pm 1% at 25°C between -30 and -20 dBm. Improves by a factor of 10 for each lower range	Provided with sensor \pm 1% at 25°C between -30 and -20 dBm. Improves by a factor of 10 for each lower range	Provided with sensor \pm 1% at 25°C between -30 and 20 dBm at 23°C	Provided with sensor \pm 1% at 25°C between -30 and -20 dBm at 23°C
CALIBRATION FACTOR Accuracy	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%	Provided with sensor Uncertainty provided with sensor 0.01%
Resolution	0.01%	0.01%	0.01%	0.01%
RF CONNECTOR	Precision N-type, male 50 Ω	MPC 3.5 mm, male 50 Ω	MPC 2.92 mm, male 50 Ω †	MPC 2.92 mm, male 50 Ω †
SIZE & WEIGHT	104 mm long, 33.5 mm dia. 180 g	87 mm long, 33.5 mm dia. 180 g	88.5 mm long, 33.5 mm dia. 150 g	88.5 mm long, 33.5 mm dia. 150 g
ORDER CODES	56920/900	56923/900	56924/001 56924/002 includes waveguide 22 coax transition and calibration table	56924/003
Supplied with	Precision Attenuator part no. 23448/873. 30 dB \pm 0.05 dB at 50 MHz at 25°C	Precision Attenuator part no. 23448/873 30 dB \pm 0.05 dB at 50 MHz at 25°C Adapter part no. 23443/822 for connection between 6923 and 0 dBm Power Reference.	Precision Attenuator part no. 23448/873. 30 dB \pm 0.05 dB at 50 MHz at 25°C Adapter part no. 23443/822 for connection between 6924 and 0 dBm Power Reference.	Precision Attenuator part no. 23448/873. 30 dB \pm 0.05 dB at 50 MHz at 5°C Adapter part no. 23443/822 for connection between 6924 and 0 dBm Power Reference.

* Lower limit is -65 dBm (0.3 nW) when used with 6970 & -60 dBm when used the Counter Power Meter

† Lower limit is -65dBm (0.3 nW) when used with Counter Power Meter

†† specifications involving type N connectors above 18 GHz are not traceable to national standards as these do not exist at present

††† specifications involving 2.92 mm connectors above 40 GHz are not traceable to national standards as these do not exist at present

6930 Series: High Power Thermocouple Sensors

	6930	6932	6934	6934S
FREQUENCY RANGE	10 MHz - 18 GHz	30 kHz - 4.2 GHz	10 MHz - 40 GHz	10 MHz - 46 GHz
POWER RANGE	-15 dBm to +35 dBm (30 μW to 3 W)	-15 dBm to +35 dBm (30 μW to 3W)	-15 dBm to +30 dBm (30 μW to 1W)	-15 dBm to +30 dBm (30 μW to 1 W)
MAX RF INPUT	+37 dBm (5 W) CW +50 dBm (100 W) peak for 2 μs	+37 dBm (5 W) CW +50 dBm (100 W) peak for 2 μs	+33 dBm (2 W) CW +45 dBm (32 W) peak for 2 μs	+33 dBm (2W) CW +45 dBm (32 W) peak for 2 μs
SENSING ELEMENT	Semiconductor thermocouple	Semiconductor thermocouple	Semiconductor thermocouple	Semiconductor thermocouple
VSWR	1.1 10 MHz - 2 GHz 1.18 2 GHz - 16 GHz 1.28 16 GHz - 18 GHz	1.1 30 kHz - 4.2 GHz	1.12 10 MHz - 100 MHz 1.1 100 MHz - 2 GHz 1.15 2 GHz - 12.4 GHz 1.2 12.4 GHz - 18 GHz 1.25 18 GHz - 26.5 GHz 1.43 26.5 - 40 GHz (vers./001) 1.55 26.5 - 40 GHz (vers./002)	1.12 10 MHz - 100 MHz 1.1 100 MHz - 2 GHz 1.15 2 GHz - 12.4 GHz 1.2 12.4 GHz - 18 GHz 1.25 18 GHz - 26.5 GHz 1.43 26.5 GHz - 40 GHz 2.3 40 GHz - 46 GHz†††
LINEARITY FACTOR	Provided with sensor	Provided with sensor	Provided with sensor	Provided with sensor
Accuracy	-1% to +5% between +25 and +35 dBm. Improves by a factor of 10 for each lower range.	-1% to +5% between +25 and +35 dBm. Improves by a factor of 10 for each lower range.	-1% to +5% between +25 and +30 dBm, less on other ranges.	-1% to +5% between +25 and +30 dBm, less on other ranges.
CALIBRATION FACTOR	Provided with sensor	Provided with sensor	Provided with sensor	Provided with sensor
Accuracy	Uncertainty provided with sensor	Uncertainty provided with sensor	Uncertainty provided with sensor	Uncertainty provided with sensor
Resolution	0.01%	0.01%	0.01%	0.01%
RF CONNECTOR	Precision N-type, male 50 Ω	Precision N-type, male 50 Ω	MPC 2.92 mm, male 50 Ω†	MPC 2.92 mm, male 50 Ω†
SIZE & WEIGHT	93 mm long, 33.5 mm dia. 190g	93 mm long, 33.5 mm dia. 190g	87 mm long, 33.5 mm dia. 150g	87 mm long, 33.5 mm dia. 150g
ORDER CODES	56930/900	56932/900	56934/001 56934/002 includes waveguide 22 coax transition and calibration table.	56934/003
Supplied with			Adapter part no. 23443/822 for connection between 6934 and 0 dBm Power Reference.	Adapter part no. 23443/822 for connection between 6934 and 0 dBm Power Reference.

†2.92 mm connectors mate non-destructively with 3.5 mm and SMA connectors.

††† specifications involving 2.92 mm connectors above 40 GHz are not traceable to national standards as these do not exist at present

	6930 (Option 002) <i>(Comprises standard 6930 plus calibrated precision 10 dB attenuator)</i>	6932 (Option 002) <i>(Comprises standard 6932 plus calibrated precision 10 dB attenuator)</i>
FREQUENCY RANGE	10 MHz - 18 GHz	30 kHz - 4.2 GHz
POWER RANGE	-5 dBm to +44 dBm (0.3 mW to 25W)	-5 dBm to +44 dBm (0.3 mW to 25W)
MAX RF INPUT	+45 dBm (30 W) CW +60 dBm (1 kW) peak for 2 μs	+45 dBm (30 W) CW +60 dBm (1 kW) peak for 2 μs
Sensing element	Semiconductor thermocouple	Semiconductor thermocouple
VSWR	1.2 10 MHz - 8 GHz 1.25 8 GHz - 12.4 GHz 1.35 12.4 GHz - 18 GHz	1.2 30 kHz - 4.2 GHz
LINEARITY FACTOR	Provided with sensor	Provided with sensor
Accuracy	-2% to +6% between +35 and +44 dBm. Improves by a factor of 10 for each lower range	-2% to +6% between +35 and +44 dBm. Improves by a factor of 10 for each lower range
CALIBRATION FACTOR	Provided with sensor	Provided with sensor
Accuracy	Uncertainty provided with sensor	Uncertainty provided with sensor
Resolution	0.01%	0.01%
RF CONNECTOR	Precision N-type, male 50 Ω	Precision N-type, male 50 Ω
SIZE & WEIGHT	228 mm long, 64 mm dia. 533 g	228 mm long, 64 mm dia. 533 g
ORDER CODES	56930/002	56932/002

Ordering numbers

44991/008
44991/009
44991/010
44991/011
44991/012
44991/013
44991/014
44991/015
44991/224
44991/225

Power Sensor Pre-Calibrated Front End Field Replacement Modules

For 6910 Power Sensor
For 6911 Power Sensor
For 6912 Power Sensor
For 6913 Power Sensor
For 6919 Power Sensor
For 6920 Power Sensor
For 6930 Power Sensor
For 6932 Power Sensor
For 6914 Power Sensor
For 6934 Power Sensor

Power Sensors



IFR Americas, Inc., 10200 West York Street, Wichita, Kansas
67215-8999, USA. E-mail: info@ifrsys.com
Tel: +1 316 522 4981 Toll Free USA: 1 800 835 2352 Fax: +1 316 522 1360

IFR Ltd, Longacres House, Norton Green Road, Stevenage, Herts
SG1 2BA, United Kingdom. E-mail: info@ifrinternational.co.uk
Tel: +44 (0) 1438 742200 Freephone UK: 0800 282 388 Fax: +44 (0) 1438 727601

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent Company IFR Systems, Inc. © IFR Ltd. 1999.

