



Meinberg Radio Clocks

Auf der Landwehr 22
31812 Bad Pyrmont, Germany
Phone: +49 (5281) 9309-0
Fax: +49 (5281) 9309-30
<http://www.meinberg.de>
info@meinberg.de

GEN77: DCF77 Code Generator

DCF77 Code Generator GEN77

Key Features

- Leap Second Capability
- Daylight Saving Capability
- Amplitude Modulation and Phase Modulation
- TCXO Reference Frequency

Description

GEN77 generates all signals that are needed to drive or to simulate a DCF77 compatible transmitter: 77.5 kHz reference for the carrier, time marks for the AM, PZF pulses and PZF window for the PM. All output signals are based on one 10MHz reference frequency. This reference frequency is either generated by the on board quartz oscillator (TCXO, optional: OCXO) or applied externally. The beginning of a second can be synchronized with an external signal.

Characteristics

Display	LC-display, 4 x 16 characters
Control elements	Shows time/date and other information of the system. Also several user parameters can be controlled and changed with 4 keys. Parameter Setting: Changeover of daylight saving is generated automatically. Beginning and ending of daylight saving may either be defined by exact dates for a single year or using an algorithm which allows the generator to recompute the effective dates year by year. The date of insertion of a leap second can be edited, too. GEN77 generates the announcement of the leap second as well as the leap second itself. The length of the time marks 0 to 15 can be controlled by 16 TTL inputs.
Interface	Single serial RS232 interface
Data format of interfaces	Baudrate: 300, 600, 1200, 2400, 4800, 9600, 19200 baud Framing: 7N2, 7E1, 7E2, 8E1, 8N1, 8N2
Dimensions of the front panel	21HP/3U (106mm x 128mm), with integrated membrane keyboard
Electrical connectors	64 pin rear VG edge connector DIN 41612
Current consumption	+5V, @300mA +12V, @50mA (only when using OCXO)
Board type	Eurocard
Board dimensions	160mm x 100mm , 1,5mm Epoxy
Power supply	+5V, +12V only when using OCXO)
Power consumption	1,5 W
Ambient temperature	0 ... 50°C / 32 ... 122°F
Humidity	Max. 85%
Options	Also available as ready installed complete system GEN77TGP.
RoHS-Status of the product	This product is fully RoHS compliant
WEEE status of the product	This product is handled as a B2B category product. In order to secure a WEEE compliant waste disposal it has to be returned to the manufacturer. Any transportation expenses for returning this product (at its end of life) have to be incurred by the end user, whereas Meinberg will bear the costs for the waste disposal itself.

Manual

There is no online manual available for this product: [1][Contact us](#)



Links:

[1] <mailto:info@meinberg.de>