

MINOX DC 4211 A DIGITAL CAMERA DESIGNED TO BE STYLISH AND SLIM

The MINOX DC 4211 is another example in the Minox range of small and flat digital cameras: 4.2 million pixels, 3x optical zoom and a large 2" TFT color monitor all packed into an elegant aluminum body make this high featured digital camera a product that combines function and design very well indeed.

The MINOX DC 4211 has a CCD image sensor of 4.2 megapixel and boasts a fast, high-performance, multi coated MINOCTAR lens. The 3x zoom lens has autofocus which allows the user

a higher degree of freedom for creative picture composition. A combination of the individual adjustment to the 4.2 megapixel sensor, the MINOCTAR lens, along with the electronics and software of the MINOX DC 4211, all ensure dynamic images with natural color rendition. The automatic white balance makes sure that exposures are correct, even in poor light, providing the natural colors expected from a camera of this quality. The four flash functions make use of the best available lighting conditions for the best use of flash at all times. A fast

image sequence and minimal shutter release delay allow for spontaneous snapshots just when you need them. Also, voice recordings can be added to each shot. The optional video recording feature of the new DC 4211 opens up a completely new area of photography for the user, making it possible to capture those fleeting moments on video as well.

The large 2.0" TFT color monitor lets you take a look at the image right away, both during and after the shot, and provides an excellent level of viewing, even in sunlight, thanks to the pinsharp definition and overall brilliance of the monitor.

For easy transfer of the image files to the computer, the MINOX DC 4211 comes complete with a digital USB interface. Using the software supplied, pictures can be touched up on the PC and mailed directly friends and family.

The extremely compact size of just $88.5 \times 24 \times 54.5 \text{ mm}$ make this lightweight camera ideal to be carried anywhere for use at any time under any conditions. Complete with a rechargeable Li-lon battery, 32 MB SD Card, pouch case, wrist strap, USB cable, video cable, CD-ROM and user's manual.



MINOX GmbH

Walter-Zapp-Str. 4 D-35578 Wetzlar, Germany Tel.: +49 (0) 6441 / 917-0 Fax: +49 (0) 6441 / 917-612 E-mail: info@minox.com

TECHNICAL DATA

Image Sensor	1/2.5" 4.2 Mega Pixel CCD Sensor
Resolution	2,272 x 1,704 pixels / 1,600 x 1,200 pixels / 1,280 x 960 pixels
	640 x 480 (still) / 320 x 240 (video)
Colour	24-bit RGB
Lens	Autofocus MINOCTAR lens
Aperture	f/2.8 ~ f/4.8
Focusing range	0.35 m to infinity (Macro Tele) / 0.06 m to infinity (Macro Wide Angle)
	0.50 m to infinity (Standard)
Exposure	Auto / Portrait / Landscape
Exposure compensation	-2.0 ~ +2.0 EV (1/3 EV steps)
Focal length	f/5.4 mm ~ 16.2 mm (corresponds to 32 - 96 mm with 35 mm format)
Shutter speed	1/2 ~ 1/1000 sec
Zoom	3x optical; 1x - 3.6x digital (capture mode); 2x and 4x (playback mode)
White Balance	Auto, Manual, Preselection: Daylight, Cloudy, Fluorescent 1 or 2, Incandescent
LCD	2.0" LTPS-TFT colour-LCD
Flash	integrated
Flash program	Auto, Red-Eye-Reduction, Off, Fill-in
ISO-Sensitivity	50/100/200; Auto: ISO 50-200
Voice record	Voice recordings can be added to every photo
Self-Timer	10 sec, 2 sec, 10+2 sec
File format	JPEG (EXIF 2.2), DCF, DPOF, AVI
Image quality	Fine / Standard / Economy
Memory	external memory with SD card up to 512 MB.
Language support	German, Engl., F, I, Sp, Por., Chin. (Traditional), Chin. (Simplified)
Software	MGI Photo Suite III SE, Photo Vista
System requirements	Windows 98/98SE/2000/ME/XP; Mac OS 8.6 or later
Connectors	DC-port, USB-1.1-port, Audio/Video-output (NTSC or PAL)
Power	rechargeable Li-Ion Battery, AC-DC-Adapter (5 V)
Dimensions	88.5 x 24 x 54.5 mm / 3.48 x 0.94 x 2.14 inch
Weight	approx. 125 g / 4,4 oz
Complete with	Rechargeable Li-lon Battery, pouch, wrist cord, USB-cable, video-cable,
	USB-power-supply-adapter, CD-ROM, manual, SD card (32 MB)
Order number	60617