



## PRODUCT INFORMATION

### MINOX DC6011 Slim

#### SLEEK AND VERY TRENDY: THE ULTRA-FLAT DIGITAL CAMERA WITH 6 MEGAPIXELS

With dimensions of just 87x54x18 mm, the MINOX digital DC 6011 slim boasts an ultra sleek and very slender design, making it barely larger than the world famous Minox spy camera of years gone by. Contrary to what its outward appearance may suggest, the performance of the DC 6011 slim is not at all small! With an image resolution of up to six million pixels this MINOX ranks in the top league of ultra-flat and highly compact digital cameras. A 3x optical zoom, large 2.5" TFT colour monitor set in a smooth and elegantly designed stainless steel body, providing a stylish, attractive and modern camera that fits almost any purse or pocket.

Because of its compact dimensions the DC 6011 slim is „pocket friendly“ making it the perfect take anywhere camera. The large 2.5" TFT display is really practical and takes up almost the whole of the camera back. This makes mode selection easy and allows more than

one person to view the results from different angles after shooting the picture.

The core features of the MINOX DC 6011 slim are a 6-megapixel CCD image sensor as well as a proven multi-coated MINOCTAR lens. Working perfectly together and combined with the electronic signal processing of the camera, they guarantee good sharp images with brilliant and natural colour rendition. With its 3x optical zoom the lens is versatile enough to cope with numerous photographic situations. The autofocus feature, which is fast and precise, and the minimal shutter release delay both allow spontaneous snapshots and a fast image sequence. The high resolution of the sensor enables top quality printouts such as small posters as well as highly enlarged detail of the image. Included with the camera is a docking station for the convenient transfer of image files. This can simultaneously be used as a charging sta-

tion. The automatic white balance guarantees optimum exposure even under changing light conditions so that the user can rely on getting images with natural colour rendition every time. Four different flash functions and the possibility to adjust the ISO sensitivity of the sensor in three stages also allow optimum adjustment of the shot in any light. With the DC 6011 slim the user can additionally make video clips and voice recordings to accompany the images taken, therefore the camera can be used as a video camera or voice recorder. For the recording and playback function this MINOX camera has an integrated microphone and a built-in loudspeaker. Image data is stored inside the camera on a SD card with a capacity of up to one gigabyte. The power supply is provided by a lithium ion battery.

Featuring a PictBridge interface the DC 6011 slim can be directly connected at home or when traveling to the appropriate peripheral equipment to print out photos without using a computer, if needed. The MINOX DC 6011 slim has a digital USB 2.0 interface for fast and uncomplicated transfer of image files to a computer.

Included with the MINOX DC 6011 slim is a power supply unit, docking station, USB and video cable, a lithium ion battery, a 32 MB SD card, wrist strap, ever-ready case as well as an Operator's Manual and CD-ROM with software and drivers.



#### Technical Data

|                       |   |
|-----------------------|---|
| Image sensor          | 6 mega pixels 1/2.5 inch CCD  |
| Colour                | 24-bit Colour (RGB)   |
| Image resolution      | Still: 2.816 x 2.112, 2.272 x 1.704, 1.600 x 1.200, 640 x 480<br>Movie: 640 x 480             |
| Lens                  | Autofocus MINOCTAR Lens   |
| Focal length          | f = 5,4 - 16,2 mm (corresponds to 32 - 96 mm with 35 mm format)                               |
| Aperture              | f = 2,8 (Wide) ~ 4,8 (Tele)   |
| Focus Range           | Macro: 5 cm ~ ∞ (Wide) / 30 cm ~ ∞ (Tele) / Normal: 0,05 m ~ ∞ (Standard)                     |
| Zoom                  | 3x optical / 4x digital   |
| Shutter speed         | 1/2 ∞ 1/1000 s  |
| Exposure              | Auto / Manual: 1/3 EV step, -2.0 ~ +2.0 EV  |
| White balance         | Auto, Pre-Set (5 Modes), Manual   |
| LCD Display           | 2.5" Colour LTPS-TFT LCD  |
| Memory                | External: SD-Card 32 MB up to 1 GB  |
| Flash                 | Build-In: Auto, Forced, Off, Red-Eye Reduction  |
| Self-timer            | 10 sec, 2 sec, 10+2 sec delay   |
| File Format           | Still: DCF, JPEG (EXIF 2.2), DPOF; Movie: DCF (AVI-Motion-JPEG)                               |
| Operating environment | PC: Windows 98/98SE/2000/ME/XP / Mac: OS 9.0 or later   |
| Software              | Photo Explorer 8.0, Photo Express 5.0   |
| Language support      | English, German, French, Spanish, Italian, Chinese (trad. and simpl.)                         |
| Connectors            | Cradle terminal   |
| Power                 | Lithium-ion rechargeable battery (via cradle)   |
| Dimensions / Weight   | 3.42 x 2.13 x 0.71 inch / 87 x 54 x 18 mm (WxHxD) / approx. 4.04 oz / 125 g (without battery) |
| Order number          | 60630   |

**MINOX GmbH**  
 Walter-Zapp-Str. 4  
 D-35578 Wetzlar, Germany  
 Tel.: +49 (0) 6441 / 917-0  
 Fax: +49 (0) 6441 / 917-612  
 E-mail: [info@minox.com](mailto:info@minox.com)  
[www.minox.com](http://www.minox.com)