

Model 627A Stereo A/V Switch Instruction Sheet



Installation

- Connect your main audio/video common outputs to your equipment's' in-puts.
- Connect the power supply wires, White to +12 V and Black to Ground, to the terminal block connections marked.
- A TTL level control signal or a dry contact across ground and relay set will change the output from the primary to the secondary.

*Relay connection: Connect the normally open (NO) contact to Ctrl. Connect the relay common (COM) contact to Gnd.

Open Collector:

Connect your transistor's Collector to **Ctrl** and the transistor's emitter to **Gnd**

Operation

The 627A's primary inputs are normally connected to the common outputs. It remains in this state until the **Ctrl** input is connected to **Gnd**. This will connect the secondary input to common for the duration of the connection.

Specifications

Video

75 Ω ; 'F' connectors

Audio

Balanced stereo; screw terminals

Video Isolation @ 950 MHz > 52 dBmV

Video-IF/RF Return Loss > 22 dBmV

Control Input

10 mA maximum to gnd.

Power Requirement

100-240 VAC $\pm 2\%,50/60$ Hz. Power pack output; +12 VDC

Physical

5.25"H x 2.75"W x 2"D

Design and specifications are subject to change without notice.

WARRANTY

Monroe Electronics, Inc. warrants to the owners, each instrument and sub-assembly manufactured by them to be free from defects in material and workmanship for a period of one year after shipment from factory. This warranty is applicable to the original purchaser only.

Liability under this warranty is limited to service, adjustment or replacement of defective parts (other than fuses or batteries) on any instrument or sub-assembly returned to the factory for this purpose, transportation charges prepaid.

This warranty does not apply to instruments or sub-assemblies subjected to abuse, abnormal operating conditions, or unauthorized repair or modification.

Since Monroe Electronics, Inc. has no control over conditions of use, no warranty is made, or implied as to the suitability of our product for the customer's intended use.

THE WARRANTY SET FORTH IN THIS ARTICLE IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS, IMPLIED OR STATUTORY INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. Except for obligations expressly undertaken by Monroe Electronics, in this warranty, Owner hereby waives and releases all rights, claims and remedies with respect to any and all warranties, express, implied or statutory (including without limitation, the implied warranties of merchantability and fitness), and including but without being limited to any obligation of Monroe Electronics with respect to incidental or consequential damages, or damages for loss of use. No agreement or understanding varying or extending the warranty will be binding upon Monroe Electronics unless in writing signed by a duly authorized representative of Monroe Electronics.

In the event of a breach of the foregoing warranty, the liability of Monroe Electronics shall be limited to repairing or replacing the non-conforming goods and/or defective work, and in accordance with the foregoing, Monroe Electronics shall not be liable for any other damages, either direct or consequential.

RETURN POLICY TO FACTORY:

Materials returned to Monroe must have a Return Material Authorization number. To obtain a RMA number, contact our A/V Switching & Control Customer Service at 585-765-2254 or fax 585-765-9330. Customers have 30 days to determine that the product ordered fills their need and performs as described in Monroe's literature. Units returned for approved repair or credit, must be in the original packaging including all parts and paperwork plus be in very good physical condition. If not, the customer is billed the cost to refurbish the unit and for missing accessories and merchandise. No products may be returned for exchange or credit after 12 months of the shipment date. Monroe reserves the right to repair or replace units under warranty.