



DC-18 GHz

COAXIAL ADAPTERS

7 mm

- Low Residual VSWR
- Precision 7 mm Connector
- Precision Narda SMA, Type N and TNC Stainless Steel Connectors

SPECIFICATIONS

7 mm to Type N Precision Adapters

FREQUENCY RANGE (GHz)	MODEL	VSWR (Max)	WEIGHT (Max)		CONNECTORS
			Oz	Gr	
DC-18	5066	1.013+.004f*	3	85	7mm to Type N male
	5067	1.013+.004f*	2	57	7mm to Type N female

7 mm to Type SMA Stainless Steel Adapters

FREQUENCY RANGE (GHz)	MODEL	VSWR (Max)		WEIGHT (Max)		CONNECTORS
		DC-12.4	12.4-18	Oz	Gr	
DC-18	5068	1.06	1.15	1.5	43	7mm to SMA male
	5069	1.06	1.15	1.5	43	7mm to SMA female

7 mm to Type TNC Stainless Steel Adapters






FREQUENCY RANGE (GHz)	MODEL	VSWR (Max)		WEIGHT (Max)		CONNECTORS
		DC-12.4	12.4-18	Oz	Gr	
DC-18	5065	1.08	1.12	2	57	7mm to TNC female

*f denotes frequency in GHz

VSWR determined by measurement of matched pair.

Adapters

OUTLINE DRAWINGS



All dimensions are Max. unless otherwise specified.