

COOLPIX 3500

Swivel. Style. Performance.

- Unique inner-swivel lens design enables easy, versatile shooting capability from different angles.
- Stylish, compact, lightweight design
- 12 versatile [SCENE] Modes
- Exclusive 256-segment Matrix Metering
- 5-Area Multi Autofocus for easier photo composition
- Small Picture function creates smaller size image data for easy e-mailing
- Movie mode at approx. 15 frames per second (fps) for up to 35 seconds
- Quick instant startup and autofocus
- Macro shooting as close as 4cm (1.6 in.)
- Bright, clear 1.5-in., 110,000-dot, low-temperature polysilicon TFT LCD monitor
- [TRANSFER] button for one-touch upload of image data to a computer



Type:	Digital camera E3500
Effective pixels:	3.2 million
CCD:	1/2.7-in. type (3.34 million)
Image size:	Selectable from: 2,048 (2,048 x 1,536 pixels), 1,600 (1,600 x 1,200 pixels), 1,280 (1,280 x 960 pixels), 1,024 (1,024 x 768 pixels), 640 (640 x 480 pixels)
Image quality (approx.):	FINE: 1/4, NORMAL: 1/8, BASIC: 1/16
Lens:	3x Zoom-Nikkor; 5.6-16.8mm [35mm (135) format equivalent to 37-111mm]; Digital zoom: up to 4.0x
LCD monitor:	1.5-in.; 110,000-dot low-temp. polysilicon TFT LCD with brightness adjustment
Storage media:	CompactFlash™ (CF) card Type I
Shooting modes:	AUTO, SCENE (Portrait, Party/Indoor, Night Portrait, Beach/Snow, Landscape, Sunset, Night Landscape, Museum, Fireworks Show, Close Up, Copy and Back Light), Manual (includes shooting menu for control of White Balance, Capture Mode, Best-Shot Selector, Exposure Compensation, Noise Reduction, and Image Sharpening), Movie (up to 35 seconds of QVGA frames at 15 fps.)
Capture modes:	Single, Continuous, Multi-shot 16 (16 frames 1/16 in size)
Number of frames with 16MB CF card:	FINE: approx. 10, NORMAL: approx. 19, BASIC: approx. 37
Built-in Speedlight:	Shooting range: approx. 0.4-3.0m/1.3-9.8 ft. (W), approx. 0.4-1.7m/1.3-5.6 ft. (T); Sensor flash system; Flash modes: Auto, Flash Cancel (off), Red-Eye Reduction, Anytime Flash (fill-flash)
Interface:	USB
Power requirements:	One Rechargeable Li-ion Battery EN-EL2 (supplied), AC Adapter Kit EH-60 (optional)
Dimensions (WxHxD):	Approx. 114 x 59.5 x 31.5mm (4.5 x 2.3 x 1.2 in.)
Weight:	Approx. 175g (6.2 oz.) (Without battery and CF card)
Supplied accessories:	Strap, 16MB CF card, USB cable, Rechargeable Li-ion Battery EN-EL2, Battery Charger MH-60, Nikon View CD-ROM
Optional accessories:	Rechargeable Li-ion Battery EN-EL2, AC Adapter Kit EH-60, Various size CF cards, LCD Hood HL-E2500, Case CS-E2500

Nikon View System Requirements

Macintosh

OS	Mac® OS 9.0-9.2 (only built-in USB ports supported), Mac® OS X (10.1.3 or later)
Models	iMac™, iMac™ DV, Power Macintosh® G3 (Blue & White), Power Mac™ G4 or later; iBook™, PowerBook® G3 or later (only built-in USB ports supported)
RAM	64MB or more recommended
Hard disk	60MB required for installation, with additional amount equivalent to twice the capacity of the camera memory card plus 10MB required when Nikon View is running
Display	800 x 600 with 16-bit color (full color recommended)
Others	CD-ROM drive required for installation

Windows

OS/Models	Windows® 98SE, Windows® Me, Windows® 2000 Professional, Windows® XP Home Edition, Windows® XP Professional pre-installed model
Models	Only models with built-in USB ports supported
CPU	Pentium® 300MHz or higher
RAM	64MB or more recommended
Hard disk	60MB required for installation, with additional amount equivalent to twice the capacity of the camera memory card plus 10MB required when Nikon View is running
Display	800 x 600 with 16-bit color (full color recommended)
Others	CD-ROM drive required for installation

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. CompactFlash™ is a trademark of SanDisk Corporation. Products and brand names are trademarks or registered trademarks of their respective companies.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer.

©2002/3 NIKON CORPORATION



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku,
Tokyo 100-8331, Japan

www.nikon-image.com/eng/

September 2003