

# EF400SV / EF400SV QUARTZ DATE

- Large viewfinder
- Focus free
- Built-in flash with Flash Cancel and Anytime Flash
  - Red-Eye Reduction
  - Compact and lightweight
- Automatic film operation with mid-roll rewind
- EF400SV QUARTZ DATE offers data imprinting

Picture-taking  
so easy,  
anyone can use it!



- Type:** 35mm lens-shutter camera with built-in flash
- Film format:** 24 × 36mm [standard 35mm (135) format]
- Lens:** 28mm f/5.6 (3 elements in 3 groups)
- Focusing:** Fixed focus
- Shooting distance:** 1.2m or 3.9 ft. to infinity (∞)
- Shutter:** Mechanical lens shutter, fixed shutter speed of 1/100 sec.
- Viewfinder:** Reverse-Galilean Albada-type bright-frame viewfinder; magnification: 0.63x; field coverage approx. 85%
- Frame counter:** Additive type, automatically resets to "S" when the camera back is opened
- Film speed:** Auto setting to ISO 100 or 400 with DX-coded film (ISO 100 with DX-coded ISO 200 film and non-DX-coded film)
- Film operation:** Film automatically advances to first frame when camera back is closed; automatic film advance and rewind; mid-roll rewind is possible
- Built-in flash:** Built-in auto flash with recycling time of approx. 6 sec.; flash cancel and anytime flash by pressing dedicated buttons on the front of camera; Red-Eye Reduction provided
- Flash shooting distance range:** 1.2-2.7m or 3.9-8.9 ft. at ISO 100, 1.2-3.8m or 3.9-12.5 ft. at ISO 200, and 1.2-5.4m or 3.9-17.7 ft. at ISO 400
- Auto power off:** With the power switch on, camera power automatically turns off 20 sec. after the flash-ready LED comes on. To turn the power on again, lightly press the shutter release button or turn the power switch on
- Battery life:** Approx. 30 rolls of 24-exposure film (20 rolls of 36-exposure film), using the flash for half of all exposures
- Power source:** Two 1.5V LR6 (AA-size alkaline) batteries
- Self-timer:** 10 sec. duration; one-shot operation; cancellable; tripod socket provided  
(EF400SV QUARTZ DATE only)
- Data imprint function:** Imprint uses 7-dot LED; five choices include: 1) Year/Month/Day, 2) Month/Day/Year, 3) Day/Month/Year, 4) Day/Hour/Minute or 5) No imprint; 24-hour cycle with no AM/PM; built-in clock with timing accuracy within ±90 sec. a month; power source: one 3V lithium battery (CR2025 type)  
(EF400SV QUARTZ DATE only)
- Dimensions (W × H × D):** Approx. 110 × 67 × 37mm or 4.3 × 2.6 × 1.5 in. (EF400SV); approx. 110 × 67 × 42mm or 4.3 × 2.6 × 1.7 in. (EF400SV QUARTZ DATE)
- Weight (without batteries):** Approx. 145g or 5.1 oz. (EF400SV); approx. 150g or 5.3 oz. (EF400SV QUARTZ DATE)

Specifications apply when fresh batteries are used at normal temperature (20°C / 68°F).  
Specifications and design are subject to change without any notice or obligation on the part of  
the manufacturer.

© 2000 NIKON CORPORATION



NIKON CORPORATION

FUJI BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN

www.nikon-image.com/eng/

January 2001