

# Lite•Touch Zoom70W/ Lite•Touch Zoom70W QD

- Wideangle 28mm coverage
- 28-70mm power zoom lens
- Built-in flash with Flash Cancel, Anytime Flash and Slow Sync
  - Red-Eye Reduction selectable in any flash mode
  - Macro capability as close as 60cm at any zoom setting
  - Infinity focus for landscape shots
  - Sliding lens cover
- Lite-Touch Zoom70W QD allows date and time imprinting



Turn a few heads with this  
eye-catching wideangle zoom.



**Type of camera:** 35mm autofocus lens-shutter camera with Nikon zoom lens

**Film format:** DX-coded 35mm film

**Picture format:** 24 × 36mm

**Lens:** 28mm f/5.6–70mm f/10, 5 elements in 4 groups

**Shutter:** Programmed electronic type

**Shutter speed:** 1 to 1/220 sec.

**Viewfinder:** Real-image viewfinder; Frame coverage: over 80%; Magnification: approx. 0.28x at 28mm, approx. 0.62x at 70mm; Dioptre: approx. -0.8m<sup>-1</sup>

**Viewfinder information:** Image size frame (with parallax compensation marks); Autofocus frame

**Red LED indications:** Ready to shoot (Lights up); Flash being charged (Blinks); Flash does not fire. In focus (Momentarily lights up); Warning when pop-up flash unit is accidentally pressed down (Blinks at 8 Hz)

**Focusing:** Activated by lightly pressing the Shutter Release button. Distance range from approx. 0.9m or 3 ft. to infinity at 28mm, approx. 1.2m or 3.9 ft. to infinity at 70mm; Macro mode 0.6 to 1.0m or 2 to 3.3 ft.; Infinity Focus mode available

**Focus lock:** Focus is locked as long as the Shutter Release button remains lightly pressed

**Exposure control:** Electronically controlled program AE; Auto exposure range (ISO100): EV5 to 15 at 28mm, EV6 to 15 at 70mm; Flash fires automatically if the available light is low

**Film speed setting:** Valid for DX-coded ISO100, 200, and 400 films (ISO100 is automatically selected for DX-coded ISO200 films)

**Film loading:** Film automatically advances to the first frame upon completion of film loading; Film cartridge confirmation window

**Film advance:** Film automatically advances after each shot; Auto rewind at end of roll; Mid-roll rewind function available

**Frame counter:** Shown in the LCD panel; Additive type; Counts back during film rewind

**Self-timer:** Electronically controlled; Activated by depressing the Shutter Release button; Self-timer lamp blinks and lights up (10 seconds in total) to show when ready; Timer duration 10 seconds; Cancelable

**Built-in flash:** Four flash modes available: Auto Flash, Flash Cancel, Anytime Flash, and Slow Sync Flash; Flash automatically fires when there is not enough light; Shutter button locked while flash is charging, Flash shooting range (ISO100): approx. 0.9 to 3.3m or 3 to 10.8 ft. at 28mm, approx. 1.2 to 1.9m or 3.9 to 6.2 ft. at 70mm, (ISO400): approx. 0.9 to 6.6m or 3 to 21.7 ft. at 28mm, approx. 1.2 to 3.8m or 3.9 to 12.5 ft. at 70mm; Recycling time approx. 6 sec.

**Red-Eye Reduction mode:** Red-Eye Reduction lamp is lit for approx. 1 second while flash fires

**Battery life:** Approx. 10 rolls of 24-exposure film when flash is used for half the exposures

**LCD panel (power is on):** Frame counter, flash mode, Red-Eye Reduction, Self-timer, Infinity Focus mode, low battery power

**Power source:** One 3V lithium battery (CR2)

**Date imprint function:** Lite-Touch Zoom70W QD only 24-hour cycle with no AM/PM; Five time formats selectable by a pushbutton; Year/Month/Day, Day/Hour/Minute, no printing, Month/Day/Year, Day/Month/Year; Leap year adjustment until 2049; Incremental correction of date; Power source: one CR2025 lithium battery

**Dimensions (W × H × D):** Lite-Touch Zoom70W: 117 × 63 × 42mm or 4.6 × 2.5 × 1.7 in.  
Lite-Touch Zoom70W QD: 117 × 63 × 47mm or 4.6 × 2.5 × 1.9 in.

**Weight (without battery):** Lite-Touch Zoom70W: Approx. 200g or 7.0 oz.  
Lite-Touch Zoom70W QD: Approx. 210g or 7.4 oz.

Specifications apply when fresh batteries are used at normal temperature (20°C / 68°F).  
Specifications and design are subject to change without any notice or obligation on the part of the manufacturer.  
© 2000 NIKON CORPORATION



NIKON CORPORATION

FUJI BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN

www.nikon-image.com/eng/