

# Nuvis S

The clever compact camera,  
with metal jacket chic.

- Shell-type stainless steel design conceals most camera features when closed
  - Whisper-quiet zooming operation
  - High-performance 3× zoom with small f-number of f/5.2-7.5
  - Sophisticated autofocus performance
- Close-Range Correction (CRC) system to minimize picture deterioration
  - Slow Sync and Red-Eye Reduction capability
  - Built-in diopter adjustment
  - Remote control option
- Advanced Photo System benefits including: Mid-Roll film Change (MRC), title imprinting, easy film handling, three selectable print types (C, H, P), Picture Quality Improvement (PQI) and Index Prints



- Type of camera:** IX240 (Advanced Photo System™) type autofocus AE lens-shutter camera with Nikon Zoom 22.5-66mm f/5.2-f/7.5 lens
- Usable film:** IX240 system (Advanced Photo System™) film cartridge (16.7 × 30.2mm)
- Print aspect ratio:** C, H and P types available
- Lens:** 22.5mm f/5.2 - 66mm f/7.5 (28mm-82.5mm converted to 35mm type); 6 elements in 6 groups
- Shutter speed:** Approx. 1 - 1/400 sec. (22.5mm), 2 - 1/400 sec. (66mm)
- Viewfinder:** Real-image zoom viewfinder; Frame coverage approx. 85% for H-type printed image area; diopter adjustment (-1.5 to +1.5 m<sup>-1</sup>); 0.34x magnification at 22.5mm, 0.85x at 66mm
- Viewfinder information:** C/H/P-type image size frame marks (C-type and H-type with parallax compensation marks); Autofocus frame; Orange LED (flash ready-light) — Lights up: flash ready; Blinks: flash being charged; Green LED (in-focus indicator) — Lights up: subject focused; Blinks slowly (at 2Hz): subject is too close to achieve correct focus; Blinks quickly (at 8Hz): subject is difficult to focus
- Focusing:** Wide-area passive-type autofocus system; Activated by lightly pressing shutter release button; Distance range from 0.45m or 1.5 ft. to infinity
- Focus lock:** Focus is locked as long as shutter release button is lightly pressed
- Exposure control:** Electronically controlled program AE; Auto exposure range (ISO 200): EV 6-17 at 22.5mm, EV 6-18 at 66mm; Flash fires automatically if the available light is low
- Film speed setting:** ISO 50, 100, 200, 400, 800 and 1600 film automatically set
- Film operation:** Drop-in loading system; Wrong film loading prevention mechanism
- Frame counter:** Shown in the LCD panel; Count-down type
- Self-timer:** Electronically controlled; Activated by depressing shutter release button; 10 sec. duration, blinking/lighting up in two steps
- Film operation:** Film is automatically wound to the first frame after inserting cartridge; Film automatically advances by one frame after each shot; Auto rewind at the end of film roll; Mid-roll rewind function available
- Remote control (optional):** Infrared wireless remote control; 2 sec. delay shutter release; Automatically canceled after 2 min. if not used; Effective range is within approx. 5m or 16 ft. straight in front of the camera; Battery will last for approx. 10 years; Dimensions (W × H × D): approx. 60 × 27 × 10mm or 2.4 × 1.1 × 0.4 in.; Weight (including battery): 13g or 0.5 oz.
- Built-in flash:** Four flash modes available: Auto flash, Flash cancel, Anytime flash, and Slow sync; Flash automatically fires when available light is low or subject is backlit; Flash shooting range: approx. 0.45-3.7m or 1.5-12.1 ft. at 22.5mm, approx. 0.45-2.6m or 1.5-8.5 ft. at 66mm (ISO 200); Shutter release button is locked during flash charging; Recycling time approx. 6 sec.
- Red-Eye Reduction mode:** Red-Eye Reduction lamp lights up for approx. 1 sec. before flash fires
- Battery life:** Approx. 10 rolls of 25 exposure film when flash is used for half of exposures
- LCD panel (power is on):** Frame counter, Flash mode, Red-Eye Reduction, Remote control/Self-timer, Cartridge, Low battery power, Data recording, Title and number of desired prints
- Power source:** One 3V lithium battery CR2
- Data recording function:** Magnetic recording system; Date/Title/No. of desired prints; Date displaying in the LCD panel with five choices: Year/Month/Day, Hour/Minute, Month/Day/Year, Day/Month/Year or No recording; 24-hour cycle with no AM/PM; Leap year adjustment until 2030; Built-in clock with timing accuracy within ±90 sec. a month; Power source is the same as the camera body; Number of desired prints (1 to 9) can be specified; Title recording function; selectable from 30 titles in 12 languages which can be printed on the back of pictures
- Dimensions (W × H × D):** Approx. 93 × 65 × 32mm or 3.7 × 2.6 × 1.3 in. (with slide cover closed)/approx. 130.5 × 65 × 32mm or 5.1 × 2.5 × 1.3 in. (with slide cover open)
- Weight (without battery):** Approx. 230g or 8.1 oz.

All specifications apply when fresh CR2-type batteries are used at normal temperature (20°C / 68°F). Specifications and designs are subject to change without any notice or obligation on the part of the manufacturer. © 2000 Nikon Corporation



NIKON CORPORATION

FUJI BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN

[www.nikon-image.com/eng/](http://www.nikon-image.com/eng/)

January 2001