

Nuvis S 2000

Good things come in small packages.

- World's lightest* shell-type 2x zoom camera
 - Practical, stylish shell-type design
 - Wide-area passive-type autofocus system
- Four versatile flash modes including Slow Sync and Red-Eye Reduction
 - Macro shooting as close as 40cm
 - Self-timer and optional remote control
 - Whisper-quiet zoom operation
- Advanced Photo System features including easy film handling, choice of three print types (C, H, P), Title Imprint, Index Prints and more

* As of June 25, 2000.



- Type of camera:** IX240 (Advanced Photo System™) type autofocus AE lens-shutter camera with Nikon Zoom 24-48mm f/4.5-8.2 lens
- Usable film:** IX240 System (Advanced Photo System™) film cartridge (16.7 × 30.2mm)
- Print aspect ratio:** C, H and P-type available
- Lens:** 24mm f/4.5-48mm f/8.2 (30mm-60mm converted to 35mm type); five elements in five groups
- Shutter:** Programmed electronic shutter; also serves as diaphragm blades
- Shutter speed:** 2.5 to 1/500 sec.
- Viewfinder:** Real-image zoom viewfinder; frame coverage approx. 85% for H-type printed image area; approx. 0.32x magnification at 24mm, approx. 0.56x at 48mm
- Viewfinder information:** C/H/P-type image size marks (C-type and H-type with parallax compensation marks); Autofocus frame, Orange LED—Lights up: flash ready; blinks (at 4 Hz): flash is recycling; blinks quickly (at 8 Hz): flash pops up improperly, Green LED—Lights up: focus operation complete; blinks slowly (at 2 Hz): subject is too close to achieve correct focus; blinks quickly (at 8 Hz): subject is difficult to focus, Orange LED—Blinks (at 4 Hz): film is rewinding
- Focusing:** Wide-area passive autofocus; Activated by lightly pressing shutter release button; Distance range from 0.4m or 1.3 ft. to infinity; With AF Assist Illuminator LED (also serves as Red-Eye Reduction lamp)
- Focus lock:** Focus is locked as long as shutter button is lightly pressed
- Exposure control:** Electronically controlled program AE; Auto exposure range (ISO 200): EV 6-17 at 24mm, EV 6-18 at 48mm; Flash fires automatically if available light is low
- Film speed setting:** ISO 50, 100, 200, 400 and 800 film automatically set
- Film operation:** Drop-in loading system; Wrong film loading prevention mechanism; Cartridge chamber cover lock mechanism
- Frame counter:** Shown in the LCD panel; countdown type
- Self-timer:** Electronically controlled; Activated by depressing shutter release button; 10 sec. duration, blinking/lighting up in two steps
- Film advance:** Film is automatically thrust to first frame after inserting cartridge; Film automatically advances by one frame after each shot; Auto rewind at end of film roll; Mid-roll rewind function available
- Remote control (optional):** Infrared wireless remote control; 2 sec. delay shutter release; Automatically canceled after 2 min. if not used; Effective range is within approx. 5m or 16.4 ft. straight in front of camera; Battery will last for approx. 10 years; Dimensions (W × H × D): approx. 60 × 27 × 10mm or 2.4 × 1.1 × 0.4 in.; Weight (including battery): approx. 13g or 0.5 oz.
- Built-in flash:** Four flash modes available: Auto Flash, Flash Cancel, Anytime Flash, and Slow Sync; Flash automatically fires when available light is low or subject is backlit; Flash shooting range: approx. 0.4-5m or 1.3-16.4 ft. at 24mm, approx. 0.4-2.8m or 1.3-9.2 ft. at 48mm (ISO 200); Shutter release button is locked during flash charging; Recycling time approx. 6 sec.
- Red-Eye Reduction mode:** Red-Eye Reduction lamp lights up for approx. 1 sec. before flash fires
- Battery life:** Approx. 10 rolls of 25-exposure film when flash is used for half of exposures
- LCD panel (power is on):** Frame counter, Flash mode, Red-Eye Reduction, Self-timer/Remote control, Cartridge, Low battery power, Title/Date/Time, Data recording
- Power source:** One 3V lithium battery CR2
- Data recording function:** Magnetic recording system; Date/title setting; Date displayed on LCD panel with five choices: Year/Month/Day, Month/Day/Year, Day/Month/Year, Hour/Minute, or No recording; 24-hour cycle with no AM/PM; auto leap year adjustment until 2039; Built-in clock with timing accuracy within ±90 sec. a month; Power source is same as camera body; Title recording function: selectable from 30 titles in 12 languages which can be printed on back of pictures
- Dimensions (W × H × D):** Approx. 89 × 60.5 × 29mm or 3.5 × 2.4 × 1.1 in. (with slide cover closed)/approx. 122.5 × 60.5 × 29mm or 4.8 × 2.4 × 1.1 in. (with slide cover opened)
- Weight (without battery):** Approx. 140g or 4.9 oz.

All specifications apply when fresh CR2-type batteries are used at normal temperature (20°C / 68°F). Specifications and designs are subject to change without any notice or obligation on the part of the manufacturer.
© 2000 Nikon Corporation



NIKON CORPORATION

FUJII BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN

www.nikon-image.com/eng/

January 2001