

One•Touch Zoom90/ One•Touch Zoom90 QD

- Wide zoom range from wideangle to telephoto
 - 38-90mm power zoom lens
- Built-in flash with Flash Cancel, Anytime Flash and Slow Sync
 - Red-Eye Reduction selectable in any flash mode
 - Macro capability as close as 30cm at any zoom setting
 - Infinity focus for landscape shots
 - Protective lens cover
- One-Touch Zoom90 QD allows date and time imprinting



Get up close and personal with this
powerful zoom compact.



Type of camera: 35mm autofocus lens-shutter camera with Nikon zoom lens

Film type: DX-coded 35mm film

Picture format: 24 × 36mm

Lens: 38mm f/4.8–90mm f/10.5, 6 elements in 6 groups (Nikon zoom lenses)

Shutter: Programmed electronic type; also serves as diaphragm blades

Shutter speed: 2.6 to 1/250 sec.

Viewfinder: Real-image viewfinder; frame coverage: approx. 80%; magnification: approx. 0.34x at 38mm, approx. 0.69x at 90mm; Diopter: approx. -0.7m⁻¹

Viewfinder information: Image size frame marks (with parallax compensation marks); Autofocus frame

Green LED indicators: Light up: Ready to shoot; Blinks: Flash being charged

Focusing: Activated by lightly pressing Shutter Release button. Distance range approx. 0.7m or 2.3ft. to infinity; The shutter locks when the subject is closer than 0.7m or 2.3 ft.; Macro mode 0.3 to 0.7m or 1 to 2.3 ft.; In Macro mode Macro button blinks; Infinity Focus mode available: Focus lock functions by lightly pressing the Shutter Release button

Exposure control: Electronically controlled program AE: auto exposure range (ISO100): EV6–16 at 38mm, EV6–18 at 90mm; Flash fires automatically if available light is low; Daylight Sync can be activated

Film speed setting: ISO100, 200, 400 and 800 film set automatically ISO100 is automatically selected for non-DX-coded films

Film loading: Film automatically advances to the first frame upon completion of film loading; Film cartridge confirmation window

Film advance: Film automatically advances by one frame after each shot; Auto rewind at the end of film roll; Mid-roll rewind function available

Lens cover: Built-in barrier type

Frame counter: Shown in the LCD panel; Additive type; Counts back during film rewind

Self-timer: Electronically controlled; Activated by depressing the Shutter Release button; Self-timer lamp blinks and lights up to show when ready; Timer duration 10 seconds; Cancelable

Built-in flash: Four flash modes available: Auto Flash, Flash Cancel, Anytime Flash, Slow Sync Flash; Flash automatically fires when there is not enough light; Shutter button locked while flash is charging
Flash shooting range: ISO100: approx. 0.7 to 3.5m or 2.3 to 11.5 ft. at 38mm, approx. 0.7 to 1.6m or 2.3 to 5.2 ft. at 90mm. ISO400: approx. 0.7 to 7.0m or 2.3 to 23 ft. at 38mm, approx. 0.7 to 3.2m or 2.3 to 10.5 ft. at 90mm; Flash recycle time approx. 7 sec.

Red-Eye Reduction mode: Red-Eye Reduction lamp lit for approx. 1 second while flash fires

LCD panel: Displays frame counter, flash mode, Red-Eye Reduction, Self-timer, Infinity Focus mode, low battery power

Battery life: Approx. 15 rolls of 24-exposure film when flash is used for half the exposures

Power source: One 3V lithium battery (CR2)

Date imprint function: Auto film speed setting with DX codes (ISO 100–800); Printed date includes year, month, day, hour, (One-Touch Zoom90 QD only) (24-hour cycle with no AM/PM) and minute; Leap year adjustment until 2049; Incremental correction of date; Power source: one CR2025 lithium battery

Dimensions: Approx. 117 × 64.4 × 50.4mm
(W × H × D) or 4.6 × 2.5 × 2.0 in.
Approx. 117 × 64.4 × 53.8mm
or 4.6 × 2.5 × 2.1 in. (QD model)

Weight: Approx. 215g or 7.6 oz.
(without battery) Approx. 225g or 7.9 oz. (QD model)

Specifications apply when fresh batteries are used at normal temperature (20°C / 68°F).
Specifications and design are subject to change without any notice or obligation on the part of the manufacturer.
© 2000 NIKON CORPORATION



NIKON CORPORATION

FUJI BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN

www.nikon-image.com/eng/

January 2001