

**Nokia Customer Care  
2118 (RH-77)  
Mobile Terminal**

# **General Information**

<b>Contents</b>	<b>Page</b>
Overview.....	3
Technical Specifications .....	4
Supported Accessories .....	4

## Overview

The 2118 is an 800 MHz CDMA DCT4 mobile terminal that supports CDMA IS-95 and IS-2000. Features include the following:

- Black and white display (96 x 65)
- 8 MB Flash memory and 1 MB RAM in the UPP
- Internal antenna
- Internal vibra
- Hands-free speakerphone
- Voice recognition
- Flashlight
- Picture frame and changeable covers
- 16 MIDI polyphonic ring tones



Figure 1: Front and side views

Dimensions	Value and Unit
Dimensions:	
Volume	69 cc
Length	102.4 mm
Width	42.2 mm
Thickness	21.5 mm
Weight	85 g

Parameter by Region	Time
Talk time::	3.5 to 4.5 hours
Standby time:	
APAC and LSA/Brazil	111 to 169 hours
China	58 to 169 hours

## Technical Specifications

Parameter	Unit
Cellular system	CDMA, IS2000
Rx frequency band	869.04 ... 893.91 MHz
Tx frequency band	824.04 ... 848.97 MHz
Output power	23 dBm
Duplex spacing	45 MHz
Number of RF channels	832
Channel spacing	30 kHz
Power levels	-50 to +25.3 dBm CDMA
Method of frequency synthesis	Three digital phase-locked loops: VHF Rx 367.2 MHz VHF Tx 457.2 MHz UHF 1052.61 - 1077.57 MHz
Frequency control	19.2 MHz VCTCXO: AFC used
Receiver type	Linear, one IF for CDMA
Modulator type	OQPSK

## Supported Accessories

Type	Name
AC-1	Retractable charger
ACP-7	AC travel charger
ACP-12	Rapid performance charger
AD-5B	Wireless audio adapter
BHF-1	Headrest handsfree
BL-5C	Standard 850 mAh li-ion battery
CK-6	Universal car installation kit
CARK-126	Car kit (for APAC)
DCV-14	Desk stand with 1-button sync
DKU-5	USB data cable
HDB-4	Boom headset
HS-2R	FM stereo headset (US)
HS-5	Standard earbud headset
HS-10	Retractable headset

Type	Name
LCH-12	Mobile charger
LPS-4	Inductive loopset
MBC-15S	Mobile holder

This page intentionally left blank.