

Nokia Customer Care RH-27 Series Transceivers

General Information

Contents

	Page No
Handportables	3
Sales Package	4
Technical Specifications	4
General Specifications of Transceiver RH-27	4
Supported Accessories	5

Handportables

The Nokia 6225 (RH-27) offers a CDMA trimode (1900/800 MHz CDMA plus 800 AMPS engine supporting 1XRTT). The RH-27 features an integrated VGA camera, integrated FM radio, high-speed data support, IR support, and RUIIM.

RH-27 contains a 128 x 128 color display and has changeable display fonts. There is an internal antenna, GPS (E-911) support, MIDI ringing tones, and an internal vibra.



Sales Package

Name	Type Code
Transceiver	RH-27
Battery (780 mAh Li-Ion)	BLD-3
Rapid Performance Charger (US plug)	ACP-12U

Technical Specifications

General Specifications of Transceiver RH-27

Parameter	Specifications	
Cellular system	CDMA/AMPS, IS-19C, IS-98 IS-2000	PCS J-STD-018, J-STD-008, IS2000
TX frequency band	824.04 ... 848.97 MHz	1850 ... 1910 MHz
RX frequency band	869.04 ... 893.91 MHz	1930 ... 1990 MHz
Number of RF channels	832	1200
Channel spacing	30 kHz	50 kHz
Power levels	-50dBm to +25dBm CDMA, +8dBm to +26dBm AMPS	-50dBm to +23dBm

Parameter	Mode	Value and unit
Talk time	Analog	up to 50min
Talk time	Digital	up to 2.4 hours
Standby time	Analog	up to 20 hours
Standby time	Digital	up to 10 days
Dimensions: length width		105.8 mm - 4.17 inches 44.8 mm - 1.77 inches
Weight		86.7 g - 3.1 ounces

Supported Accessories

Type	Name
BLD-3	Standard 780 mAh Li-ion Battery
ACP-7U	AC Travel Charger (US) 108-132 Vac
ACP-8U	AC Charger
ACP-12U	Rapid Performance Charger (US)
DDC-1	Spare Battery Charger
DCV-15	Desk stand with one-button synchronization
CARK-143	Advanced car kit
BHF-1	Headrest handsfree
LPS-4	Loopset
LCH-12	Cigarette Lighter Charger
HDB-4	Boom Headset
HS-5	Earbud Headset
HDS-3	FM Stereo Headset
HS-3	Fashion Stereo Headset
HS-10	Retractable Headset
DKU-5	USB cable

