

**Nokia Customer Care
6255/6255i/6256/6256i (RM-19)
Mobile Terminal**

General Information

Contents	Page
Introduction	3
Sales Package	4
Supported Accessories	5

Introduction

The Nokia 6255/6255i/6256/6256i mobile terminal offers a CDMA trimode (800/1900 MHz CDMA plus AMPS) engine and includes the following features:

- Fold design
- Integrated VGA camera featuring a flash, digital zoom, and red-eye reduction
- Video and voice recording
- Streaming video and audio
- Integrated FM radio and digital MP3 music player
- Optional Multimedia Memory Card (MMC)
- True GPS support (6255i and 6256i)
- 128 x 160 high-resolution, primary color display
- 96 x 65 secondary display
- Integrated hands-free speaker
- 5-way scrolling
- Calendar, reminder, and memo recording
- Game downloads are available with optional Brew and Java
- Helix, whip, Bluetooth, and GPS (6255i and 6256i) antennas
- Internal vibra
- Side volume keys



Model Numbers	NMP Engine Codes	UI	Factory	Region
6255i, 6256i	0202264	0210118	Brazil	NAM
6255, 6256	0202264	0202441	Brazil	LTA, APAC, China

Parameter	Value and Unit
BL-6C Talk time Standby time	3.25 hours 168 hours
Dimensions: Volume Length Width Thickness Weight	104 cc 87.3 mm 47.4 mm 27 mm 126 grams

Sales Package

Name	Type	Code
Transceiver	RM-19	0512247
Battery BL-6C (1070 mAh Li-Ion)	BL-6C MCM China APAC	0670454 0670463 0670462 0670461
Headsets	HS-5 (no label) HS-5 (English) HS-5 (Brazil) HDS-3	0694120 0694121 0694148 0694093

Supported Accessories

Type	Name
AC-1	Travel Charger
ACP-7	AC Travel Charger
ACP-12	Rapid Performance Charger
BHF-3	Hands-free Headrest
CK-1W	Wireless Car Kit
CK-7	Universal Car Installation Kit
DKU-2	USB Connectivity Cable and PC Suite
DT-1	Music Stand
HDB-4	Boom Headset
HDS-3	FM Stereo Headset
HF-6W	Wireless Handsfree
HS-3	Fashion Stereo Headset
HS-3W	Bluetooth Wireless Headset
HS-4W	Wireless Boom Headset
HS-5	Headset
HS-9	2.5 mm Headset
HS-11	Bluetooth Headset
LCH-12	Cigarette Lighter Charger
LPS-4	Inductive Loopset
RX-3	Medallion
RX-4	Medallion 2
SU-1B	Bluetooth Digital Pen
SU-2	Image Viewer
SU-4	Image Frame
SU-5	Image Viewer Pop-Port
	32, 64, and 128 MB MMC (supports up to 512 MB MMC)

This page intentionally left blank.