# SERVICE MANUAL

NHL-9, RM-69 Cellular Phones

(NMP Part No: 9231334) **Nokia 6820, 6822 Issue 3** 

**COMPANY CONFIDENTIAL** 

NOKIA

## **Amendment Record Sheet**

| Amendment No | Date  | Inserted By   | Comments  |
|--------------|-------|---------------|---|
| Issue 1      | 12/03 | J-AK          |   |
| Issue 2      | 02/04 | J-AK          | System Module: Structure/<br>content partly renewed.<br>Parts Lists and Component<br>Layouts: Parts list replaced<br>and component layout dia-<br>grams added.  |
| Issue 3      | 03/05 | M. Hautaniemi | RM-69 added to the manual.  |
|              |       |               | General Information:<br>RM-69 accessories list and<br>figure added, RM-69 fea-<br>tures added to the transceiver<br>features list.  |
|              |       |               | Parts List: Exploded view updated, Spare Parts Overview added, Mechanical Parts List updated, RM-69 Swap Units table added. NHL-9 TB6_21 parts list added, RM-69 TB6_23ia parts list and component layout diagrams added. |
|              |       |               | Service Sorftware Instructions: RM-69 limits for enerty management calibration table added on page 46. FLS-4S for US area added in POS (Point of Sales) flash concept table on page 72.                                   |
|              |       |               | Service Tools: SS-49 camera tool added.   |
|              |       |               | Disassembly Instructions:<br>Camera module disassembly<br>with the camera tool added.   |

| Amendment No | Date | Inserted By | Comments  |
|--------------|------|-------------|---|
|              |      |             | Troubleshooting Instructions: Excluded for issue 3 version.   |
|              |      |             | System Module: Baseband Block Description figure updated. RM-69 note added to Baseband regulators table. Battery section updated. RM-69 engine board LCD and keyboard LED connections figure added. LCD section updated with RM-69 information. |
|              |      |             | Schematics:<br>NHL-9 TB6_21a schematics<br>and RM-69 TB6_23ia sche-<br>matics added.  |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |
|              |      |             |   |

## Nokia NHL-9, RM-69 Service Manual Structure

- 1 Foreword
- 2 General Information
- 3 Parts Lists and Component Layouts
- 4 Service Software and Tuning Instructions
- 5 Service Tools
- 6 Disassembly/Assembly Instructions
- 7 System Module
- 8(a) Schematics NHL-9
- 8(b) Schematics RM-69

Copyright © 2005 Nokia. All rights reserved.

Reproduction, transfer, distribution or storage of part or all of the contents in this document in any form without the prior written permission of Nokia is prohibited.

Nokia, Nokia Connecting People, Nokia 6820 and Nokia 6822 are trademarks or registered trademarks of Nokia Corporation. Other product and company names mentioned herein may be trademarks or tradenames of their respective owners.

Nokia operates a policy of continuous development. Nokia reserves the right to make changes and improvements to any of the products described in this document without prior notice.

Under no circumstances shall Nokia be responsible for any loss of data or income or any special, incidental, consequential or indirect damages howsoever caused.

The contents of this document are provided "as is". Except as required by applicable law, no warranties of any kind, either express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose, are made in relation to the accuracy, reliability or contents of this document. Nokia reserves the right to revise this document or withdraw it at any time without prior notice.

The availability of particular products may vary by region.

#### **IMPORTANT**

This document is intended for use by qualified service personnel only.

#### Warnings and Cautions

Please refer to the *product's* user guide for instructions relating to operation, care and maintenance including important safety information. Note also the following:

#### Warnings:

- 1. IF THE DEVICE CAN BE INSTALLED IN A VEHICLE, CARE MUST BE TAKEN ON INSTALLATION IN VEHICLES FITTED WITH ELECTRONIC ENGINE MANAGEMENT SYSTEMS AND ANTI-SKID BRAKING SYSTEMS. UNDER CERTAIN FAULT CONDITIONS, EMITTED RF ENERGY CAN AFFECT THEIR OPERATION. IF NECESSARY, CONSULT THE VEHICLE DEALER/MANUFACTURER TO DETERMINE THE IMMUNITY OF VEHICLE ELECTRONIC SYSTEMS TO RF ENERGY.
- 2. THE *product* MUST NOT BE OPERATED IN AREAS LIKELY TO CONTAIN POTENTIALLY EXPLOSIVE ATMOSPHERES EG PETROL STATIONS (SERVICE STATIONS), BLASTING AREAS ETC.
- 3. OPERATION OF ANY RADIO TRANSMITTING EQUIPMENT, INCLUDING CELLU-LAR TELEPHONES, MAY INTERFERE WITH THE FUNCTIONALITY OF INADE-QUATELY PROTECTED MEDICAL DEVICES. CONSULT A PHYSICIAN OR THE MANUFACTURER OF THE MEDICAL DEVICE IF YOU HAVE ANY QUESTIONS. OTHER ELECTRONIC EQUIPMENT MAY ALSO BE SUBJECT TO INTERFERENCE.

#### Cautions:

- 1. Servicing and alignment must be undertaken by qualified personnel only.
- 2. Ensure all work is carried out at an anti-static workstation and that an anti-static wrist strap is worn.
- 3. Ensure solder, wire, or foreign matter does not enter the telephone as damage may result.
- 4. Use only approved components as specified in the parts list.
- Ensure all components, modules screws and insulators are correctly re-fitted after servicing and alignment. Ensure all cables and wires are repositioned correctly.

#### For your safety

#### QUALIFIED SERVICE

Only qualified personnel may install or repair phone equipment.

#### **ACCESSORIES AND BATTERIES**

Use only approved accessories and batteries. Do not connect incompatible products.

#### CONNECTING TO OTHER DEVICES

When connecting to any other device, read its user's guide for detailed safety instructions. Do not connect incompatible products.

#### **ESD** protection



Nokia requires that *product* service points have sufficient ESD protection (against static electricity) when servicing *products*.

Any product of which the covers are removed must be handled with ESD protection. The SIM card can be replaced without ESD protection if the product is otherwise ready for use.

To replace the covers ESD protection must be applied.

All electronic parts of the product are susceptible to ESD. Resistors, too, can be damaged by static electricity discharge.

All ESD sensitive parts must be packed in metallized protective bags during shipping and handling outside any ESD Protected Area (EPA).

Every repair action involving opening the product or handling the product components must be done under ESD protection.

ESD protected spare part packages MUST NOT be opened/closed out of an ESD Protected Area.

For more information and local requirements about ESD protection and ESD Protected Area, contact your local Nokia After Market Services representative.

### **Battery information**

Note that a new battery's full performance is achieved only after two or three complete charge and discharge cycles!

The battery can be charged and discharged hundreds of times but it will eventually wear out. When the operating time (talk-time and standby time) is noticeably shorter than normal, it is time to buy a new battery.

Use only batteries approved by the phone manufacturer and recharge the battery only with the chargers approved by the manufacturer. Unplug the charger when not in use. Do not leave the battery connected to a charger for longer than a week, since overcharging may shorten its lifetime. If left unused a fully charged battery will discharge itself over time.

Temperature extremes can affect the ability of your battery to charge.

For good operation times with Ni–Cd/NiMh batteries, discharge the battery from time to time by leaving the product switched on until it turns itself off (or by using the battery discharge facility of any approved accessory available for the product). Do not attempt to discharge the battery by any other means.

Use the battery only for its intended purpose.

Never use any charger or battery which is damaged.

Do not short-circuit the battery. Accidental short-circuiting can occur when a metallic object (coin, clip or pen) causes direct connection of the + and - terminals of the battery (metal strips on the battery) for example when you carry a spare battery in your pocket or purse. Short- circuiting the terminals may damage the battery or the connecting object.

Leaving the battery in hot or cold places, such as in a closed car in summer or winter conditions, will reduce the capacity and lifetime of the battery. Always try to keep the battery between 15°C and 25°C (59°F and 77°F). A phone with a hot or cold battery may temporarily not work, even when the battery is fully charged. Batteries' performance is particularly limited in temperatures well below freezing.

Do not dispose of batteries in a fire!

Dispose of batteries according to local regulations (e.g. recycling). Do not dispose as household waste.

#### Care and maintenance

The product is a product of superior design and craftsmanship and should be treated with care. The suggestions below will help you to fulfil any warranty obligations and to enjoy this product for many years.

Keep the phone and all its parts and accessories out of the reach of small children.

Keep the phone dry. Precipitation, humidity and all types of liquids or moisture can contain minerals that will corrode electronic circuits.

Do not use or store the phone in dusty, dirty areas. Its moving parts can be damaged.

Do not store the phone in hot areas. High temperatures can shorten the life of electronic devices, damage batteries, and warp or melt certain plastics.

Do not store the phone in cold areas. When it warms up (to its normal temperature), moisture can form inside, which may damage electronic circuit boards.

Do not drop, knock or shake the phone. Rough handling can break internal circuit boards.

Do not use harsh chemicals, cleaning solvents, or strong detergents to clean the phone.

Do not paint the phone. Paint can clog the moving parts and prevent proper operation

Use only the supplied or an approved replacement antenna. Unauthorised antennas, modifications or attachments could damage the phone and may violate regulations governing radio devices.

All of the above suggestions apply equally to the product, battery, charger or any accessory.

#### **Company Policy**

Our policy is of continuous development; details of all technical modifications will be included with service bulletins.

While every endeavour has been made to ensure the accuracy of this document, some errors may exist. If any errors are found by the reader, NOKIA CORPORATION should be notified in writing.

Please state:

Title of the Document + Issue Number/Date of publication Latest Amendment Number (if applicable) Page(s) and/or Figure(s) in error Please send to:

> NOKIA CORPORATION Nokia Customer Care

PO Box 86

FIN-24101 SALO

**Finland**