

Programmes After Market Services NSD-5 Series Transceivers

2. General Information

Contents

	Page No
Product Selection	5
Handportables.....	5
Product and Module List	6
Technical Specifications	6
General Specifications of Transceiver NSD-5FX.....	6

Product Selection

Handportables

The NSD-5FX is a 1900MHz single-band CDMA handportable mobile telephone.

1.



Item	Name	Type code	Material code
1	Transceiver	NSD-5FX	0507296
2	Standard battery	BLB-2	0670322
3	AC Travel charger (US 108-132 VAC)	ACP-7U	0675143

Product and Module List

Unit/type	Product code
Transceiver NSD-5FX	0507296
Battery BLB-2	0670322
Battery stand DDC-1	0675243
AC Travel Charger ACP-7U	0675143
Personal Handsfree HDC-5	0694059
Clip-on Kit SKB-2	0700071
Mobile Charger LCH-9	0675120

Technical Specifications

General Specifications of Transceiver NSD-5FX

Parameter	Unit
Cellular system	PCS 1900 CDMA
RX frequency band	1930-1990 MHz
TX frequency band	1850-1910 MHz
Duplex spacing	80 MHz
Number of RF channels	1200
Channel spacing	50 MHz
Number of TX power levels	50 dBm to max power