



Economical, Tactical Grade IMU Combines with NovAtel's GNSS Technology to Deliver 3D Position, Velocity and Attitude Solution

Benefits

Economical tactical grade IMU

Easy integration with NovAtel's
SPAN-capable GNSS/INS receivers

Short product delivery time

Features

Ring-laser gyro technology

100 Hz data rate

12-28 VDC power input

SPAN INS functionality

SPAN: World-Leading GNSS + INS Technology

SPAN (Synchronous Position, Attitude and Navigation) technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and inertial navigation. The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are tightly coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

UIMU-HG Overview

The UIMU-HG contains the Honeywell HG1700 IMU. The HG1700 is a tactical grade IMU containing ring-laser gyros and servo accelerometers. The UIMU-HG handles the power requirements of the IMU from a 12-28 VDC power input and provides the IMU data to a SPAN enabled GNSS/INS receiver such as the FlexPak6 or SPAN-SE using a custom NovAtel interface. IMU measurements are used by the GNSS/INS receiver to compute a blended GNSS/INS position, velocity and attitude solution at up to 100 Hz. The HG1700 is ITAR controlled and requires export approval for customers outside the United States.

Advantages of UIMU-HG

The HG1700 IMU is available in a range of gyro performance levels from one to five degrees per hour. Honeywell's high production volume of HG1700 IMUs enables excellent tactical grade performance for an economical price with short delivery times. The UIMU-HG is available as a complete assembly including the IMU and environmentally sealed enclosure. For customers who already have the HG1700 IMU, the enclosure can be purchased separately and the IMU easily integrated.

Improve SPAN UIMU-HG Accuracy

Take advantage of our Advance® RTK as well as support for satellite based augmentation systems such as L-Band or SBAS to improve real-time performance and accuracy. For more demanding applications, Inertial Explorer® post-processing software from our Waypoint® Product Group can be used to post-process SPAN UIMU-HG data and offers the highest level of accuracy with the system.

If you require more information about our SPAN IMUs,
visit novatel.com/products/span-gnss-inertial-systems/inertial-measurement-units-imus



novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

SPAN System Performance¹

Horizontal Position Accuracy (RMS)	
Single Point L1	1.5 m
Single Point L1/L2	1.2 m
SBAS	0.6 m
DGPS	0.4 m
L-Band	
VBS	0.6 m
XP	0.15 m
HP	0.1 m
RT-2™	1 cm+1 ppm
Acceleration Accuracy 0.03 m/s RMS ²	
Max Velocity³ 515 m/s	
Data Rate	
IMU Measurements	100 Hz
INS Position	100 Hz
INS Velocity	100 Hz
INS Attitude	100 Hz

IMU Performance⁴

UIMU-H62	
Gyro Input Range	±1000 deg/sec
Gyro Rate Bias	5.0 deg/hr
Gyro Rate Scale Factor	150 ppm
Angular Random Walk	0.5 deg/√hr
Accelerometer Range ⁵	±50 g
Accelerometer Linearity	500 ppm
Accelerometer Scale Factor	300 ppm
Accelerometer Bias	2.0 mg
UIMU-H58	
Gyro Input Range	±1000 deg/sec
Gyro Rate Bias	1.0 deg/hr
Gyro Rate Scale Factor	150 ppm
Angular Random Walk	0.125 deg/√hr
Accelerometer Range ⁵	±50 g
Accelerometer Linearity	500 ppm
Accelerometer Scale Factor	300 ppm
Accelerometer Bias	1.0 mg

IMU Physical and Electrical

Dimensions	168 x 195 x 146 mm
Weight	4.5 kg
Power	
Power Consumption	8 W (typical)
Input Voltage	+12 to +28 V
Connectors	
Power	MIL-C-38999-III, 3 pin
Communication	MIL-C-38999-III, 13 pin

Optional Accessories

- Inertial Explorer post-processing software

Environmental

Temperature	
Operating	-30°C to +60°C
Storage	-45°C to +80°C
Humidity	95% non-condensing
MTBF	2,000 hrs
Waterproof	IEC 60259 IPX7
Dust	IEC 60259 IP6X

Performance During GNSS Outages (UIMU-H58)¹

Outage Duration	Positioning Mode	Position Accuracy (m) RMS		Velocity Accuracy (m/s) RMS		Attitude Accuracy (degrees) ² RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK	0.020	0.050	0.020	0.010	0.010	0.010	0.021
	HP	0.100	0.080	0.020	0.010	0.010	0.010	0.022
	SP	1.200	0.600	0.020	0.010	0.010	0.010	0.023
	PP ⁶	0.010	0.015	0.020	0.010	0.007	0.007	0.010
10 s	RTK	0.090	0.050	0.023	0.010	0.014	0.014	0.026
	HP	0.320	0.260	0.028	0.012	0.015	0.015	0.028
	SP	1.720	1.590	0.030	0.012	0.015	0.015	0.028
	PP ⁶	0.020	0.020	0.200	0.010	0.008	0.008	0.012
60 s	RTK	2.450	0.280	0.096	0.013	0.016	0.016	0.035
	HP	2.870	0.490	0.102	0.013	0.017	0.017	0.039
	SP	3.490	1.680	0.105	0.014	0.017	0.017	0.040
	PP ⁶	0.011	0.040	0.030	0.010	0.009	0.009	0.016



Version 7 - Specifications subject to change without notice.
 ©2012 NovAtel Inc. All rights reserved.
 NovAtel, SPAN, Inertial Explorer, AdVance and Waypoint are registered trademarks of NovAtel Inc.
 FlexPak6 and RT-2 are trademarks of NovAtel Inc.
 Printed in Canada. D10152
 UIMU-HG July 2012

For the most recent details of this product:
novatel.com/assets/Documents/Papers/HG1700_SPAN58.pdf

¹ Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

² When SPAN is in RTK mode.

³ Export licensing restricts operation to a maximum of 515 metres per second.

⁴ For UIMU-H62 Performance During GNSS Outages Table, please visit novatel.com/assets/Documents/Papers/IMU-HG62table.pdf

⁵ GNSS receiver sustains tracking up to 4 g.

⁶ Post-processing results using Inertial Explorer software.



Statements related to the export of products are based solely on NovAtel's experience in Canada, are not binding in any way and exportability may be different with respect to the export regulations in effect in another country. The responsibility for re-export of product from a Customer's facility is solely the responsibility of the Customer.