

Compact DMM/AC Clamp Meter/Digital Thermometer

HHM61
\$119



- **Measures: Current to 400 A ac; Voltage to 750 Vac, 400 Vdc; Resistance to 400 Ω**
- **Reads Type K Thermocouple Directly**
- **Diode Test Function**
- **Peak Hold Feature**
- **Recessed Safety Test Lead Input Jacks**

The HHM61 combination DMM/ac current clamp meter/digital thermometer is a compact, lightweight, multi-function test and measurement instrument at an economical price. The HHM61 is ideal for electrician's and technicians who need a portable test instrument that is both accurate and reliable. The integral ac clamp meter function makes this meter ideal for troubleshooting the operation of electric resistance heaters and other plant electrical systems.

Specifications

General

Display: 3½ digit LCD, max reading 3999, with automatic sign, AC, BAT, and peak hold indicators

Overrange Indication: "OL" displayed

Low Battery: "BAT" displayed

Measurement Rate: 3 measurements per second, nominal

Operating Temperature: 0 to 50°C (32 to 122°F), 0 to 70% RH

Storage Temperature: -20 to 60°C (0 to 140°F), 0 to 80% RH with battery removed

Accuracy: Accuracy specifications at 23 ±5°C (73 ±9°F), less than 75% RH

Power: 9 V battery (included)

Battery Life: 100 hours typical (alkaline battery)

Weight: 270 g (9.4 oz) including battery

Dimensions: 33 H x 82 W x 192 mm L (1.3 x 3.2 x 7.5")

AC Current

Ranges: 40 A, 400 A

Resolution: 10 mA (40 A range), 100 mA (400 A range)

Accuracy: ±2.0% rdg + 4 digits at 50 to 60 Hz

Jaw Opening: 3.18 cm (1.25")

AC Voltage

Ranges: 400 V, 750 V

Resolution: 100 mV (400 V range), 1 V (750 V range)

Accuracy: ±1.2% rdg + 4 digits at 50 to 500 Hz (400 V range) and ±1.5% rdg + 4 digits at

50 to 500 Hz (750 V range)

Input Impedance: 10 MΩ

Overload Protection: 1200 Vdc/800 Vac on both ranges

DC Voltage

Ranges: 4 V, 40 V, 400 V

Resolution: 1 mV (4 V range), 10 mV (40 V range),

100 mV (400 V range)

Accuracy: ±0.5% rdg + 1 digit

Input Impedance: 10 MΩ

Overload Protection: 1200 Vdc/800 Vac on all ranges

Resistance

Range: 400 Ω

Resolution: 0.1 Ω

Accuracy: ±1% rdg + 1 digit

Overload Protection: 500 Vdc/350 Vac

HHM61, \$119, shown smaller than actual size.



Test leads included.

Thermocouple Included!

Temperature models include a free 1 m (40") Type K insulated beaded wire thermocouple with subminiature connector and wire spool caddy (1 per channel).

Order a Spare!
Model No. SC-GG-K-30-36, \$15.

Temperature

Ranges: -50 to 750°C

(-58 to 1400°F)

Resolution: 1°F/C

Accuracy: ±3% rdg

+ 1 digit from -20 to 750°C-

(4 to 1400°F) and ±5% rdg

+ 2 digits from -50 to -20°C (-58 to -4°F)

Diode Test

Test Current: 1 mA

Test Voltage: 3.4 V max

Overload Protection: 500 Vdc/350 Vac

Continuity

Response Time: 100 msec (instant continuity buzzer)

Overload Protection: 500 Vdc/350 Vac

AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number)

Model No.	Price	Description
HHM61	\$119	Compact DMM/A AC clamp meter/digital thermometer

Comes with test leads, Type K beaded wire probe, 9 V battery, wrist strap, carrying case and operator's manual.

Ordering Example: HHM61, compact DMM, \$119.



UNITED STATES

www.omega.com
1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de
Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk
Manchester, England
0800-488-488

FRANCE

www.omega.fr
Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters