


TX-21AD3F Service Manual

Safety
Specifications
Parts List
Service Information
Adjustments
Self Check
Service Hints
Mechanical View
Disassembly
Location of Controls
Waveforms



Block Diagrams



Schematic Diagrams



PCB Views

Service Support

Service and repair of this product is supported by Panasonic's LUCI interface.

This interface provides a link between the TV and a standard PC to allow a number of diagnostic and control functions to be performed.


For more details contact your local Panasonic company.

←
BACK

EXIT

Video / Audio

Control


BACK

B - PCB

E - PCB

B - Schematic

E - Schematic


Y - PCB

P - Schematic

Y - Schematic


BACK


BACK

Service Manual



Colour Television
TX-21AD3F

EURO-2M Chassis

Specifications

Power Source : 220 – 240 V AC, 50Hz

Power Consumption : 75W

Aerial Impedance : 75Ω unbalanced, Coaxial Type

Receiving System : PAL B, G, H PAL – 60

SECAM B, G L, L'

MNTSC, NTSC (AV Only)

VHF E2 – E12

VHF A – H (ITALY)

VHF R1 – R2

VHF R6 – R12

CATV (S01 – S05)

CATV S11 – S20 (U1 – U10)

Intermediate Frequency :

Video 38.9MHz, 34MHz

Sound 33.16MHz, 33.4MHz, 32.4MHz, 33.05MHz

40.4MHz, 32.9MHz

Colour 34.47MHz, 34.5MHz, 34.65MHz

Video / Audio Terminals :

AV1 IN	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms 10kΩ
	RGB (21 pin)	

AV1 OUT	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms 1kΩ

AV2 IN	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms 10 kΩ
	S-Video IN	Y : 1V p-p 75Ω
	(21 pin)	C : 0.3V p-p 75Ω

AV2 OUT	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms 1kΩ

AV3 IN	Audio (RCA x 2)	500mV rms 10kΩ
	Video (RCA x 1)	1V p-p 75Ω

High Voltage : 27kV ± 1kV at zero beam current

Picture Tube : A51ECQ51X01 51 cm

Visible screen size: 90° deflection

Audio Output : Internal Speaker
2 x 20W (Music Power)
8Ω Impedance

Headphones 8Ω Impedance

Accessories supplied : Remote Control
2 x R6 (UM3) Batteries

Dimensions :
Height : 465mm
Width : 558mm
Depth : 495mm

Net Weight 23kg

Specifications are subject to change without notice.
Weight and dimensions shown are approximate.

Technische Daten

Netzspannung : 220 – 240 V AC, 50Hz

Leistungsaufnahme : 75W

Antennenimpedanz : 75Ω asymmetrisch, Koaxial – Typ

PAL B, G, H PAL – 60

SECAM B, G L, L'

MNTSC, NTSC (nur AV Eingang)

VHF E2 – E2

VHF A – H (ITALY)

VHF R1 – R2

VHF R6 – R12

CATV (S01 – S05)

CATV S11 – S20 (U1 – U10)

CATV S21 – S41 (HYPERBAND)

Zwischenfrequenz :

Video 38.9MHz, 34MHz

Sound 33.16MHz, 33.4MHz, 32.4MHz, 33.05MHz

40.4MHz, 32.9MHz

Colour 34.47MHz, 34.5MHz, 34.65MHz

Video / Audio Anschlüsse :

AV1 EINGANG	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms10kΩ
	RGB (21 pin)	

AV1 AUSGANG	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms1kΩ

AV2 EINGANG	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms 10 kΩ
	S-Video IN	Y : 1V p-p 75Ω
	(21 pin)	C : 0.3V p-p 75Ω

AV2 AUSGANG	Video (21 pin)	1V p-p 75Ω
	Audio (21 pin)	500mV rms1kΩ

AV3 EINGANG	Audio (RCA x 2)	500mV rms10kΩ
	Video (RCA x 1)	1V p-p 75Ω

Hochspannung :

27kV ± 1kV bei Nullstrahlstrom

Bildrohre : A51ECQ51X01 51 cm

Visuelle Diagonale : 90° Ablenkung

Ton Ausgangsleistung :

Einbaulautsprecher

2 x 20W (Musikleistung)

8Ω Impedanz

Kopfhörer

Mitgel. Zubehör

8Ω Impedanz

Fernbedienung

2 x R6 (UM3) Batterien

Abmessungen :

Höhe : 465mm

Breite : 558mm

Tiefe : 495mm

Gewicht

23kg

Änderungen der technischen Daten vorbehalten.

Gewichte und Abmessungen sind Näherungsangaben.

Panasonic

CONTENTS

SAFETY PRECAUTIONS
LOCATION OF CONTROLS
SERVICE HINTS
ADJUSTMENTS
SELF CHECK
WAVEFORM PATTERN TABLE
BLOCK DIAGRAM
PARTS LOCATION
REPLACEMENT PARTS LIST
CONDUCTOR VIEWS
SCHEMATIC DIAGRAMS

SAFETY PRECAUTIONS

General Guide Lines

1. It is advisable to insert an isolation transformer in the AC supply before servicing a hot chassis.
2. When servicing, observe the original lead dress in the high voltage circuits. If a short circuit is found, replace all parts which have been overheated or damaged by the short circuit.
3. After servicing, see that all the protective devices such as insulation barriers, insulation papers, shields and isolation R-C combinations are correctly installed.
4. When the receiver is not being used for a long period of time, unplug the power cord from the AC outlet.
5. Potentials as high as 28kV are present when this receiver is in operation. Operation of the receiver without the rear cover involves the danger of a shock hazard from the receiver power supply. Servicing should not be attempted by anyone who is not familiar with the precautions necessary when working on high voltage equipment. Always discharge the anode of the picture to the chassis before handling the tube.
6. After servicing make the following leakage current checks to prevent the customer from being exposed to shock hazards.

LEAKAGE CURRENT COLD CHECK

1. Unplug the AC cord and connect a jumper between the two prongs of the plug.
2. Turn on the receiver's power switch.
3. Measure the resistance value with an ohmmeter, between the jumpered AC plug and each exposed metallic cabinet part on the receiver, such as screw heads, aerials, connectors, control shafts etc. When the exposed metallic part has a return path to the chassis the reading should be between 4M ohm and 20M ohm. When the exposed metal does not have a return path to the chassis the reading must be infinite.

INHALT

SICHERHEITSVORKEHRUNGEN
LAGE DER EINSTELLREGLER
WARTUNGSHINWEISE
JUSTIERUNGEN
SELBSTDIAGNOSE
SIGNAL TABELLE
SCHALTBILD BLOCK
EXPLOSIONSZEICHNUNG
ERSATZTEILLISTE
ANSICHT DER LEITERBAHNEN
SCHALTBILD SCHEMA

SICHERHEITSVORKEHRUNGEN

Allgemeine Richtlinien

1. Es ist empfehlenswert einen Trenntransformator in die Stromversorgung zu schalten, bevor Reparaturen an einem Gerät vorgenommen werden, dessen Chassis unter Spannung steht.
2. Bei der Durchführung von Servicearbeiten dürfen die ursprünglichen Kabelanschlüsse nicht vertauscht werden. Dies gilt insbesondere für die Anschlüsse im Hochspannungsteil. Hat sich ein Kurzschluß ereignet, dann sind alle Teile, an denen Spuren von Überhitzung sichtbar sind, auszuwechseln.
3. Nach Beenden der Servicearbeiten ist sicherzustellen, daß alle Sicherheitsvorrichtungen, wie Isolationsstege, Isolationspapiere, Abschirmungen und Isolations-R/C-Glieder wieder richtig eingesetzt sind.
4. Wenn der Fernseher während längerer Zeit nicht in Betrieb gesetzt wird, sollte der Netzstecker aus der Netzsteckdose gezogen werden.
5. Im Betrieb sind Spannungen bis zu 28kV in diesem Gerät vorhanden. Die Inbetriebnahme des Fernsehers ohne aufgesetzte Rückwand bringt die Gefahr eines elektrischen Schläges von der Fernseher-Stromversorgung mit sich. Servicearbeiten sollten daher auch nie durch Personen versucht werden, die nicht in vollem Umfang mit den Sicherheitsvorkehrungen beim Umgang mit Hochspannungsgeräten vertraut sind. Vor der Handhabung mit der Bildröhre ist die Anode der Bildröhre immer an dem Empfängerchassis zu entladen.
6. Nach Beenden der Servicearbeiten sind die folgenden Kriechstrom-Prüfungen durchzuführen, um den Kunden vor der Gefahr eines elektrischen Schläges zu schützen.

MESSUNG DES ISOLATIONSWIDERSTANDES IM ABGESCHALTETEN ZUSTAND

1. Den Netzstecker aus der Netzsteckdose ziehen und die beiden Steckerstifte kurzschließen.
2. Den Geräteschalter des Fernsehgerätes einschalten.
3. Mit einem Ohmmeter den Widerstandswert zwischen dem überbrückten Netzstecker und jedem zugänglichen Metallteil am Gehäuse des Fernsehgerätes, wie Schraubenköpfen, Antennen, Achsen der Regler, Griffassungen usw messen. Wenn ein zugängliches Metallteil keine Rückleitung zum Chassis hat, muß die Anzeige unendlich betragen.

LEAKAGE CURRENT HOT CHECK

1. Plug the AC cord directly into the AC outlet. Do not use an isolation transformer for this check.
2. Connect a $2k\Omega$ 10W resistor in series with an exposed metallic part on the receiver and an earth such as a water pipe.
3. Use an AC voltmeter with high impedance to measure the potential across the resistor.
4. Check each exposed Metallic part and check the voltage at each point.
5. Reverse the AC plug at the outlet and repeat each of the above measurements.
6. The potential at any point should not exceed 1.4 Vrms. In case a measurement is outside the limits specified, there is a possibility of a shock hazard, and the receiver should be repaired and rechecked before it is returned to the customer.

HOT CHECK CIRCUIT

SCHALTUNGSANFABAU FÜR PRUFUNG IM EINGESCHALTEIN ZUSTAND




Fig.1
Abb.1

X-RADIATION WARNING

1. The potential sources of X-Radiation in TV sets are the high voltage section and the picture tube.
2. When using a picture tube test jig for service ensure that the jig is capable of handling 28kV without causing X-Radiation.

NOTE : It is important to use an accurate periodically calibrated high voltage meter

1. Set the brightness to minimum.
2. Measure the high voltage. The meter should indicate $27\text{kV} \pm 1\text{kV}$ if the meter indication is out of tolerance, immediate service and correction is required to prevent the possibility of premature component failure.
3. To prevent any X-Radiation possibility, it is essential to use the specified tube.

MESSUNG DES KRIECHSTROMS IM EINGESCHALTEIN ZUSTAND

1. Den Netzstecker direkt in eine Netzteckdose stecken. Für diese Messung keinen Trenntransformator verwenden.
2. Einen $2k\Omega / 10\text{W}$ -Widerstand in Serie mit einem von außen zugänglichen Metallteil am Fernsehgerät und einer guten, Erdung z.B Wasserleitung, anschließen.
3. Ein Wechselstrom-Voltmeter mit einem Meßbereich von 1000 Ohm.Volt oder größer verwenden, um die Spannung über den Widerstand zu messen.
4. Jedes zugängliche Metallteil prüfen, und an jedem Punkt die Spannung messen.
5. Den Netzstecker umgekehrt in die Steckdose stecken und jede der obigen Messungen wiederholen.
6. Die Spannung darf an keinem der Punkte 1.4V eff. überschreiten. Wird dieser Wert nicht eingehalten, besteht die Gefahr eines elektrischen Schläges, und das Fernsehgerät sollte daher repariert und nachgeprüft werden, bevor es an den Kunden zurückgegeben wird.

RÖNTGENSTRahlUNG ACHTUNG :

1. Potentielle Quellen von Röntgenstrahlung in Fernsehgeräten sind das Hochspannungsteil und die Bildröhre.
2. Bei Verwendung eines Bildröhren-Prüfgerätes für den Service ist sicherzustellen, daß es für die Belastung von 28kV geeignet ist, ohne daß eine Röntgenstrahlung verursacht wird.

ANMERKUNG : Es ist wichtig, daß ein präzises, regelmäßig geprüftes Voltmeter verwendet wird.

1. Helligkeit auf Minimum stellen.
2. Die Hochspannung messen. Die Anzeige des Instrumentes sollte $27\text{kV} \pm 1\text{kV}$ betragen. Falls die Anzeige diese Toleranzgrenzen überschreitet, ist die sofortige Behebung nötig, um die Möglichkeit vorzeitigen Komponentenausfalls zu verhindern.
3. Um die Möglichkeit von Röntgenstrahlung zu begrenzen, ist es wichtig, daß nur die vorgeschriebene Bildröhre verwendet wird.

LOCATION OF CONTROLS

LAGE DER EINSTELLREGLER




Fig.2
Abb.2

SERVICE HINTS


How to remove the rear cover

1. Remove the 5 screws (A) as shown in Fig.3/Fig.4.

SERVICE HINWEISE

Entfernen Der Geräterückwand

1. Die 5 Schrauben (A) entfernen, siehe Abb.3/Abb.4.



SCREWS (A)
SCHRAUBEN A
Fig.3.
Abb.3.

Fig.4
Abb.4

ADJUSTMENT PROCEDURE

The remote control is used for entering and storing adjustments, with the exception of cut-off adjustments which must always be done prior to service adjustment. Perform adjustments in accordance with screen display. The display on the screen also specifies the CCU variants as well as the approx. setting values. The adjustment sequence for the service mode is indicated below.

1. Set the Bass to maximum position, set the Treble to minimum position, press the F button followed by the volume down button on the customer controls at the front of the TV and at the same time press the Reveal button on the remote control, this will place the TV into the Service Mode.
2. Press the RED / GREEN buttons to step up / down through the functions.
3. Press the YELLOW / BLUE buttons to alter the function values.
4. Press the STORE button after each adjustment has been made to store the required values.
5. To exit the Service Mode press the Normalisation button..

NOTE: This TV also has the option of using a Memory Pack which enables you to copy the preset TV channels into the Memory Pack and then download them onto this or any other EURO-2 TV set.

TV to Memory Pack process

1. Plug the memory pack into the lower of the two 21 pin terminals at the back of the TV and switch the TV on. If the TV has only one 21 pin connector then this will be able to accept the memory pack.
2. Go into the Service Mode as explained above. The screen will show:—

Program
External >> TV

3. Press the blue button on the remote control. The screen will show:—

Program
TV >> External

4. Press the STORE button on the TV. The screen will show:—

Storing

5. All the tuning information stored inside the TV will now be transferred to the Memory Pack. This process will take 2–3 minutes to complete and when finished the screen will show:—

OK!

Memory Pack to TV Process

1. Plug the memory pack into the lower of the two 21 pin terminals at the back of the TV and switch the TV on. If the TV has only one 21 pin connector then this will be able to accept the memory pack.
2. Go into the Service Mode as explained above. The screen will show:—

Program
External >> TV

3. Press the STORE button on the TV. The screen will show:—

Loading

4. All the tuning information stored inside the Memory Pack will now be transferred to the TV. This process will take 2–3 minutes to complete and when finished the screen will show:—

OK!

5. The tuning information from the Memory Pack has now been copied into the TV.

6. To exit from the Service Mode press the Normalisation button.

7. The process has now been completed and the Memory Pack can now be removed.

Errors

If an error occurs while using the Memory Pack the TV will detect this and the screen will show:—

Program
Error!

If this happens then press the Normalisation button and repeat the process that was being used. If the errors continue to occur then check the connectors between the TV and the memory pack and check the 9V battery inside the memory pack.

ABGLEICHVERFAHREN

Die Fernbedienung dient zum Eingeben und Abspeichern der Einstellwerte, mit Ausnahme der Sperrpunkteinstellung, die grundsätzlich vor den hier beschriebenen Einstellungen vorgenommen werden muss. Die Einstellung erfolgt entsprechend dem Bildschirm–Display. Auf dem Bildschirm–Display erscheinen auch die CCU–Varianten sowie die ungefähren Einstellwerte. Die Einstellfolge für den Service–Modus ist nachstehend beschrieben.

1. Den Tiefenregler auf Höchststellung und den Höhenregler auf Mindeststellung stellen. Nachdem die F–Taste am Bedienfeld des FS–Gerätes gedrückt wurde, die Die Taste "Lautstärke Minus" am FS–Gerät drücken und gleichzeitig die Taste "Reveal" auf der Fernbedienung betätigen. Hierdurch wird das FS–Gerät auf Service–Modus geschaltet.
2. Die einzelnen Funktionen mit Hilfe der ROTEN und GRÜNEN Taste anwählen.

3. Mit der GELBEN und BLAUEN Taste die Werte der einzelnen Funktionen ändern.
4. Nach jeder Einstellung die Taste STR auf der Fernbedienung oder am Bedienfeld drücken, um die geänderten Werte abzuspeichern.
5. Zum Verlassen des Service–Modus die "N"–Taste auf der Fernbedienung drücken

HINWEIS: Dieses FS–Gerät bietet auch die Möglichkeit eines Memory Pack, mit dem Sie die gewählten Fernsehkanäle abspeichern und auf jedes beliebige EURO2 FS–Gerät umkopieren können.

Kopieren der Einstelldaten vom FS–Gerät in das Memory Pack

1. Das Memory Pack in die untere der beiden 21–poligen Steckerleisten an der Rückseite des FS–Geräts stecken und das Gerät einschalten. Wenn das FS–Gerät nur eine 21–polige Anschlussleiste hat, kann das Memory Pack auch an diese angeschlossen werden.
2. Wie schon oben beschrieben auf Service–Modus umschalten. Auf dem Bildschirm erscheint:

Program
External>>TV

3. Nun die blaue Taste an der Fernbedienung betätigen. Auf dem Bildschirm erscheint:

Program
TV>>External

4. Die Taste STORE am Fernseher drücken. Der Bildschirm meldet nun:

Storing

5. Die im FS–Gerät abgespeicherten Kanal–Einstelldaten werden nun in das Memory Pack überspielt. bei abgeschlossener Datenübertragung meldet der Bildschirm:

OK!

Kopieren der Einstelldaten vom Memory Pack in das FS–Gerät

1. Das Memory Pack in die untere der beiden 21–poligen Steckerleisten an der Rückseite des FS–Geräts stecken und das Gerät einschalten. Wenn das FS–Gerät nur eine 21–polige Anschlussleiste hat, kann das Memory Pack auch an diese angeschlossen werden.
2. Wie schon oben beschrieben auf Service–Modus umschalten. Auf dem Bildschirm erscheint:

Program
External>>TV

3. Die Taste STORE am Fernseher drücken. Der Bildschirm meldet nun:

Loading

4. Die im Memory Pack abgespeicherten Einstelldaten werden nun in das FS–Gerät überspielt. bei abgeschlossener Datenübertragung meldet der Bildschirm:

OK!

5. Die Kanal–Einstelldaten sind damit vom Memory Pack in das FS–Gerät überspielt.

6. Zum Verlassen des Service–Modus die "N"–Taste auf der Fernbedienung drücken
7. Der Kopievorgang ist somit abgeschlossen, und das Memory Pack kann von der Steckerleiste abgezogen werden.

Fehler

Falls beim Gebrauch des Memory Packs Fehler auftreten, zeigt das FS–Gerät dies auf dem Bildschirm mit der folgenden Meldung an:

Program
Error!

In diesem Fall muss der Service–Modus durch Drücken der "N"–Taste auf der Fernbedienung verlassen und anschliessend der Vorgang wiederholt werden. Falls weiterhin Fehlermeldungen erscheinen, müssen die Anschlusskontakte zwischen FS–Gerät und Memory Pack sowie die 9V Batterie im Memory Pack kontrolliert werden.

ADJUSTMENT PROCEDURE

Item/Preparation	Adjustments
+B SET-UP 1. Receive a test pattern 2. Set the controls: Brightness minimum Contrast minimum Volume minimum	1. Set the +B voltage up as follows: Adjust R811 so that B2 shows $130V \pm 1V$ 2. Confirm the following voltages. B1 $200 \pm 10V$ B6 $12 \pm 0.5V$ B3 $27 \pm 1V$ B7 $5 \pm 0.1/-0.25V$ B4 $35.5 \pm 1V$ B8 $5 \pm 0.25V$ B5 $15.5 \pm 1V$ U33 $31 \pm 1V$
RF AGC 1. Receive a test pattern. 2. Connect an oscilloscope between the tuner RF AGC and ground. 3. Set the oscilloscope gain range to 1V/div.	1. Check that the noise becomes large when the RF AGC VR R126 is turned counterclockwise. After the check adjust to previous setting (clockwise). 2. Gradually turn the RF AGC VR anti-clockwise, and set the RF AGC VR to the point where the RF AGC voltage is just falling to a point where this voltage drops by 0.2V from the maximum value.
CUT OFF 1. Receive a test pattern. 2. Degauss the tube externally. 3. Set the TV into Service Mode 1. 4. Select Cutoff DC mode.	1. Confirm the value is 128 and select Ug2 mode noting colour with largest value 2. Turn the screen VR until a colour reaches 20~30. 3. Connect an oscilloscope to the cathode with the biggest value colour. 4. Select Cutoff DC mode and adjust Cutoff pulse to $159V \pm 5V$. 5. Disconnect the oscilloscope and adjust the screen to whichever colour reaches 70 ± 30 first.

ABGLEICH

Vorbereitung	Abgleich
+B – Abgleich 1. Testbild empfangen. 2. Helligkeit auf Minimum Kontrast auf Minimum Lautstärke auf Minimum	1. Mit R811 muß die B2 auf $130V \pm 1V$ eingestellt werden. 2. Folgende Spannungen sind zu überprüfen : B1 $200 \pm 10V$ B6 $12 \pm 0.5V$ B3 $27 \pm 1V$ B7 $5 \pm 0.1/-0.25V$ B4 $35.5 \pm 1V$ B8 $5 \pm 0.25V$ B5 $15.5 \pm 1V$ U33 $31 \pm 1V$
RF AGC 1. Testbild empfangen. 2. An die Tuner RF AGC und Masse ein Oszilloskop anschließen. 3. Die Empfindlichkeit des Oszilloskopes auf 1V/div. einstellen.	1. Wenn das Poti R126 (RF AGC) gegen den Uhrzeigersinn gedreht wird. muß das Rauschen zunehmen. 2. Das Poti R126 gegen den Uhrzeigersinn so einstellen, daß die eingestellte Spannung um 0,2V unter dem Maximalwert
CUT OFF 1. Testbild empfangen. 2. Bildröhre entmagnetisieren. 3. Service-Mode 1 anwählen. 4. Im Service-Mode den Abgleichpunkt Cutoff DC-Mode wählen (14).	1. Im Feld Cutoff DC muß der Wert 128 stehen, Im Ugz-Feld muß Farbe mit dem höchstem Wert notiert werden. 2. Mit dem Screen-Poti wird die Farbe auf 20 bis 30 eingestellt. 3. An die Kathode mit den höchsten Wert (aus Punkt 1) wird ein Oszilloskop angeschlossen. 4. Im Cutoff DC Mode wird der Cutoff-Puls auf $159V \pm 5V$ eingestellt. 5. Das Oszilloskop entfernen und im Cutoff Mode die Werte so einstellen, daß sie alle bis 70 ± 30 liegen.

ALIGNMENT SETTINGS (The figures used below are nominal and used for representative purposes only)

Alignment Function	TX-21AD3F	Settings / Special features
1. Vertical amplitude	V-AMP 051	
2. Vertical symmetry	V-SYM 013	Optimum setting
3. Vertical linearity	V-LIN 012	
4. Vert. DC.	Vert. D.C.. 000	Not to be adjusted.
5. V-Pos.	V. Pos. 003	Optimum setting
6. Horizontal amplitude	H-AMP -033	
7. Horizontal position	H-POS 049	Optimum setting
8. Text Position	TEXT POSITION 045	Optimum setting
9. EW-amplitude	E-W-AMP 1 -058	Optimum setting
10. EW-amplitude	E-W-AMP 2 023	Optimum setting
11. Trapezium-comp	TRAPEZ-1 -014	Optimum setting
12. Trapezium-comp	TRAPEZ-2 012	Optimum setting
13. Colour VCO	Colour VCO 015	Press either Blue or Yellow buttons to effect automatic adjustment
14. Cut-off DC	Cut-off DC 050	Not to be adjusted.
15. Ug2 Test	Ug 2 Test 107 021 023	Select Cutoff DC in Service Mode mode and confirm the value is 128. Select Ug 2 Test noting colour with largest value, adjust on FBT until a colour reaches 20 ~ 30. Connect an oscilloscope to the cathode of the biggest value colour, select Cutoff DC mode and adjust get Cutoff pulse voltage to $159 \pm 5V$. Disconnect the oscilloscope and adjust the screen to whichever colour reaches 70 ± 30 first.
16. Cutoff	Cutoff 045 055 050	Press the GREEN button to step through the settings. Adjust for optimum.
17. White	White 224 255 237	Press the GREEN button to step through the settings. Adjust for optimum.

ABGLEICHTABELLE

(Die angegebenen Werte sind Mittelwerte und können individuell nach oben oder unten nach dem korrekten Abgleich abweichen)

Abgleichfunktion	TX-21AD3F	Einstellung/Besondere Merkmale
1. Vertikale Amplitude	V-AMP 051	
2. Vertikale symmetrie	V-SYM 013	Optimale Einstellung
3. Vertical linearität	V-LIN 012	
4. Vert. DC.	Vert. D.C.. 000	Nicht einstellen
5. V-Pos.	V. Pos. 003	Optimale Einstellung
6. Horizontale Amplitude	H-AMP -033	
7. Horizontale position	H-POS 049	Optimale Einstellung
8. Text Position	TEXT POSITION 045	Optimale Einstellung
9. OW-amplitude	E-W-AMP 1 -058	Optimale Einstellung
10. OW-amplitude	E-W-AMP 2 023	Optimale Einstellung
11. Trapez-Kompensation	TRAPEZ-1 -014	Optimale Einstellung
12. Trapez-Kompensation	TRAPEZ-2 012	Optimale Einstellung
13. Colour VCO	Colour VCO 015	Auf minimale Schwebung einstellen.
14. Cut-off DC	Cut-off DC 050	Nicht einstellen
15. Bildschirm	Ug 2 Test 107 021 023	Wählen Sie den Cutoff DC Im Service Mode und bestätigen Sie den Wert 128. Im Ug2-Feld muß die Farbe mit dem höchsten Wert notiert werden. Mit dem Screen-Poti wird die Farbe auf 20 bis 30 eingestellt. An die Kathode mit den höchsten Wert (aus Punkt 1) wird ein Oszilloskop angeschlossen. Im Cutoff DC Mode wird der Cutoff-Puls auf $159V \pm 5V$ eingestellt. Das Oszilloskop entfernen und im Cutoff Mode die Werte so einstellen, daß sie alle bis 70 ± 30 liegen.
16. Cutoff	Cutoff 045 055 050	Die Einstellungen mit Hilfe der GRÜNEN Taste anwählen. Optimale Einstellung.
17. White	White 224 255 237	Die Einstellungen mit Hilfe der GRÜNEN Taste anwählen. Optimale Einstellung.

SELF CHECK

Self check is used to automatically check the Bus Lines and Hexadecimal code of the TV set.

To get into the Self Check mode press the F button followed by the volume down button on the customer controls at the front of the TV at the same time pressing the Status button, on the Remote Control, and the screen will show:—

1 —— ok	Tuner
2 —— ok	VIF
3 —— ok	EEPROM
4 —— ——	Sound AV switch1
5 —— ok	Video AV switch1
6 —— ok	VDP
7 —— ok	TPU
8 —— ok	MSP
9 —— ——	Dolby Sub
10 —— ——	Dolby IC for L/R

11 —— ——	Dolby IC for C/R
12 —— ok	P S MODE
13 —— ok	P TAO
14 —— ok	P TA1
15 —— ok	P TA2
16 —— ok	P TA3
17 —— ok	P SDA
18 —— ok	P SCL1
19 —— ok	P SCL3
20 —— ok	P SCL4

If the CCU ports have been checked and found to be incorrect then "——" will appear in place of "OK".

Hex codes

21 —— ok	P SBLED
22 —— ok	P OFF
23 —— ok	P DEFL
24 —— ok	P RAM

6A
22
21
94
95

SELBSTDIAGNOSE

1) Die Selbstdiagnose dient zum automatischen Prüfen der Bus-Leitungen sowie des Hexadezimalcodes des FS-Geräts.

Zum Umschalten auf Selbstdiagnose nach dem Drücken der "F"—Taste die "Lautstärke Minus" Taste am Bedienfeld des FS—Geräts und gleichzeitig die Taste "Status" an der Fernbedienung drücken; auf dem Bildschirm erscheint hierauf:—

2) Nach der Selbstdiagnose wird das Gerät automatisch auf sämtliche werkseitigen Standardeinstellungen zurückgesetzt.

1 —— ok	Tuner	11 —— ——	Dolby IC for C/R
2 —— ok	ZF—Verstärker	12 —— ok	P S MODE
3 —— ok	EEPROM	13 —— ok	P TAO
4 —— ——	Audio AV—Schalter 1	14 —— ok	P TA1
5 —— ok	Video AV switch1	15 —— ok	P TA2
6 —— ok	Video AV—Schalter 1	16 —— ok	P TA3
7 —— ok	Video AV—Schalter 2	17 —— ok	P SDA
8 —— ok	MSP	18 —— ok	P SCL1
9 —— ——	Dolby Sub	19 —— ok	P SCL3
10 —— ——	Dolby IC for L/R	20 —— ok	P SCL4


Wenn der Hauptprozessor (CCU) an den Anschlüssen einen Fehler finden sollte, oder der Anschluss nicht belegt ist, zeigt die entsprechende Position —— anstelle von OK an.

Hexadezimalcode


21 —— ok	P SBLED
22 —— ok	P OFF
23 —— ok	P DEFL
24 —— ok	P RAM

6A
22
21
94
95

WAVEFORM PATTERN TABLE




AUDIO BLOCK DIAGRAM TONSIGNAL BLOCKSCHEMA




POWER SUPPLY AND CONTROL BLOCK DIAGRAM

STROMVERSORGUNGS BLOCKSCHEMA




VIDEO BLOCK DIAGRAM BILDSIGNAL BLOCKSCHEMA



NOTE :

The numbers on the exploded view below refer to the miscellaneous section of the Replacement Parts List.



REPLACEMENT PARTS LIST

Important Safety Notice

Components identified by **▲** mark have special characteristics important for safety.
When replacing any of these components, use only manufacturer's specified parts.

Ref No.	Part No.	Description		
MISCELLANEOUS COMPONENTS				
1)	TSX8E0020	POWER CORD	▲	
2)	UR51EC780	BATTERY COVER (REMOTE)		
3)	EUR51920	REMOTE CONTROL		
4)	VP15005-35	SCREW		
5)	A51ECQ51X01	CRT	▲	
6)	TKY8E092	CABINET	▲	
7)	TBX8E030	POWER BUTTON		
8)	TBM8E1726	PANASONIC BADGE		
9)	TKP8E1138AD2	DOOR LID		
10)	TKP8E1139	SPEAKER NET		
11)	TMX8E010	CHASSIS BRACKET		
12)	EAGG1218D2	SPEAKER		
13)	TNP8EE008BJ	E P.C.B.	▲	
14)	TNP8EB007AB	B PCB	▲	
15)	TLK8E05117	DEGAUSS COIL		
16)	TNP117069AD	Y P.C.B.	▲	
17)	TKU8E00240	BACK COVER	▲	
18)	TBM8E1717	MODEL LABEL		
	TNP8EP013AB	P .P.C.B.	▲	
	TBM8E1605	RESET LABEL		
	31221212478	FIX CLIP		
	TES4537	SPRING		
	TEK6935	LID SWITCH		
	TKP8E1140	LED TUBE		
TNR1	ENG29501G	TUNER		
	TMW8E022	LED HOLDER		
S.351	0330550049	CRT SOCKET		
	TBM8E1535	A.V.LABEL		
	F9-4-220	RELAY		
	TPC8E4639	OUTER CARTON		
	TPD8E615	CUSHION-TOP		
	TPD8E616	CUSHION-BOTTOM		
	TQB8E2344A	GERMAN INST BOOK	▲	
	TQB8E2344B	DUTCH INST BOOK	▲	
	TQB8E2344C	ITALIAN INST BOOK	▲	
	TQB8E2344D	FRENCH INST BOOK	▲	
	TQB8E2344E	SPANISH INST BOOK	▲	
	TQB8E2344J	PORTUGUESE INST BOOK	▲	
	ERC12GK825	SOLID 0.5W 10% 8M2Ω		
	UM-3DJ-2P	BATTERY-SET		
CAPACITORS				
C100	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C101	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C102	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C103	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C104	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C107	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C124	ECEA1CKA470	ELECT	16V 47μF	
C130	ECEA1CKA470	ELECT	16V 47μF	
C135	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C136	ECA1CM100GB	ELECT	16V 10pF	
C137	ECA1EM101GB	ELECT	25V 1μF	
C138	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C139	ECUV1H390JCX	S.M.CAP	50V 39pF	
C140	ECUV1H390JCX	S.M.CAP	50V 39pF	
C141	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C144	ECA1HMR33GB	ELECT	50V 0.33μF	

Ref No.	Part No.	Description		
C145	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C146	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C147	ECUV1H102KBX	S.M.CAP	50V 1nF	
C148	ECEA1HKAR22	ELECT	50V 0.22μF	
C149	ECA1EM470GB	ELECT	25V 47pF	
C150	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C151	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C154	ECA1CM221GB	ELECT	16V 220pF	
C170	ECUV1H331KBX	S.M.CAP	50V 330pF	
C201	ECUV1H070DCX	S.M.CAP	50V 7pF	
C202	ECUV1H070DCX	S.M.CAP	50V 7pF	
C203	ECUV1H470JX	S.M.CAP	50V 47pF	
C204	ECUV1H560JCX	S.M.CAP	50V 56pF	
C205	ECUV1H560JCX	S.M.CAP	50V 56pF	
C207	ECUV1H560JCX	S.M.CAP	50V 56pF	
C209	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C210	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C211	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C251	ECA1EM100GB	ELECT	25V 0.1μF	
C252	ECUY1H563KBX	S.M.CAP	50V 56nF	
C253	ECA1HM4R7GB	ELECT	50V 4.7μF	
C254	ECQM1H104J	FILM	50V 100nF	
C255	ECEA1EGE101	ELECT	25V 100μF	
C256	ECUY1H563KBX	S.M.CAP	50V 56nF	
C257	ECA1HM4R7GB	ELECT	50V 4.7μF	
C258	ECA1EM100GB	ELECT	25V 0.1μF	
C259	ECQM1H104J	FILM	50V 100nF	
C260	ECA1VM102GE	ELECT	35V 1nF	
C261	ECA1VM102GE	ELECT	35V 1nF	
C262	ECQM1H474J	FILM	50V 470nF	
C263	ECA1HM010GB	ELECT	50V 1pF	
C264	ECEA1HGE222	ELECT	50V 2200μF	
C265	ECQM1H474J	FILM	50V 470nF	
C266	ECA1HM010GB	ELECT	50V 1pF	
C267	ECUV1H104KBX	S.M.CAP	50V 100nF	
C268	ECUV1H104KBX	S.M.CAP	50V 100nF	
C271	ECUV1H561KBX	S.M.CAP	50V 560pF	
C301	ECA1CM470GB	ELECT	16V 47μF	
C302	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C303	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C310	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C354	ECQM2104KZ	FILM	250V 100nF	
C355	ECUV1H222JCX	S.M.CAP	50V 2.2nF	
C356	ECUV1H222JCX	S.M.CAP	50V 2.2nF	
C357	ECUV1H222JCX	S.M.CAP	50V 2.2nF	
C358	222236516224	FILM	160V 220nF	
C360	ECKC3D152J	CERAMIC	2KV 1.5nF	▲
C361	ECA1HMR47GB	ELECT	50V 0.47μF	
C451	ECUV1H102JX	S.M.CAP	50V 1nF	
C452	ECUV1H102ZFX	S.M.CAP	50V 1nF	
C453	ECUV1H472KBX	S.M.CAP	50V 4.7nF	
C454	ECUV1H104ZFX	S.M.CAP	50V 100nF	
C455	ECA1VM222GE	ELECT	35V 2.2nF	
C456	ECEA1HGE221	ELECT	50V 220μF	
C457	ECUV1H103KBX	S.M.CAP	50V 10nF	
C458	ECQM1H273J	FILM	50V 27nF	
C459	222236516154	FILM	160V 150nF	
C460	222236516105	FILM	160V 1μF	
C462	ECEA1VGE332	ELECT	35V 3300μF	
C463	ECQB1H222J	FILM	50V 2200pF	
C501	ECA1AM330GB	ELECT	10V 33pF	
C506	ECUV1H103ZFX	S.M.CAP	50V 10nF	
C508	222236516105	FILM	160V 1μF	

Ref No.	Part No.	Description			
C509	ECEA1HGE101	ELECT	50V	100 μ F	
C510	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C511	ECQM2683JZ	FILM	250V	68nF	
C551	ECWH12H272J	CERAMIC	1250V	2.7nF	▲
C552	ECWH12H102J	FILM	1250V	1nF	▲
C555	ECWH12H103J	FILM	1250V	10nF	▲
C556	ECQF4273JZH	FILM	400V	0.027 μ F	
C559	ECWF2H474J	FILM	500V	470nF	▲
C562	ECKC2H101J	CERAMIC	500V	100pF	▲
C563	ECEA2EU220	ELECT	250V	22 μ F	
C564	ECEA2AU2R2	ELECT	100V	2.2 μ F	
C565	ECQP1H273J	FILM	100V	2700 μ F	
C601	ECUV1H271JCX	S.M.CAP	50V	270pF	
C602	ECUV1H121JCX	S.M.CAP	50V	120pF	
C603	ECUV1H471JCX	S.M.CAP	50V	470pF	
C604	ECA0JM102GB	ELECT	6.3V	1nF	
C605	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C608	ECUV1H683ZFX	S.M.CAP	50V	68nF	
C609	ECA1CM470GB	ELECT	16V	47 μ F	
C610	ECUV1H683ZFX	S.M.CAP	50V	68nF	
C611	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C612	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C613	ECUV1H102JCX	S.M.CAP	50V	1nF	
C614	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C615	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C616	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C618	ECUV1H473ZFX	S.M.CAP	50V	47nF	
C619	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C620	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C621	ECA1CM100GB	ELECT	16V	10pF	
C622	ECA1CM100GB	ELECT	16V	10pF	
C623	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C624	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C625	ECEA1HNR22	ELECT	50V	0.22 μ F	
C626	ECA0JM102GB	ELECT	6.3V	1nF	
C627	ECUV1H100DCX	S.M.CAP	50V	10pF	
C628	ECUV1H470JCX	S.M.CAP	50V	47pF	
C629	ECUV1H101JCX	S.M.CAP	50V	100pF	
C630	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C631	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C632	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C633	ECUV1H102JCX	S.M.CAP	50V	1nF	
C636	ECUV1H101JCX	S.M.CAP	50V	100pF	
C637	ECUV1H102KBX	S.M.CAP	50V	1nF	
C638	ECUV1H181JCX	S.M.CAP	50V	180pF	
C639	ECUV1H561KBX	S.M.CAP	50V	560pF	
C701	ECEA1HU101	ELECT	50V	100 μ F	
C702	ECUV1H103KBX	S.M.CAP	50V	10nF	
C703	ECA1HM100GB	ELECT	50V	10pF	
C704	ECQB1H223K	FILM	50V	22nF	
C705	ECQB1H152K	FILM	50V	1.5nF	
C801	ECUV1H101JCX	S.M.CAP	50V	100pF	
C802	ECQE6104K	FILM	600V	100nF	▲
C803	ECUV1H560JX	S.M.CAP	50V	56pF	
C804	ECA1HM101GB	ELECT	50V	100pF	
C805	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C806	ECEA1HU101	ELECT	50V	100 μ F	
C807	ECEA1EGE101	ELECT	25V	100 μ F	
C808	ECQB1H103J	FILM	50V	10nF	
C809	ECQB1H103J	FILM	50V	10nF	
C811	ECEA1HN010	ELECT	50V	1 μ F	
C815	ECKC2H472J	CERAMIC	500V	4.7nF	▲
C816	ECKC3D222JB	CERAMIC	2KV	2200pF	▲
C817	ECQB1H223K	FILM	50V	22nF	
C818	ECKC2H472J	CERAMIC	500V	4.7nF	▲
C820	ECOS2GA151CB	ELECT	400V	150pF	
C821	ECKWNA332MECCERAMIC	250V	3.3nF		
C841	222233510224	CAPACITOR	0.22 μ F		
C851	ECKC2H681J	CERAMIC	500V	680pF	▲
C852	ECEA1HU102	ELECT	50V	1000 μ F	
C853	ECEA1EGE222	ELECT	25V	2200 μ F	
C854	ECEA1HGE102	ELECT	50V	1000 μ F	

Ref No.	Part No.	Description			
C855	ECKC3D471JB	CERAMIC	2KV	470pF	▲
C856	ECEA1EGE222	ELECT	25V	2200 μ F	
C857	ECA2CM101E	ELECT	160V	100 μ F	
C858	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C859	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C860	ECA1CM471GB	ELECT	16V	470pF	
C861	ECA2CGE221	ELECT	160V	220 μ F	
C862	ECA1CM471GB	ELECT	16V	470pF	
C1051	ECA0JM101G	ELECT	6.3V	100pF	
C1052	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C1201	ECUV1H332KBX	S.M.CAP	50V	3.3nF	
C1202	ECUV1H332KBX	S.M.CAP	50V	3.3nF	
C1203	ECUV1H332KBX	S.M.CAP	50V	3.3nF	
C1204	ECUV1H332KBX	S.M.CAP	50V	3.3nF	
C1205	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C1206	ECA1HM4R7GB	ELECT	50V	4.7 μ F	
C1207	ECUV1H472KBX	S.M.CAP	50V	4.7nF	
C1208	ECUV1H390JCX	S.M.CAP	50V	39pF	
C1209	ECUV1H390JCX	S.M.CAP	50V	39pF	
C1210	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C1211	ECUV1H470JCX	S.M.CAP	50V	47pF	
C1212	ECA1CM470GB	ELECT	16V	47 μ F	
C1213	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C1214	ECA1CM470GB	ELECT	16V	47 μ F	
C1215	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C1217	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C1219	ECA1CM471GB	ELECT	16V	470pF	
C1220	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C1221	ECA0JM102GB	ELECT	6.3V	1nF	
C1222	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C1223	ECA1HM101GB	ELECT	50V	100pF	
C1224	ECA0JM222GB	ELECT	6.3V	2.2nF	
C1225	ECA0JM472GE	ELECT	6.3V	4.7nF	
C1226	ECA1HM101GB	ELECT	50V	100pF	
C1227	ECA1VM221B	ELECT	35V	220pF	
C1228	ECA1EM101GB	ELECT	25V	1 μ F	
C2101	ECUV1H223KBX	S.M.CAP	50V	22nF	
C2102	ECUV1H391KBX	S.M.CAP	50V	390pF	
C2103	ECUV1H102KBX	S.M.CAP	50V	1nF	
C2104	ECUV1H102KBX	S.M.CAP	50V	1nF	
C2107	ECUV1H391KBX	S.M.CAP	50V	390pF	
C2108	ECA1HM101GB	ELECT	50V	100pF	
C2109	ECUV1H223KBX	S.M.CAP	50V	22nF	
C2110	ECA1CM100GB	ELECT	16V	10pF	
C2111	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C2112	ECA1CM100GB	ELECT	16V	10pF	
C2113	ECUV1H102KBX	S.M.CAP	50V	1nF	
C2114	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C2115	ECUV1H471KBX	S.M.CAP	50V	470pF	
C2116	ECA1HM3R3GB	ELECT	50V	3.3 μ F	
C2117	ECUV1H471KBX	S.M.CAP	50V	470pF	
C2118	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C2119	ECA1CM100GB	ELECT	16V	10pF	
C220	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C221	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C223	ECA1CM100GB	ELECT	16V	10pF	
C224	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C225	ECUV1H010CCX	S.M.CAP	50V	1pF	
C226	ECUV1H010CCX	S.M.CAP	50V	1pF	
C227	ECA1CM100GB	ELECT	16V	10pF	
C228	ECUV1H683ZFX	S.M.CAP	50V	68nF	
C229	ECQM1H334J	FILM	50V	330nF	
C2307	ECA1CM470GB	ELECT	16V	47 μ F	
C2308	ECA1CM470GB	ELECT	16V	47 μ F	
C2310	ECA1CM470GB	ELECT	16V	47 μ F	
C2312	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C2313	ECUV1H103KBX	S.M.CAP	50V	10nF	
C2314	ECUV1H104ZFX	S.M.CAP	50V	100nF	
C2315	ECUV1H103KBX	S.M.CAP	50V	10nF	
C2316	ECUV1H103ZFX	S.M.CAP	50V	10nF	
C2317	ECA1CM470GB	ELECT	16V	47 μ F	
C2318	ECUV1H222KBX	S.M.CAP	50V	2.2nF	

Ref No.	Part No.	Description				
C2319	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C2651	ECUV1H103KBX	S.M.CAP	50V	10nF		
C2652	ECUV1H103KBX	S.M.CAP	50V	10nF		
C3001	ECA1HMR47GB	ELECT	50V	0.47μF		
C3002	ECA1HMR47GB	ELECT	50V	0.47μF		
C3003	ECA1EM4R7GB	ELECT	25V	4.7μF		
C3004	ECA1HM4R7GB	ELECT	50V	4.7μF		
C3005	ECA1HM4R7GB	ELECT	50V	4.7μF		
C3006	ECUV1H473ZFX	S.M.CAP	50V	47nF		
C3007	ECA1HM470GB	ELECT	50V	47μF		
C3011	ECUV1H473ZFX	S.M.CAP	50V	47nF		
C3012	ECA1CM470GB	ELECT	16V	47μF		
C3013	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3014	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3017	ECEA1CN470	ELECT	16V	47μF		
C3018	ECUV1H102KBX	S.M.CAP	50V	1nF		
C3019	ECUV1H102KBX	S.M.CAP	50V	1nF		
C3020	ECCR1H120J	CERAMIC	50V	12pF		
C3021	ECUV1H102KBX	S.M.CAP	50V	1nF		
C3023	ECA1CM470GB	ELECT	16V	47μF		
C3024	ECUV1H473ZFX	S.M.CAP	50V	47nF		
C3025	ECUV1H102KBX	S.M.CAP	50V	1nF		
C3026	ECA1CM470GB	ELECT	16V	47μF		
C3027	ECA1CM470GB	ELECT	16V	47μF		
C3028	ECUV1H221JX	S.M.CAP	50V	220pF		
C3029	ECUV1H221JX	S.M.CAP	50V	220pF		
C3030	ECUV1H221JX	S.M.CAP	50V	220pF		
C3031	ECUV1H221JX	S.M.CAP	50V	220pF		
C3032	ECA1HMR47GB	ELECT	50V	0.47μF		
C3033	ECA1HMR47GB	ELECT	50V	0.47μF		
C3034	ECUV1H221JX	S.M.CAP	50V	220pF		
C3035	ECUV1H221JX	S.M.CAP	50V	220pF		
C3036	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3037	ECUV1H561JCX	S.M.CAP	50V	560pF		
C3038	ECA1CM470GB	ELECT	16V	47μF		
C3039	ECA1CM470GB	ELECT	16V	47μF		
C3040	ECA1HMR47GB	ELECT	50V	0.47μF		
C3041	ECA1HMR47GB	ELECT	50V	0.47μF		
C3043	ECA1HM4R7GB	ELECT	50V	4.7μF		
C3045	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3049	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3050	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3051	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3052	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3053	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3054	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3055	ECUV1H222KBX	S.M.CAP	50V	2.2nF		
C3056	ECUV1H101JCX	S.M.CAP	50V	100pF		
C3062	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3071	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3151	ECUV1H561JCX	S.M.CAP	50V	560pF		
C3152	ECUV1H561JCX	S.M.CAP	50V	560pF		
C3501	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3502	ECA1HM101GB	ELECT	50V	100pF		
C3503	ECUV1H103ZFX	S.M.CAP	50V	10nF		
C3504	ECUV1H102JCX	S.M.CAP	50V	1nF		
C3505	ECUV1H104ZFX	S.M.CAP	50V	100nF		
C3506	ECA1CM470GB	ELECT	16V	47μF		
C3507	ECA1CM470GB	ELECT	16V	47μF		
C3508	ECUV1H473ZFX	S.M.CAP	50V	47nF		
C3509	ECUV1H103ZFX	S.M.CAP	50V	10nF		
C3510	ECA0JM102GB	ELECT	6.3V	1nF		
C3511	ECUV1H103ZFX	S.M.CAP	50V	10nF		

DIODES

D140	MA3020TX	DIODE
D141	MA3020TX	DIODE
D251	MA2180TP	DIODE
D253	RB721Q40T77	DIODE
D254	RB721Q40T77	DIODE
D310	MA165TA5	DIODE 1SS133T-77

Ref No.	Part No.	Description				
D311	MA29TA5	DIODE				
D312	MA29TA5	DIODE				
D354	ERA22-04V1	DIODE				
D355	ERA22-04V1	DIODE				
D356	ERA22-04V1	DIODE				
D357	MA165TA5	DIODE 1SS133T-77				
D358	MA165TA5	DIODE 1SS133T-77				
D359	MA165TA5	DIODE 1SS133T-77				
D360	MA4150	DIODE				
D451	MA165TA5	DIODE 1SS133T-77				
D452	MA165TA5	DIODE 1SS133T-77				
D454	ERA15-02V3	DIODE				
D456	MA2160BLFS	DIODE				
D470	MA4020	DIODE				
D501	MA165TA5	DIODE 1SS133T-77				
D502	EU02	DIODE				
D551	ERD07-15L7	DIODE				
D552	TVSRU2AM	DIODE				
D554	AU02V0	DIODE				
D556	MA165TA5	DIODE 1SS133T-77				
D601	MA165TA5	DIODE 1SS133T-77				
D602	MA165TA5	DIODE 1SS133T-77				
D604	MA165TA5	DIODE 1SS133T-77				
D605	MA165TA5	DIODE 1SS133T-77				
D606	MA165TA5	DIODE 1SS133T-77				
D609	MA165TA5	DIODE 1SS133T-77				
D701	MA165TA5	DIODE 1SS133T-77				
D702	MTZJT-775.6C	DIODE				
D804	ERA15-02V3	DIODE				
D805	EU02	DIODE				
D806	RBV4-08	DIODE				
D807	EU02	DIODE				
D809	MA165TA5	DIODE 1SS133T-77				
D814	MA165TA5	DIODE 1SS133T-77				
D851	EU02	DIODE				
D852	ERD32-02L7	DIODE				
D853	FML22SLF610	DIODE				
D854	RU4AMLF-M1	DIODE				
D855	RU4BLF-L1	DIODE				
D856	MTZJT-775.1A	DIODE				
D857	MTZJ33B	DIODE				
D858	MA29TA5	DIODE				
D1201	SLR56UR3FLF	LED				
D1203	MA170	DIODE				
D1205	MA165TA5	DIODE 1SS133T-77				
D1207	MA165TA5	DIODE 1SS133T-77				
D1208	MA165TA5	DIODE 1SS133T-77				
D1209	MA165TA5	DIODE 1SS133T-77				
D1211	MTZJT-775.1C	DIODE				
D1212	MA170	DIODE				
D1213	MA165TA5	DIODE 1SS133T-77				
D1214	MA170	DIODE				
D1216	MTZJT-778.2C	DIODE				
D2303	MA165TA5	DIODE 1SS133T-77				
D2304	MTZJT-779.1C	DIODE				
D3001	MTZJT-7712C	DIODE				
D3003	MTZJT-778.2C	DIODE				
D3004	MA4100	DIODE				
D3005	MTZJT-7712C	DIODE				
D3006	MTZJT-7712C	DIODE				
D3007	MTZJT-7712C	DIODE				
D3008	MTZJT-778.2C	DIODE				
D3009	MTZJT-778.2C	DIODE				
D3010	MTZJT-778.2C	DIODE				
D3011	MTZJT-778.2C	DIODE				
D3012	MTZJT-7712C	DIODE				
D3013	MTZJT-7712C	DIODE				
D3014	MTZJT-7712C	DIODE				
D3015	MTZJT-7712C	DIODE				
D3016	MTZJT-7712C	DIODE				
D3018	MA165TA5	DIODE 1SS133T-77				

Ref No.	Part No.	Description				
D3019	MA165TA5	DIODE 1SS133T-77				
D3501	MA165TA5	DIODE 1SS133T-77				
FUSES						
F840	2153.15H	FUSE	▲			
F851	TR5-T1250	FUSE	▲			
F852	TR5-T2000	FUSE	▲			
F853	TR5-T2000	FUSE	▲			
F8401	EYF52BC	FUSE HOLDER				
F8402	EYF52BC	FUSE HOLDER				
SOCKETS						
H1202	832AG11D-ESL	I.C.SOCKET				
INTEGRATED CIRCUITS						
IC100	TSA5514AT/C2	A.F.C.CONTROL				
IC103	L78M09MRB	9V REGULATOR				
IC1051	RPM-637CBRL	LED RECEIVER				
IC1201	CCU3000I-07	MICRO-PROCESSOR				
IC1202	27C010-006AE	EPROM				
IC1203	X24LM0401EY	EAROM				
IC1205	MN1280R	RESET				
IC2101	MSP3410BPPF7	AUDIO PROCESSOR				
IC2301	AN78L08TA	8V REGULATOR				
IC251	LA4280-TV	AUDIO OUTPUT				
IC3001	TEA6415C	VIDEO SWITCH				
IC3501	UD61256DC-08	DYNAMIC RAM				
IC3502	TPU3040-20	TEXT PROCESSOR				
IC351	TDA6103Q-N3	R.G.B.AMPLIFIER				
IC451	LA7845N	VERTICAL OUTPUT				
IC601	VDP3108APPA1	VIDEO PROCESSOR				
IC701	TEA2031A	HORIZONTAL OUTPUT				
IC801	TDA4601	POWER SUPPLY				
IC851	L78M12MRB	12V REGULATOR				
TERMINALS AND LINKS						
JA.1	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.10	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.11	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.12	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.13	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.14	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.15	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.16	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.17	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.18	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.19	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.2	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.20	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.21	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.22	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.24	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.25	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.26	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.27	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.28	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.29	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.3	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.30	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.4	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.5	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.6	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.7	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA.8	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA.9	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JA33	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA34	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		

Ref No.	Part No.	Description				
JA35	ERJ8GEY0R00	S.M.CAR .125W	5%	0Ω		
JA36	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB1	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB10	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB11	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB12	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB13	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB14	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB15	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB16	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB17	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB18	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB19	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB2	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB20	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB21	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB22	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB23	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB24	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB25	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB26	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB27	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB28	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB29	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB3	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB30	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB31	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB32	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB33	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB34	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB35	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB36	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB37	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB38	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB39	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB40	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB41	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB42	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB43	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB44	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB45	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB46	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB47	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB48	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB49	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB50	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB51	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB52	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB53	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB54	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB55	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB56	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB57	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB58	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB59	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB6	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB61	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB62	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB63	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB64	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB65	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB66	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB67	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB68	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB69	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB7	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB70	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB71	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB72	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB73	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB74	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		
JB75	ERJ6GEY0R00	S.M.CARB 0.1W	5%	0Ω		

Ref No.	Part No.	Description				
JB77	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JB79	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JB8	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JB80	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JB81	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JB9	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JK2301	TJB18644	AV TERMINAL				
JK3001	TJS8E007	21PIN TERMINAL				
JK3101	TJS8E007	21PIN TERMINAL				
JK3102	TJB16673	AV TERMINAL				
JSB1	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSB12	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSB13	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSB14	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSB2	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSB4	EXCELSA35T	COIL				
JSE011	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE012	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE013	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE014	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE015	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE016	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE031	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE032	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE035	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
JSE037	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
J104	EXCELSA35T	COIL				
J106	EXCELSA35T	COIL				
J107	EXCELSA35T	COIL				
J169	EXCELSA35T	COIL				
COILS						
L001	TLT100K991R	COIL				
L003	EXCELSA35T	COIL				
L100	TLT181K991R	COIL				
L111	TLT101K991R	COIL				
L112	EXCELSA35T	COIL				
L113	EXCELSA35T	COIL				
L130	ELESN8R2KA	COIL				
L132	ELESN8R2KA	COIL				
L202	TLT068K991R	COIL				
L251	EXCELSA35T	COIL				
L301	TLT047K991R	COIL				
L302	EXCEMT101BT	COIL				
L303	EXCEMT101BT	COIL				
L304	EXCEMT101BT	COIL				
L552	ELH5L429	COIL				
L601	TLT047K991R	COIL				
L602	EXCELDR35V	COIL				
L603	TLT047K991R	COIL				
L604	EXCELDR35V	COIL				
L606	TLT015K991R	COIL				
L607	EXCELSA35T	COIL				
L701	ELC10D006	COIL				
L801	EXCELSA24T	COIL				
L802	TLT022K991R	COIL				
L804	ELESN4R7KA	COIL				
L805	298-82858002	COIL				
L841	ELF18D490F	COIL				
L851	EXCELDR35V	COIL				
L852	EXCELSA35T	COIL				
L853	ELEIE470KA	COIL				
L854	ELEIN470KA	COIL				
L855	ELEIN470KA	COIL				
L856	ELEIN470KA	COIL				
L1051	TLT331K991R	COIL				
L1201	TLT047K991R	COIL				
L1202	TLT047K991R	COIL				
L1203	TLT047K991R	COIL				
L1204	EXCELDR35V	COIL				
L2101	TLT100K991R	COIL				

Ref No.	Part No.	Description				
L2102	TLT039K991R	COIL				
L2103	EXCELSA35T	COIL				
L2104	EXCELSA35T	COIL				
L3151	EXCEMT101BT	COIL				
L3152	EXCEMT101BT	COIL				
L3153	EXCEMT101BT	COIL				
L3154	EXCEMT101BT	COIL				
L3155	ELEBT6R8KA	COIL				
L3156	ELEBT6R8KA	COIL				
L3158	EXCELSA39V	COIL				
L3501	EXCELDR35V	COIL				
L3502	EXCELDR35V	COIL				
L3503	ELESN4R7KA	COIL				
L3504	EXCELSA35T	COIL				
TRANSISTORS						
Q201	BC847B	TRANSISTOR OR 2SD601ATX				
Q202	BC847B	TRANSISTOR OR 2SD601ATX				
Q251	2SD1328STX	TRANSISTOR				
Q252	2SD1328STX	TRANSISTOR				
Q301	BC857B	TRANSISTOR OR 2SB709ATX				
Q302	BC847B	TRANSISTOR OR 2SD601ATX				
Q303	BC857B	TRANSISTOR OR 2SB709ATX				
Q304	BC847B	TRANSISTOR OR 2SD601ATX				
Q305	BC857B	TRANSISTOR OR 2SB709ATX				
Q306	BC847B	TRANSISTOR OR 2SD601ATX				
Q307	BC847B	TRANSISTOR OR 2SD601ATX				
Q308	BC847B	TRANSISTOR OR 2SD601ATX				
Q309	BC847B	TRANSISTOR OR 2SD601ATX				
Q310	BC847B	TRANSISTOR OR 2SD601ATX				
Q311	BC847B	TRANSISTOR OR 2SD601ATX				
Q351	2SA1767	TRANSISTOR				
Q352	2SA1767	TRANSISTOR				
Q353	2SA1767	TRANSISTOR				
Q451	BC847B	TRANSISTOR OR 2SD601ATX				
Q501	BC847B	TRANSISTOR OR 2SD601ATX				
Q502	BC847B	TRANSISTOR OR 2SD601ATX				
Q503	2SD836-AL	TRANSISTOR				
Q504	BC847B	TRANSISTOR OR 2SD601ATX				
Q551	BU2506DXLB	TRANSISTOR				
Q552	2SC1473-RN	TRANSISTOR				
Q701	BC857B	TRANSISTOR OR 2SB709ATX				
Q802	S2000NLBMA	TRANSISTOR				
Q851	2SD1273PLB	TRANSISTOR ALT 2SD2396/JM3				
Q852	TFD312SOF632	DIODE				
Q1202	BC847B	TRANSISTOR OR 2SD601ATX				
Q1205	BC847B	TRANSISTOR OR 2SD601ATX				
Q1206	BC847B	TRANSISTOR OR 2SD601ATX				
Q1207	BC847B	TRANSISTOR OR 2SD601ATX				
Q1208	BC857B	TRANSISTOR OR 2SB709ATX				
Q1211	BC547B	TRANSISTOR				
Q1212	BC847B	TRANSISTOR OR 2SD601ATX				
Q1213	BC847B	TRANSISTOR OR 2SD601ATX				
Q2101	BC860B	TRANSISTOR				
Q2102	BC860B	TRANSISTOR				
Q2301	BC857B	TRANSISTOR OR 2SB709ATX				
Q2302	BC857B	TRANSISTOR OR 2SB709ATX				
Q2305	2SD1328STX	TRANSISTOR				
Q2306	2SD1328STX	TRANSISTOR				
Q2307	BC860B	TRANSISTOR				
Q2308	BC857B	TRANSISTOR OR 2SB709ATX				
Q2309	BC860B	TRANSISTOR				
Q2310	BC860B	TRANSISTOR				
Q3001	2SC1318-S	TRANSISTOR				
Q3004	BC847B	TRANSISTOR OR 2SD601ATX				
Q3005	BC847B	TRANSISTOR OR 2SD601ATX				
Q3006	2SC1318-S	TRANSISTOR				
Q3011	BC857B	TRANSISTOR OR 2SB709ATX				
Q3012	2SD1328STX	TRANSISTOR				
Q3013	2SD1328STX	TRANSISTOR				

Ref No.	Part No.	Description				
RESISTOR						
RL1201	TSE1885-1	TRANSISTOR				
R.604	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R.622	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R100	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R101	ERJ6GEYJ331	S.M.CARB	0.1W	5%	330Ω	
R102	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R103	ERJ6GEYJ331	S.M.CARB	0.1W	5%	330Ω	
R107	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R109	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R112	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R114	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ	
R117	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R130	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R131	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R132	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ	
R133	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R134	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R136	ERJ6GEYJ393	S.M.CARB	0.1W	5%	39KΩ	
R138	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R201	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R203	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R204	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ	
R205	ERJ6GEYJ391	S.M.CARB	0.1W	5%	390Ω	
R206	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω	
R207	ERJ6GEYJ123	S.M.CARB	0.1W	5%	12KΩ	
R208	ERJ6GEYJ182	S.M.CARB	0.1W	5%	1K8Ω	
R210	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R251	ERJ6GEYJ181	S.M.CARB	0.1W	5%	180Ω	
R252	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω	
R253	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R254	ERJ6GEYJ181	S.M.CARB	0.1W	5%	180Ω	
R255	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R256	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R257	ERJ6GEYJ560	S.M.CARB	0.1W	5%	56Ω	
R258	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω	
R259	ERJ6GEYJ560	S.M.CARB	0.1W	5%	56Ω	
R260	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R261	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R262	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R265	ERD25TJ2R2	CARBON	0.25W	5%	2R2Ω	
R266	ERD25TJ2R2	CARBON	0.25W	5%	2R2Ω	
R267	ERF7ZK4R7	WOUND	7W	10%	4R7Ω	▲
R271	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R272	ERF7ZK5R6	WOUND	7W	10%	5R6Ω	▲
R273	ERD25TJ273	CARBON	0.25W	5%	27KΩ	
R301	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω	
R302	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R303	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R304	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R305	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω	
R306	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R307	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R308	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R309	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω	
R310	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R311	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R312	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω	
R313	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R314	ERJ6GEYJ332	S.M.CARB	0.1W	5%	3K3Ω	
R315	ERJ6GEYJ332	S.M.CARB	0.1W	5%	3K3Ω	
R316	ERJ6GEYJ332	S.M.CARB	0.1W	5%	3K3Ω	
R321	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ	
R322	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ	
R323	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R324	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ	
R351	ERJ6GEYJ182	S.M.CARB	0.1W	5%	1K8Ω	
R352	ERJ6GEYJ182	S.M.CARB	0.1W	5%	1K8Ω	
R353	ERJ6GEYJ182	S.M.CARB	0.1W	5%	1K8Ω	
R354	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ	
R355	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ	

Ref No.	Part No.	Description				
RESISTOR						
R356	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ	
R357	ERG1FJ563	METAL	1W	5%	56KΩ	▲
R358	ERG2FJ563	METAL	2W	5%	56KΩ	▲
R359	ERG1FJ563	METAL	1W	5%	56KΩ	▲
R363	ERDS1TJ103	CARBON	0.5W	5%	10KΩ	
R364	ERDS1TJ103	CARBON	0.5W	5%	10KΩ	
R365	ERDS1TJ103	CARBON	0.5W	5%	10KΩ	
R366	ERDS1TJ222	CARBON	0.5W	5%	2K2Ω	
R367	ERDS1TJ222	CARBON	0.5W	5%	2K2Ω	
R368	ERDS1TJ222	CARBON	0.5W	5%	2K2Ω	
R369	ERD25TJ223	CARBON	0.25W	5%	22KΩ	
R370	ERD25TJ103	CARBON	0.25W	5%	10KΩ	
R372	ERQ12AJ121	FUSIBLE	0.5W	5%	120Ω	▲
R373	ERJ6GEYJ220	S.M.CARB	0.1W	5%	22Ω	
R374	ERDS1TJ274	CARBON	0.5W	5%	270KΩ	
R375	ERJ6GEYJ684	S.M.CARB	0.1W	5%	680KΩ	
R376	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ	
R377	ERQ12HJ1R2	METAL	0.5W	5%	1R2Ω	▲
R378	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R379	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R380	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω	
R451	ERJ6GEYJ273	S.M.CARB	0.1W	5%	27KΩ	
R452	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω	
R453	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ	
R455	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω	
R456	ERJ6GEYJ123	S.M.CARB	0.1W	5%	12KΩ	
R457	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R458	ERD25TJ1R5	CARBON	0.25W	5%	1R5Ω	
R459	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω	
R460	ERJ6GEYJ513	S.M.CARB	0.1W	5%	51KΩ	
R461	ERDS1TJ471	CARBON	0.5W	5%	470Ω	
R462	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω	
R463	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω	
R464	ERW12PK1R5	WIRE	12W	10%	1R5Ω	
R465	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R466	ERO25CKF1801	METAL	0.25W	1%	1K8Ω	▲
R467	ERO25CKF1201	METAL	0.25W	1%	1K2Ω	▲
R470	ERD25TJ512	CARBON	0.25W	5%	5K1Ω	
R471	ERDS1TJ152	CARBON	0.5W	5%	1K5Ω	
R472	ERDS1TJ4R7	CARBON	0.5W	5%	4R7Ω	
R501	ERJ6GEYJ331	S.M.CARB	0.1W	5%	330Ω	
R502	ERJ6GEYJ560	S.M.CARB	0.1W	5%	56Ω	
R503	ERJ6GEYJ273	S.M.CARB	0.1W	5%	27KΩ	
R504	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R506	ERD25TJ560	CARBON	0.25W	5%	56Ω	
R507	ERQ14AJW3R3	FUSABLE	0.25W	5%	3R3Ω	▲
R509	ERDS1TJ152	CARBON	0.5W	5%	1K5Ω	
R510	ERDS1TJ152	CARBON	0.5W	5%	1K5Ω	
R511	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ	
R512	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω	
R513	ERJ6GEYJ123	S.M.CARB	0.1W	5%	12KΩ	
R514	ERJ6GEYJ123	S.M.CARB	0.1W	5%	12KΩ	
R551	ERW2PKR47	WIREWOUND2W		10%	0R47Ω	▲
R553	ERG1SJ152	METAL	1W	5%	1K5Ω	
R558	ERDS1TJ124	CARBON	0.5W	5%	120KΩ	
R561	ERJ6GEYJ563	S.M.CARB	0.1W	5%	56KΩ	
R562	ERJ6GEYJ225	SM.CARB0.125W		5%	2.2MΩ	
R563	ERJ6GEYJ225	SM.CARB0.125W		5%	2.2MΩ	
R564	ERJ6GEYJ623	SM.CARB0.125W		5%	62KΩ	
R566	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ	
R567	ERJ6GEYJ274	S.M.CARB	0.1W	5%	270KΩ	
R601	ERJ6GEYJ151	S.M.CARB	0.1W	5%	150Ω	
R602	ERJ6GEYJ151	S.M.CARB	0.1W	5%	150Ω	
R603	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω	
R605	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ	
R606	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω	
R607	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ	
R608	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R609	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω	
R610	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ	
R611	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ	
R612	ERJ6GEYJ123	S.M.CARB	0.1W	5%	12KΩ	

Ref No.	Part No.	Description			
R613	ERJ6GEYJ271	S.M.CARB	0.1W	5%	270Ω
R614	ERJ6GEYJ470	S.M.CARB	0.1W	5%	47Ω
R615	ERJ6GEYJ333	S.M.CARB	0.1W	5%	33KΩ
R616	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ
R618	ERJ6GEYJ151	S.M.CARB	0.1W	5%	150Ω
R619	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R623	ERJ6GEYJ821	S.M.CARB	0.1W	5%	820Ω
R701	ERQ12AJ101	FUSIBLE	0.5W	5%	100Ω ▲
R702	ERQ12HJ330	METAL	0.5W	5%	33Ω ▲
R703	ERG2FJ821	METAL	2W	5%	820Ω ▲
R704	ERJ6GEYJ563	S.M.CARB	0.1W	5%	56KΩ
R705	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R706	ERJ6GEYJ272	S.M.CARB	0.1W	5%	2K7Ω
R707	ERJ6GEYJ122	S.M.CARB	0.1W	5%	1K2Ω
R708	ERJ6GEYJ393	S.M.CARB	0.1W	5%	39KΩ
R709	ERJ6GEYJ393	S.M.CARB	0.1W	5%	39KΩ
R710	ERJ6GEYJ273	S.M.CARB	0.1W	5%	27KΩ
R711	ERJ6GEYJ681	S.M.CARB	0.1W	5%	680Ω
R712	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R713	ERG1SJ101	METAL	1W	5%	100Ω
R801	ERG3FJ682H	METAL	3W	5%	6K8Ω ▲
R802	ERG2FJ472	METAL	2W	5%	4K7Ω ▲
R803	ERX12SJWR47	METAL	12W	5%	R47
R804	ERJ6GEYJ682	S.M.CARB	0.1W	5%	6K8Ω
R805	ERJ6GEYJ221	S.M.CARB	0.1W	5%	220Ω
R807	ERO25CKF1201	METAL	0.25W	1%	1K2Ω ▲
R808	232266296319	THERMISTOR			
R809	ERO25CKF1302	METAL	0.25W	1%	13KΩ ▲
R810	ERD25TJ103	CARBON	0.25W	5%	10KΩ
R811	EVMEA00B33	CONTROL	3KΩ		
R812	ERDS1TJ220	CARBON	0.5W	5%	22Ω
R813	ERD50FJ274	CARBON	0.5W	5%	270KΩ
R814	ERF7ZK2R7	WOUND	7W	20%	2R7Ω ▲
R815	ERDS1TJ563	CARBON	0.5W	5%	56KΩ
R817	ERG3FJ470	METAL	3W	5%	47Ω ▲
R818	ERD50FJ104	CARBON	0.5W	5%	100KΩ
R819	ERD50FJ184	CARBON	0.5W	5%	180KΩ
R820	ERD75TAJ825	CARBON	0.75W	5%	8M2Ω ▲
R841	ERC12ZGK335D	SOLID	0.5W	10%	3M3Ω
R852	ERJ6GEYJ271	S.M.CARB	0.1W	5%	270Ω
R853	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R854	ERDS1TJ474	CARBON	0.5W	5%	470KΩ
R855	ERG2FJ223	METAL	2W	5%	22KΩ ▲
R856	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ
R857	ERG2SJS100H	METAL	2W	2%	10Ω ▲
R1201	ERJ6GEYJ271	S.M.CARB	0.1W	5%	270Ω
R1202	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1203	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1204	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1205	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1206	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1208	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ
R1209	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1210	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1212	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1213	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1214	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1215	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1216	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1217	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1218	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1219	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1220	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1221	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1222	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1224	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1225	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1226	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1227	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1229	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R1230	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R1231	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω

Ref No.	Part No.	Description			
R1232	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1233	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1235	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1236	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1237	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1238	ERJ6GEYJ393	S.M.CARB	0.1W	5%	39KΩ
R1239	ERJ6GEYJ392	S.M.CARB	0.1W	5%	3K9Ω
R1240	ERJ6GEYJ392	S.M.CARB	0.1W	5%	3K9Ω
R1241	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1242	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1244	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R1245	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R1246	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1247	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1249	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1250	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1251	ERJ6GEYJ393	S.M.CARB	0.1W	5%	39KΩ
R1252	ERX1SJ3R3	METAL	1W	5%	3R3Ω
R1253	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R1254	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R1255	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R1256	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ
R1257	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R1258	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
R1260	ERDS1FJ121	CARBON	0.5W	5%	120Ω ▲
R1261	ERJ6GEYJ392	S.M.CARB	0.1W	5%	3K9Ω
R1262	ERJ6GEYJ682	S.M.CARB	0.1W	5%	6K8Ω
R1263	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ
R1264	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R1265	ERJ6GEYJ152	S.M.CARB	0.1W	5%	1K5Ω
R1266	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ
R1277	ERDS1TJ151	CARBON	0.5W	5%	150Ω
R2101	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2102	ERJ6GEYJ561	S.M.CARB	0.1W	5%	560Ω
R2103	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2104	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2105	ERJ6GEYJ561	S.M.CARB	0.1W	5%	560Ω
R2106	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ
R2107	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2108	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2109	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2110	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R2111	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ
R2301	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R2302	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R2303	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2304	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2313	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2314	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R2315	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ
R2316	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R2318	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R2321	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R2322	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2323	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R2324	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2325	ERJ6GEYJ273	S.M.CARB	0.1W	5%	27KΩ
R2326	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2327	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2328	ERJ6GEYJ473	S.M.CARB	0.1W	5%	47KΩ
R2329	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R2330	ERJ6GEYJ222	S.M.CARB	0.1W	5%	2K2Ω
R2331	ERJ6GEYJ223	S.M.CARB	0.1W	5%	22KΩ
R2332	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2333	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R2334	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R2335	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R2651	ERG2FJ221	METAL	2W	5%	220Ω ▲
R2652	ERG2FJ221	METAL	2W	5%	220Ω ▲
R2653	ERDS1TJ151	CARBON	0.5W	5%	150Ω
R2654	ERDS1TJ151	CARBON	0.5W	5%	150Ω
R3001	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ

Ref No.	Part No.	Description			
R3002	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3003	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3004	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ
R3005	ERJ6GEYJ470	S.M.CARB	0.1W	5%	47Ω
R3006	ERJ6GEYJ470	S.M.CARB	0.1W	5%	47Ω
R3007	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3008	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R3009	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R3010	ERJ6GEYJ561	S.M.CARB	0.1W	5%	560Ω
R3011	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3012	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3013	ERJ6GEYJ561	S.M.CARB	0.1W	5%	560Ω
R3014	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R3015	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R3016	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3017	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ
R3019	ERJ6GEYJ471	S.M.CARB	0.1W	5%	47Ω
R3020	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3022	ERD2FCG560	CARBON	2W	2%	56Ω
R3024	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R3025	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3026	ERJ6GEYJ471	S.M.CARB	0.1W	5%	47Ω
R3027	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω
R3029	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω
R3030	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3032	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω
R3034	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3036	ERJ6GEYJ220	S.M.CARB	0.1W	5%	22Ω
R3037	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3038	ERD2FCG100	CARB	2W	2%	10Ω
R3039	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3040	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3041	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ
R3042	ERJ6GEYJ682	S.M.CARB	0.1W	5%	6K8Ω
R3043	ERD2FCG100	CARB	2W	2%	10Ω
R3044	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3045	ERJ6GEYJ471	S.M.CARB	0.1W	5%	470Ω
R3046	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3047	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω
R3048	ERJ6GEYJ102	S.M.CARB	0.1W	5%	1KΩ
R3049	ERJ6GEYJ680	S.M.CARB	0.1W	5%	68Ω
R3050	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3051	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3052	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3053	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3054	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3055	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3056	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3057	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3058	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ
R3059	ERJ6GEYJ153	S.M.CARB	0.1W	5%	15KΩ
R3060	ERJ6GEYJ470	S.M.CARB	0.1W	5%	47Ω
R3062	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3063	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3064	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3065	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R3066	ERJ6GEYJ104	S.M.CARB	0.1W	5%	100KΩ
R3067	ERJ6GEYJ273	S.M.CARB	0.1W	5%	27KΩ
R3068	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3069	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3070	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3071	ERJ6GEYJ470	S.M.CARB	0.1W	5%	47Ω
R3150	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3151	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3152	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3153	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3154	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ
R3155	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3156	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3157	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ
R3158	ERJ6GEYJ750	S.M.CARB	0.1W	5%	75Ω
R3502	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω

Ref No.	Part No.	Description			
R3504	ERJ6GEYJ101	S.M.CARB	0.1W	5%	100Ω
R3505	ERJ6GEY0R00	S.M.CARB	0.1W	5%	0Ω
R3508	ERJ6GEYJ183	S.M.CARB	0.1W	5%	18KΩ
R3511	ERJ6GEYJ103	S.M.CARB	0.1W	5%	10KΩ
R3512	ERJ6GEYJ472	S.M.CARB	0.1W	5%	4K7Ω
SWITCHES					
S801	ESB91232A	SWITCH			▲
S1201	EVQ23405R	SWITCH			
S1202	EVQ23405R	SWITCH			
S1203	EVQ23405R	SWITCH			
S1204	EVQ23405R	SWITCH			
S1205	EVQ23405R	SWITCH			
TRANSFORMERS					
T501	5270103200	TRANSFORMER			
T551	ZTFH44010A	F.B.T.			
T801	TLP8E1003	CHOPPER TRANSFORMER			
T1201	ETP35KAN61ZU	TRANSFORMER			
FILTERS					
X100	EFCA6R5MB3	FILTER			
X601	TSS2169-B	CRYSTAL			
X1201	TSS120M2	CRYSTAL			
X2101	4730007158	CRYSTAL			

SCHEMATIC DIAGRAM FOR MODEL TX-21AD3F (Euro-2 Chassis)

— IMPORTANT SAFETY NOTICE —

Components identified by  mark have special characteristics important for safety. When replacing any of these components, use only manufacturer's specified parts.

Notes

- RESISTOR
All resistors are carbon $\frac{1}{4}$ W resistor, unless marked as follows:
Unit of resistance is OHM (Ω) ($K=1,000$, $M=1,000,000$).
 - CAPACITORS
All capacitors are ceramic 50V, unless marked as follows:
Unit of capacitance is μF , unless otherwise stated.
 - COIL
Unit of inductance is μH , unless otherwise stated.
 - Components marked 'L' on the schematic diagram shows leadless parts.
 - TEST POINT
 Test Point Position
 - EARTH SYMBOL
 Chassis Earth Cold  Line Earth Hot
 - VOLTAGE MEASUREMENT
Voltage is measured by a DC voltmeter.
Measurement conditions are as follows:

Power source	AC 220V–240V, 50Hz
Receiving Signal	Colour Bar signal (RF)
All customer controls	Maximum position
 -  Indicates the video signal path
 -  Indicates the Audio signal path
 -  Indicates the Vertical/Horizontal path
 - This schematic diagram is the latest at the time of printing and is subject to change without notice.

Remarks

1. The Power Circuit contains a circuit area which uses a separate power supply to isolate the earth connection. The circuit is defined by HOT and COLD indications in the schematic diagram. All circuits, except the Power Circuit, are COLD. Take the following precautions:

Precautions


- a. Do not touch the hot part, or the hot and cold parts at the same time, as you are liable to a shock hazard.
 - b. Do not short-circuit the hot and cold circuits as electrical components may be damaged.
 - c. Do not connect an instrument, such as an oscilloscope, to the hot and cold circuits simultaneously, as this may cause fuse failure. Connect the earth of the instruments to the earth connection of the circuit being measured.
 - d. Make sure to disconnect the power plug before removing the chassis.


**ZEICHENERKLÄRUNG FÜR MODELL
TX-21AD3F
(Euro-2 Chassis)**

WICHTIGER SICHERHEITSHINWEIS


Teile, die mit einem Hinweis  gekennzeichnet sind, sind wichtig für die Sicherheit. Sollte ein Auswechseln erforderlich sein, sind unbedingt Originalteile einzusetzen.


Anmerkung





P-BOARD 
TNP8EP013





TNP8EB007

B-9

B-6

