# Panasonic<sub>®</sub>

17: 1 Motor Drive Zoom Lens AW-LZ17MD9 for AW-E800 Series

# Instructions

Before attempting to connect or operate this product, please read these instructions carefully and save this manual for future use.



We declare under our sole responsibility that the product to which this declaration relates is in conformity with the standards or other normative documents following the provisions of Directive EEC/89/336.

### **PREFACE**

Motor drive zoom lens AW-LZ17MD9 used with AW-E800 series color camera (2/3" 3CCD Bayonet mount remote control color camera).

## **INSTALLATION**

Rotate the lens fixing ring knob of camera counterclockwise and remove the lens mount cap. Mount the lens on the camera and rotate the lens fixing ring knob clockwise in order to fix the lens securely. Connect the camera cable to the IRIS connector on the back panel of the camera.

Connect the control cable to the lens I/F connector on the pan/tilt unit.

# To lens I/F connector on the pan/tilt unit To iris connector Control cable Camera cable Option CARD Opti

## **SPECIFICATION**

Focal Length: 9 - 153 mm, 17 times

Maximum Relative

Aperture: F1.9 (9 - 115 mm) - F2.6 (153 mm)

Image Size :  $\phi$ 11 mm (8.8 x 6.6 mm)

Iris: F1.9 - F16, CLOSE Servo or Manual

Zoom : Servo or Manual Focus : Servo or Manual

Focusing Range: 0.9 m (Macro:0.05m) - ∞

 Field of View :
 Wide
 Tele

 Horizontal :
 52°06′ - 3°18′

 Vertical :
 40°16′ - 2°28′

 Diagonal :
 62°51′ - 4°07′

Flangeback: 48.0 mm (±0.4 mm Adjustable)

Mount: 2/3" Bayonet Mount Filter (Flont frame) Size: M82 x 0.75 mm

Dimensions: 123 (W) x 120 (H) x 214 (D) mm

(with Hood)

[4-7/8" (W) x 4-3/4" (H)

x 8-7/16" (D)]

Weight: 1.3 kg (2.87 lbs) (without Hood)

Finish: Black

Input Voltage: +12 V DC Current Consumption: 410 mA Max.

Iris Operating Time : Approx. 2 s (Full Travel)
Zoom Operating Time : Approx. 3 s (Full Travel)
Focus Operating Time : Approx. 3 s (Full Travel)
Camera Connector : HR10A-10P-12P, HIROSE
Control Connector : HR10A-10P-12S, HIROSE

Weight and dimensions shown are approximate. Specifications are subject to change without notice.

NOTE: Refer to the operating instructions of AW-E800 series for details.



# PANASONIC BROADCAST & DIGITAL SYSTEMS COMPANY DIVISION OF MATSUSHITA ELECTRIC CORPORATION OF AMERICA

Executive Office: 3330 Cahuenga Blvd W., Los Angeles, CA 90068

(323) 436-3500

EASTERN ZONE: One Panasonic Way 4E-7, Secaucus, NJ 07094 (201) 348-7621

Mid-Atlantic: One Panasonic Way 4E-7, Secaucus, NJ 07094 (201) 348-7621

Southeast Region: 1225 Northbrook Parkway, Ste 1-160 Suwanee, GA 30024

(770) 338-6845

 Central Region:
 1707 N Randall Road E1-C-1, Elgin, IL 60123 (847) 468-5200

 WESTERN ZONE:
 3330 Cahuenga Blvd W., Los Angeles, CA 90068 (323) 436-3500

 Dallas Region:
 6226 Abington Way, Houston, TX 77008 (713) 802-2726

 Government Marketing Department:
 52 West Gude Drive, Rockville, MD 20850 (301) 738-3840

PANASONIC CANADA INC.

5770 Ambler Drive, Mississauga, Ontario, L4W 2T3 (905) 238-2115

PANASONIC SALES COMPANY

DIVISION OF MATSUSHITA ELECTRIC OF PUERTO RICO, INC.

San Gabriel Industrial Park, 65th Infantry Ave., KM9.5 Carolina, Puerto Rico 00630 (809) 750-4300

# Matsushita Electric Industrial Co., Ltd.

Central P.O. Box 288, Osaka 530-91, Japan

NM1199-0 7J1A431A