




CAUTION

THE STRIPED FRAME INDICATES THE PRIMARY CIRCUIT TO DISTINGUISH THE PRIMARY FROM THE SECONDARY CIRCUIT.  
PAY ATTENTION NOT TO RECEIVE AN ELECTRIC SHOCK DURING REPAIR AND SERVICE OF THE PRODUCTS.

(R) :TO POWER SUPPLY/RF SECTION  
(S) :TO SYSTEM CONTROL & SERVO SECTION  
(T) :TO TIMER SECTION



IMPORTANT SAFETY NOTICE:  
COMPONENTS IDENTIFIED WITH THE MARK  HAVE THE SPECIAL CHARACTERISTICS FOR SAFETY.  
WHEN REPLACING ANY OF THESE COMPONENTS,USE ONLY THE SAME TYPE.

NOTE1:WHEN MEASURE THE VOLTAGE OR WAVEFORM ON THE POWER TRANSFORMER  
CIRCUIT,SET THE GND TERMINAL OF MEASURING POINT AS FOLLOWS.  
PRIMARY SIDE.....   
SECONDARY SIDE... 

NOTE2:THE DC VOLTAGE INDICATED IN PRIMARY SIDE IS SHOWN THE VOLTAGE WHEN  
INPUT AC IS 240V.

NOTE:DO NOT USE ANY PART NUMBER SHOWN ON THIS SCHEMATIC DIAGRAM FOR  
ORDERING.WHEN YOU ORDER A PART,PLEASE REFER TO PARTS LIST.  
NOTE:THE MEASUREMENT MODE OF THE DC VOLTAGE ON THIS DIAGRAM IS STOP MODE.

NV-HS825F  
POWER TRANSFORMER  
SECTION IN MAIN  
SCHEMATIC DIAGRAM