



[illegible]

[illegible]



POWER		INPUT CONDITION					Video Output Result LA73021 setting										Audio Output Results AN3655 settings						Mute signals					
		AV2 SELECT	TV/EE/ VTR	DVR/ MODE	OSD ON(H)	RGB	DVD	INPUT CH	AV2 PB(H)	AV1 PB(H)	AV2 OUT	V-DECSL	AV1-8 out	RGB OFF(H)	D/D(L)	V-INSEL	YC- INSEL	YC INPUT	YC-out OUT	AV1 OUT	AV2 OUT	RF (G)	REC/ PB	Input Select	AV1 output Select	AV2 output Select	Mute (H)	A-Mute (H)
Function menu		AV link		Function menu		AV2-8 in																				not used		

Remark:

NO.TU

C+TU

RGW SW

RGW SW

EE

VV

INSEL

\*1[L]

\*2[H\*] / \*6[M/H]

\*3

\*4

\*5[M/H]

\*6[M/H]

\*7[M/H]

Tuner position, DECODER OFF (e.g. ARD)

Tuner position, DECODER ON (e.g. PREMI)

OFF = HIGH

ON = LOW

Non-Playback signal

Playback signal

Inputselect= Audio Output signal from AN3655 at Line Out

In case of Personal Planner standby(not External Link), AV1 PB must not output 'M' or 'H'

AV2 PB must not output 'M' or 'H' if AV2 PB IN is 'M' or 'H'.

In case of EXT LINK (1/2) mode or normal REC from AV2 AV2 PB(H) should be low,

In case of ex. EXTLINK (1/2) mode or normal REC AV2follow the result of DVD.

In case of EXT LINK (1/2) mode AV2 PB(H) should be low, in case of ex. EXTLINK (1/2) follow the result of DVD.

State of AV PB should be decided by 16:9 information from DVD.

State of AV2PB output should be decided by distinction of PB CTL.

State of AV1PB output should be decided by result of AV2PB input.