

NOTE:
PARTS ENCLOSED IN DASHED LINES MARKED "Z" ARE NOT USED.

KEY MATRIX CHART


OUT IN	SCAN 1 PIN 104	SCAN 2 PIN 105
DATA 8 PIN 102	—	REC /TIME
DATA 9 PIN 8	—	REW
DATA 10 PIN 9	—	FF
DATA 11 PIN 10	CH DOWN	POWER
DATA 12 PIN 11	VCR/TV	CH UP
DATA 13 PIN 12	STOP /EJECT	PLAY



NOTE:
FOR SCHEMATIC DIAGRAM AND CIRCUIT BOARD LAYOUT NOTES,
REFER TO BEGINNING OF SCHEMATIC SECTION.



IC3001 VIDEO/AUDIO PROCESS IC-DETAIL BLOCK DIAGRAM, HA118421ASNF




MAIN III (OPERATION) SCHEMATIC DIAGRAM

NOTE:
FOR SCHEMATIC DIAGRAM AND CIRCUIT BOARD LAYOUT NOTES,
REFER TO BEGINNING OF SCHEMATIC SECTION.

COMPARISON CHART
OF MODELS & MARKS


MODEL	MARK
PV-VS4821	A
PV-VS4821-K	B
Not Used	Z



LINK TO VOLTAGE CHART

UNLESS OTHERWISE SPECIFIED;
SWITCHES IS EVQ11A09K.
PNP TRANSISTORS IS 2SB709A,
NPN TRANSISTORS IS 2SD601A AND

NOTE:
FOR SCHEMATIC DIAGRAM AND CIRCUIT BOARD LAYOUT NOTES,
REFER TO BEGINNING OF SCHEMATIC SECTION.





MAIN V (POWER SUPPLY) SCHEMATIC DIAGRAM

NOTE: PARTS ENCLOSED IN DASHED LINES MARKED "Z" ARE NOT USED.

NOTE: FOR SCHEMATIC DIAGRAM AND CIRCUIT BOARD LAYOUT NOTES, REFER TO BEGINNING OF SCHEMATIC SECTION.

CAUTION: FOR CONTINUED PROTECTION AGAINST FIRE HAZARD, REPLACE ONLY WITH THE SAME TYPE 1.6A 125/250V FUSE.
ATTENTION: POUR UNE PROTECTION CONTINUE LES RISQUES D'INCENDIE N'UTILISER QUE DES FUSIBLES DE MÊME TYPE 1.6A 125/250V

IMPORTANT SAFETY NOTICE: COMPONENTS IDENTIFIED BY THE SIGN  HAVE SPECIAL CHARACTERISTICS IMPORTANT FOR SAFETY. WHEN REPLACING ANY OF THESE COMPONENTS, USE ONLY THE SPECIFIED PARTS.



MAIN VI (ADVANCE) SCHEMATIC DIAGRAM

NOTE:
PARTS ENCLOSED IN DASHED LINES MARKED "Z" ARE NOT USED.

NOTE:
FOR SCHEMATIC DIAGRAM AND CIRCUIT BOARD LAYOUT NOTES,
REFER TO BEGINNING OF SCHEMATIC SECTION.

