System Features	Operation Procedures	
	·	

Please use this Operating Instructions Manual for basic operations. Refer to the Electronic Modular Switching System (EMSS) Control Unit Manual for additional features.

## **Notice**

A series of the beep tone may sound periodically when the MEMORY switch is set to the "PROGRAM". This is a normal condition.

PANUG-001-

Panasonic Company Division of Matsushita Electric Corporation of America

One Panasonic Way, Secaucus, New Jersey 07094

Panasonic Company (West) of America Division of Matsushita Electric Corporation of America

6550 Katella Avenue, Cypress, California 90630

Panasonic Sales Company ("PSC")
Division of Matsushita Electric of Puerto Rico, Inc.

San Gabriel Industrial Park, 65th Infantry Avenue, KM 9.5, Carolina, P.R. 00630

## **Panasonic**

## MODEL NO. **KX-T7020 Operating Instructions**

Making Calls			
Press the SP-PHONE button or lift the handset first.			
Feature Description		Operation Procedures	
Intercom Calling	Dials from station to station within the system.	extension number or DSS	
Individual Line Access	Selects any CO line directly.	phone number	
Automatic Line Access	Selects an unoccupied CO line automatically.	9 phone number	
System Speed Dialing	Dials the stored phone number by following simple operation.	AUTO DIAL access code	
One-Touch Dialing	Dials the stored number by pressing only one button.	Programming:  1. Set the memory switch to "PROGRAM".  2. Faccess number phone number AUTO DIAL STORE  3. The memory switch must be adjusted so that it is in the "SET" position.	
When a Line is Busy			
Automatic Call Back Busy (Camp-on)	Receives a notice that the busy line becomes free.	Outside Calls:  CO Hear à busy tone  Hang up	
(Camp-on)		extension number busy tone 6 Hang up	
Redial	Redials the last number dialed. Automatic redial can work in upgraded systems.	SP-PHONE or Lift the handset	