



CFS10A: 10 MHz OXCO Frequency Reference

CFS10A Front View



CFS10A Rear View



Key Features

- 10 MHz Output, +13 dBm
- Oven Controlled Crystal Oscillator
- Very Low Phase Noise
- Low Aging of 2×10^{-10} / day
- High Thermal Stability of 5×10^{-10} (0 to 50 °C)
- Low 1 second Allan Variance of 2×10^{-12}
- 19" Rack mount Case
- Many Options Available
- CE Marked

General Description

The CFS10A is a 10 MHz frequency reference which offers excellent performance for virtually any frequency or timing application. It is ideal for instrumentation and communication systems which require a precise frequency reference. The CFS10A is supplied in a 19" rack mount case and is powered from a 115 / 230 VAC power supply.

A number of options allow the CFS10A to be customized to meet specific requirements. Aging, phase noise, thermal stability and operating temperature can all be separately specified, so you only need to pay for the performance you require.

Other options such as a DC power input, multiple isolated 10 MHz outputs and squarewave outputs are also available.

Applications

The CFS10A is already used by a leading UK telecommunications company to synchronize their automatic satellite communication system.

Miscellaneous Information

The CFS10A is a highly reliable unit. It is housed in a fully screened aluminum 19 inch case aluminum case and operates from a 115 VAC or 230 VAC supply. The CFS10A is CE marked for sale within the EEC.

CFS10A SPECIFICATIONS

Specification Parameter	Specification
Frequency	10.000000 MHz
Output level	+13 dBm into 50 Ω
Output Waveform	Sinewave. 2 nd Harmonic < -45 dBc. Other harmonics < -60 dBc
Accuracy at shipment	< 1 x 10 ⁻¹⁰ (0.0001 ppm)
Frequency Stability (0 to 50 °C)	± 2 x 10 ⁻⁹ standard. ± 5 x 10 ⁻¹⁰ optionally available
Frequency Stability (-20 to 70 °C)	± 2 x 10 ⁻⁹ . This temperature range is an option.
Aging (per day)	< 1 x 10 ⁻⁹ standard. < 2 x 10 ⁻¹⁰ optionally available
Allan Variance (1s)	< 1 x 10 ⁻¹¹ standard. < 2 x 10 ⁻¹² optionally available
Phase Noise 10 Hz	< -120 dBc/Hz standard. < -130 dBc optionally available
Phase Noise 100 Hz	< -150 dBc/Hz
Phase Noise 1 kHz	< -155 dBc/Hz
Power (AC)	115 VAC or 230 VAC ± 10%. Power 25 Watts max
Size	483 mm x 88 mm x 180 mm. Width x Depth x Height
Weight	4 kg
Ambient Operating Temperature	-10°C to +50 °C
Options Available	DC Power Input. Multiple Frequency Outputs. Different Frequency Outputs. Squarewave Outputs. Redundancy. IRIG timing outputs.

Precision Test Systems			
Head Office - UK	South Africa	USA	Represented locally by:
Precision Test Systems LTD 40 Holkham Avenue, South Woodham Ferrers Essex, CM3 7AU, England Tel: +44 (0) 845 052 0920 Fax: +44 (0) 870 135 4973 Email: uksales@ptsyst.com Web: www.ptsyst.com	Precision Test Systems cc 183 Edison Crescent Hennops Park X7 Pretoria South Africa Tel: +27 (0) 12 653 5848 Email: sasales@ptsyst.com Web: www.ptsyst.com	Precision Test Systems Suite # 981 14781 Memorial Dr. Houston, TX 77079 Tel: 1 888 876 4804 Fax: 1 413 410 1112 Email: usasales@ptsyst.com Web: www.ptsyst.com	

Full specifications available from www.ptsyst.com. Specifications and features subject to change without notice (200904)