



weight 198 oz (7g)

CHARACTERISTICS

NOMINAL IMPEDANCE	50 Ω
FREQUENCY RANGE	0-2 GHz
TEMPERATURE RATING	-65/+165 °C
VSWR	1.30 Max
RF INSERTION LOSS	- fF dB Maxi
VOLTAGE RATING	335 Vrms Maxi
DIELECTRIC WITHSTANDING VOLTAGE	1000 Vrms mini
INSULATION RESISTANCE	5000 Mo mini
HERMETIC SEAL	NA cc/s - Atm.cm3/s
LEAKAGE (pressurized only)	NA psi - MPa
-	-
-	-

PACKAGING

Standard	Unit	Other-
100	'W' option	Contactus

CABLE RETENTION	NA	Lb mini N
CENTER CONTACT RETENTION		
Axial force - mating end	3.30	Lb mini N
Axial force - opposite end	NA	Lb mini N
Torque (Min)	NA	Inch.oz cm.N
RECOMMENDED TORQUES		
Mating	6.888	Inch. Lb cm.N
Panel nut		Inch. Lb cm.N
Clamp nut		Inch. Lb cm.N

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	NICKEL
OUTER CONTACT	-	-
CENTER CONTACT	BRASS	GOLD
INSULATORS	PTFE	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
02	02-04-005	ASOUT OPTION W/ + COND 100		
04-07	03-08-017		BERTHET	11-01-94
A			VIGNARD	23-09-92

Initiated on	11-MAR-92	The information given here is subject to change without notice. Design changes may be in order to improve the product.
Superseded on	23-09-92	

