



weight 0.612 oz ( 17.5 g)

cables:

**CHARACTERISTICS**

NOMINAL IMPEDANCE	75 $\Omega$
FREQUENCY RANGE	0 - 1 GHz
TEMPERATURE RATING	-40/+85 °C
VSWR	1.22 Max
RF INSERTION LOSS	NA /F dB Maxi
VOLTAGE RATINGS	330 Vras Maxi
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vras mini
INSULATION RESISTANCE	5000 Ma mini
HERMETIC SEAL	NA cc/s Atm.cm3/s
LEAKAGE (pressurized only)	NA psi MPa
-	-
-	-

**STANDARDISATION**

**CABLE RETENTION**

NA Lb mini  
N

**CENTER CONTACT RETENTION**

Axial force - mating end

9 Lb mini  
40 N

Axial force - opposite end

NA Lb mini  
N

Torque (Min)

NA Inch.oz  
cm.N

**RECOMMENDED TORQUES**

Mating

NA Inch.Lb  
cm.N

Panel nut

NA Inch.Lb  
cm.N

Clamp nut

NA Inch.Lb  
cm.N

**CONSTRUCTION**

CONNECTOR PARTS	MATERIALS	FINISH
HALF-BODY	ZINC ALUMINIUM ALLOY	NICKEL
HALF-BODY	BRASS	NICKEL
OUTER CONTACT	BRONZE	GOLD
CENTER CONTACT	BRASS	GOLD
INSULATORS	PTFE + POLYPROPYLENE	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE

Initiated on 07-FEB-90

The information given here is subject to change without notice. Design changes may be in order to improve the product.



Superseded on -----