



WEIGHT oz (g)

Cable:

CHARACTERISTICS

NOMINAL IMPEDANCE	50 Ω
FREQUENCY RANGE	0-4 GHz
TEMPERATURE RATING	-65/+165 °C
VSWR	AD Max
RF INSERTION LOSS	AD \sqrt{f} dB Maxi
VOLTAGE RATING	500 Vrms Maxi
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms mini
INSULATION RESISTANCE	5000 M Ω mini
HERMETIC SEAL	NA cc/s Atm.cm ³ /s
LEAKAGE (pressurized only)	NA psi MPa
-	-
-	-

STANDARDISATION	CECC	22120/BNC
	CEI	169-8/BNC
	MIL	M39012/BNC
	NF	C93-564/KBN

CABLE RETENTION	8.8 Lb mini
	40 N

CENTER CONTACT RETENTION

Axial force - mating end	5.95 Lb mini
	27 N
Axial force - opposite end	5.95 Lb mini
	27 N
Torque (Min)	NA Inch.oz cm.N

RECOMMENDED TORQUES

Mating	NA Inch. Lb cm.N
Panel nut	NA Inch. Lb cm.N
Clamp nut	NA Inch. Lb cm.N

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	NICKEL
OUTER CONTACT	BRASS	NICKEL
CENTER CONTACT	BRASS	GOLD
INSULATORS	PTFE	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
.
.
.
.

Initiated on 13-AUG-90

The information given here is subject to change without notice. Design changes may be in order to improve the product.



Superseded on

perez