



MOUNTING HOLE

WEIGHT oz ( g)

cables:

CHARACTERISTICS

NOMINAL IMPEDANCE	NA	Ω	STANDARDISATION	
FREQUENCY RANGE	NA	GHz		
TEMPERATURE RATING	-	°C		
VSWR	NA	Max		
RF INSERTION LOSS	NA	dB Max	CABLE RETENTION	NA Lb Min N Min
VOLTAGE RATING	NA	Vrms	CENTER CONTACT RETENTION	
DIELECTRIC WITHSTANDING VOLTAGE	NA	Vrms	Axial force - mating end	NA Lb Min N Min
INSULATION RESISTANCE	NA	MΩ	Axial force - opposite end	NA Lb Min N Min
HERMETIC SEAL	NA	cc/s cm <sup>3</sup> /s	Torque (Min)	NA inch.oz cm.N
LEAKAGE (pressurized only)	-	psi kg/cm <sup>2</sup>	RECOMMENDED TORQUES	
-	-	-	Mating	NA inch.Lb cm.N
-	-	-	Panel nut	NA inch.Lb cm.N
-	-	-	Clamp nut	NA inch.Lb cm.N

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
METAL GASKET	Light alloy	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
.	.	.	.	.
.	.	.	.	.
.	.	.	.	.
.	.	.	.	.

Initiated on 06-MAR-90  
Superseded on ---

The information given here is subject to change without notice. Design changes may be in order to improve the product.

